

furnished with hook and eye fastenings and back do.—
 The entrance doors to be two inch four panel mould
 and bead butt with panes over hung with 4 inch butt
 hinges and provided with 8 inch 3 bolt iron rim, brass
 nob locks, rose and thumb socket, 12 inch top and
 bottom barrel bolts, 1 inch headed jamb linings and com-
 plete. The room doors to be 2 inch 4 panel mould both
 sides hung with 6 1-2 inch butts in 1-2 inch double re-
 bedded jamb linings with inch framed grounds splayed to
 receive the plastering, and provide with good 7 inch iron
 rim brass nob locks and single faced architraves both
 sides. Fix staff heads to all the chimney breasts. The
 stairs to commence with a bold curtain and to be 1 1-2
 inch clear steps and risers with bold nosings on pine
 treads housed into a two inch framed string with a
 3-4 return bead stick on the lower edge and 1 2 inch
 headed capping on the top; 2 1-2 inch square framed
 cherry wood handrail with scrole and newels, 1-4 inch
 plate balusters, two to each step introducing a sufficient
 number of iron balusters to effectually strengthen the
 railing. The skirting to be scribed to the steps
 and 3-4 lining with rounded nosing to well hole of
 stairs. Fix a two inch wrought and moulded shelf or
 sloped brackets to kitchen fire place. Provide and fix
 a red and blue glass door fronts the light of the story
 where shown on the plan including four tier of shelving;
 the door to be hung in two heights with 3 inch butts and
 provided with 7 inch iron rim bolts. Provide neat
 wood chimney pieces to all the fire places.

Plastering.—The plastering will be done in the
 rooms to be plastered in the following manner:—
 1. All the walls to be plastered with 3 coats of
 plaster, the entire thickness to be 3 inches of each
 coat, 2 coats of lime and 1 coat of sand.

Plastering.—Rough plastering to be done in the
 rooms to be plastered in the following manner:—
 1. All the walls to be plastered with 3 coats of
 plaster, the entire thickness to be 3 inches of each
 coat, 2 coats of lime and 1 coat of sand.

Painting.—The walls of the rooms to be painted in the
 following manner:—
 1. All the walls to be painted with 3 coats of
 paint, the entire thickness to be 3 inches of each
 coat, 2 coats of lime and 1 coat of sand.