

Longitudinal Modulus.—The longitudinal modulus $\frac{I}{y}$ is the moment of inertia I of the midship section about the neutral axis divided by the distance y measured from the neutral axis to the top of the strength deck beam at side, calculated in way of openings but without deductions for rivet holes. Areas are measured in square inches and distances in feet.

Below the strength deck, all continuous longitudinal members other than such parts of under deck girders as are required entirely for supporting purposes, are included. Above the strength deck, the gunwale angle bar and the extension of the sheerstrake are the only members included.

The required longitudinal modulus for effective material is expressed by f.d.B., where f is the factor obtained from the following table:—

L.	f.	L.	f.
100	1.80	360	9.40
120	2.00	380	10.30
140	2.35	400	11.20
160	2.70	420	12.15
180	3.15	440	13.10
200	3.60	460	14.15
220	4.20	480	15.15
240	4.80	500	16.25
260	5.45	520	17.35
280	6.20	540	18.45
300	6.95	560	19.60
320	7.70	580	20.80
340	8.55	600	22.00

For intermediate lengths, the value of f is determined by interpolation.

This formula applies where L does not exceed 600 feet;

B is between $\frac{L}{10} + 5$ and $\frac{L}{10} + 20$, both inclusive, and $\frac{L}{D_s}$ is between 10 and 13.5, both inclusive.

Frame.—For the purpose of the frame modulus, the frame is regarded as composed of a frame angle and a reverse angle each of the same size and thickness.

Frame Modulus.—The modulus $\frac{I}{y}$ of the midship frame below the lowest tier of beams is the moment of inertia I of the frame section about the neutral axis divided by the distance y measured from the neutral axis to the extremity of the frame section, calculated without deduction for rivet and bolt holes. The modulus is measured in inch units.