

- (l) An airtight receptacle containing one kilogramme (equivalent to two pounds) of provisions for each person.
- (m) A watertight receptacle provided with a dipper with lanyard containing one litre (equivalent to one quart) of fresh water for each person.
- (n) At least one dozen self-igniting "red lights" and a box of matches in watertight containers.
- (o) Half a kilogramme (equivalent to one pound) of condensed milk for each person.
- (p) A suitable locker for the stowage of the small items of the equipment.
- (q) Any boat which is certified to carry 100 or more persons shall be fitted with a motor and shall comply with the requirements of Regulation XXVII.

A motor lifeboat need not carry a mast or sails or more than half the complement of oars, but it shall carry two boathooks.

Decked lifeboats shall have no plug-hole, but shall be provided with at least two bilge-pumps.

In the case of a ship which carries passengers in the North Atlantic north of 35° North Latitude, only a proportion of the boats, to be fixed by the Administration, need be equipped with masts and sails, and only one-half of the quantity of condensed milk need be carried.

2. Where the number of lifeboats carried on a ship is more than 13, one shall be a motor boat, and where the number is more than 19, two shall be motor boats. These motor lifeboats shall be fitted with a wireless telegraph installation and a searchlight.

The wireless telegraph installation shall comply with conditions as to range and efficiency to be decided by each Administration.

The searchlight shall include a lamp of at least 80 watts, an efficient reflector and a source of power which will give effective illumination of a light coloured object over a width of about 18 metres (60 feet) at a distance of 180 metres (200 yards) for a total period of six hours, and it shall be capable of working for three hours continuously.

Where the power for the wireless equipment and the searchlight are derived from the same source, this shall be sufficient to provide for the adequate working of both appliances.

3. The normal equipment of every approved life raft shall consist of—

- (a) Four oars.
- (b) Five rowlocks.
- (c) A self-igniting lifebuoy light.
- (d) A sea-anchor.
- (e) A painter.
- (f) A vessel containing four and a half litres (equivalent to one gallon) of vegetable or animal oil. The vessel shall be so constructed that the oil can be easily distributed on the water, and so arranged that it can be attached to the sea-anchor.
- (g) An airtight receptacle containing one kilogramme (equivalent to two pounds) of provisions for each person.
- (h) A watertight receptacle provided with a dipper with lanyard containing one litre (equivalent to one quart) of fresh water for each person.
- (i) At least one dozen self-igniting red lights and a box of matches in watertight containers.