

Summary of Canadian Steel Industry Operations¹⁾

	Imperial (inches)		Metric (mm)	
Hollow Structural Sections:	Diameter	Wall	Diameter	Wall
Round				
Dofasco (Prudential)	2 3/8-10 ³ / ₄	0.095-0.5	60.3-273	2.4-13
IPSCO	1.05-16	0.1-0.5	27-406	2.5-13
Stelco	1.25-16	0.1-0.5	32-406	2.5-13
Square	Width		Width	
Dofasco (Prudential)	2-8	0.095-0.5	50.8-203	2.4-13
Ipsco	1-10	0.083-0.5	25-254	2-13
Stelco	1-12	0.10-0.5	25-305	2.5-13
Rectangular	Width × Height		Width × Height	
Dofasco (Prudential)	2.5 × 1.5-10 × 6	0.095-0.5	63 × 38-254 × 15	2.4-13
IPSCO	1 × 2-8 × 12	0.083-0.5	25 × 51-203 × 305	2-13
Stelco	1 × 2-8 × 12	0.10-0.5	25 × 51-203 × 305	2.5-13
	Weight per Yard		Weight per Metre	
Rails:				
Algoma	up to 136 lbs.		up to 67.6 kg	
Sydney Steel Corp.	75 to 136 lbs.		37.3 to 67.6 kg	
	Outside Diameter	Wall	Outside Diameter	Wall
Pipe and Tube:				
Welded				
Dofasco (Prudential)	2 3/8-10 ³ / ₄	0.083-0.50	60.3-273	2.1-12.7
IPSCO	1.05-80	0.083-0.540	21.3-2032	2.11-13.7
Sidbec-Dosco	0.84-6.625	0.1-0.3	21.3-168.3	2.5-7.6
Stelco	0.405-60	0.068-1.125	10.3-1524	1.73-28.58
Seamless				
Algoma	2 3/8 to 12 ³ / ₄	0.126-1.5	60.3-324	3.17-38.1
Other Products:				
(refer to Corporate Reports, pages 8 to 42)				