



930 Series Gurney Hot Water Boiler

Make due allowance for mains and risers when selecting size of boiler required.

When soft coal or wood is used as fuel, select a size larger boiler than for hard coal.

Direct-indirect radiation requires 50% more boiler capacity. Indirect radiation requires 75% increased boiler capacity.



No.	List Price	Capacity, Feet*	Equivalent in 1-inch Pipe	Height of Flow, Inches	Width, Inches	Length, Inches	Grate, Inches	Flow, Inches	Return, Inches	Approximate Shipping Weight	Smoke Out- let, Inches	Size of Flue Required, Inches
934W	\$450.00	2,000	6,000	64	44	42	30×28	2-5	2-5	3,200	12	12×12
935W	525.00	2,500	7,500	64	44	51	30×37	2-5	2-5	3,700	12	12×12
936W	600.00	2,975	8,925	64	44	60	30×46	2-5	2-5	4,400	12	12×16
937W	675.00	3,500	10,500	64	44	68	30×54	3-5	3-5	5,000	12	12×16
938W	750.00	3,900	11,700	64	44	77	30×63	3-5	3-5	5,600	12	16×10
939W	812.50	4,450	13,350	64	44	85½	30×72	3-5	3-5	6,300	12	16×16

* See Page 2.