

- (vi) a mast or masts, with galvanised wire stays together with sails (coloured orange);
- (vii) an efficient compass in binnacle, to be luminised or fitted with suitable means of illumination;
- (viii) a life-line becketed round the outside of the lifeboat;
- (ix) a sea-anchor of approved size;
- (x) two painters of sufficient length. One shall be secured to the forward end of the lifeboat with strop and toggle so that it can be released, and the other shall be firmly secured to the stem of the lifeboat and be ready for use;
- (xi) a vessel containing one gallon (or four and half litres) of vegetable, fish or animal oil. The vessel shall be so constructed that the oil can be easily distributed on the water, and so arranged that it can be attached to the sea-anchor;
- (xii) an air-tight receptacle containing two pounds (or one kilogramme) of provisions for each person;
- (xiii) one pound (or half a kilogramme) of condensed milk or its equivalent for each person;
- (xiv) water-tight receptacles containing three quarts (or three litres) of fresh water for each person; a dipper with lanyard;
- (xv) two parachute signals of approved type capable of giving a bright red light at a high altitude; six hand flares of an approved type giving a bright red light;
- (xvi) two buoyant smoke signals of an approved type (for day-time use) capable of giving off a volume of orange-coloured smoke;
- (xvii) approved means to enable persons to cling to the boat should it be upturned, in the form of bilge keels or keel rails, together with grab lines secured from gunwale to gunwale under the keel, or other approved arrangements;
- (xviii) an approved first aid outfit in a watertight case,
- (xix) an electric torch suitable for morse-signalling together with two spare batteries and two spare bulbs;
- (xx) a daylight-signalling mirror of an approved type;
- (xxi) a jack-knife fitted with a tin opener to be kept attached to the boat with a lanyard;
- (xxii) two light buoyant heaving lines;
- (xxiii) a manual pump of an approved type; and
- (xxiv) a suitable locker for stowage of small items of equipment.

(b) In the case of ships engaged on voyages of such duration that in the opinion of the Administration concerned the items specified in subparagraphs (vi), (xii), (xiii), (xx) and (xxi) of paragraph (a) of this Regulation are unnecessary, the Administration may allow them to be dispensed with.

(c) Notwithstanding the provisions of paragraph (a) of this Regulation, motor lifeboats or other approved mechanically propelled lifeboats need not carry a mast or sails or more than half the complement of oars, but they shall carry two boat hooks.

(d) All lifeboats certified to carry more than 60 persons shall be fitted with suitable means to enable persons in the water to climb into the lifeboat.