AIT SPECIFICATION - Globe GC-lA, GC-lB Page 3 o	GC-1A	A-766-2 GC-1B
Engine and Engine Accessories - Fuel and Oil System 102. Cabin air heater 103. Oil radiator 104. Starter - Delco Remy 1109656 105. Two engine-driven fuel pumps (Upper AC10538-III or Continental 40585-III,	2 lbs. (-15) 2 lbs. (-11) 4 lbs. (-13) 16 lbs. (-8) 4 lbs. (-26)	=
lower Continental 40452) 106. Carburetor air filter 107. Carburetor air heater 108. Oil radiator (Harrison 3875) (Required when item 4 installed)	<u>x</u>	1 lb. (-19) 4 lbs. (-13)
109. Starter - Delco Remy A-40098 110. Engine-driven fuel pump (AC1523066) 111. Wobble pump (Air Corps Type D-2)		15 lbs. (-7) 2 lbs. (-33) 3 lbs. (+34)
Landing Gear and Floats 201. 6.00-6 wheels and brakes (Goodyear L6H/LBD) or LF6H/LBD) with 6.00-6 tires (4-ply) and tubes 202. 6x2.00 tail wheel, tire and fork (Scott) 203. Tail wheel steering mechanism	31 lbs. (+24) 4 lbs. (+179) 2 lbs. (+170)	31 lbs. (+24) 4 lbs. (+179) 2 lbs. (+170)
Electrical and Radio Equipment 301. Battery - 12 volt, 24 amp. hr., 5 hr. rate 302. Engine-driven generator (Delco-Remy 1101876) 303. Hydraulic system energizer (Adel model M-15668) 304. Two-way radio (General Electric AS-1B) 305. Engine-driven generator (Delco-Remy A-40435)	6 lbs. (-3) 12 lbs. (+16)	6 lbs. (-4) 6 lbs. (-3) 12 lbs. (+16) 10 lbs. (-7)

- NOTE 1. A weight and balance report including list of equipment included in certificated weight empty, and loading instructions when necessary, must be submitted for each airplane with original inspector's report and each subsequent report covering change in equipment.
- NOTE 2. Placard instrument panel:
 - (a) "INTENTIONAL SPINS PROHIBITED."
 - (b) "DO NOT LOWER LANDING GEAR ABOVE 100 MPH."
- NOTE 3. (Deleted September 25, 1946)

Charles F. Dicery Director Aircraft and Components Service

Copies of this specification may be obtained upon application to: Office of Aviation Information, Civil Aeronautics Administration, Department of Commerce, Washington 25, D. C.