

TABLE OF CONTENTS (Continued)

<u>Section</u>	<u>Title</u>
6.3	ESM Payload
6.3.1	Requirements of the Paxisat EM Antenna/Receiver System
6.3.2	Available Receiver Approaches
6.3.2.1	Crystal Video Receiver (CVR)
6.3.2.2	Instantaneous Frequency Measurement (IFM)
6.3.2.3	Superheterodyne Receiver
6.3.2.4	Compressive (Microscan) Receiver
6.3.2.5	Channelized Receiver
6.3.2.6	Acousto-Optic Bragg Cell Receiver
6.3.2.7	Digital Fast Fourier Transform (FFT)
6.3.2.8	Available Receiver Approaches - Summary of Characteristics
6.3.2.9	Some Possible Receiver Combinations
6.3.3	Receiving Subsystem Proposed for Paxisat
6.3.4	Receiver Antenna Configuration for Paxisat
6.3.5	Summary of Proposed EM Receiving Subsystem Performance Capabilities
7.0	A CONCEPTUAL PAXSAT SPACECRAFT DESIGN
7.1	Introduction
7.2	Configuration
7.2.1	Requirements
7.2.2	General Arrangement
7.2.3	Orientation in Flight During Stand-Off Observation
7.2.4	Orientation in Flight During Maneuvers
7.2.4.1	Out-of-Plane Maneuver
7.2.4.2	In-Plane Maneuver