

c/ The summer period shall begin no later than 1 May and shall not end before 30 September. For member States with arctic conditions the summer period shall begin no later than 1 June and not end before 31 August and the RVP is limited to 70 kPa.

d/ Except for regular unleaded petrol (minimum motor octane number (MON) of 81 and minimum research octane number (RON) of 91), for which the maximum olefin content shall be 21% v/v. These limits shall not preclude the introduction on the market of a member State of another unleaded petrol with lower octane numbers than set out here.

e/ Other mono-alcohols with a final distillation point no higher than the final distillation point laid down in national specifications or, where these do not exist, in industrial specifications for motor fuels.

Note: Parties shall ensure that, no later than 1 January 2000, petrol can be marketed within their territory only if it complies with the environmental specifications set out in table 8. Where a Party determines that banning petrol with a sulphur content which does not comply with the specifications for sulphur content in table 8, but does not exceed the current content, would raise severe difficulties for its industries in making the necessary changes in their manufacturing facilities by 1 January 2000, it may extend the time period of marketing within its territory until 1 January 2003 at the latest. In such a case the Party shall specify, in a declaration to be deposited together with its instrument of ratification, acceptance, approval or accession, that it intends to extend the time period and present written information on the reason for this to the Executive Body.

**Table 9. Environmental specifications for marketed fuels
to be used for vehicles equipped with compression-ignition engines**

Type: Diesel fuel

Paramètre	Unité	Limits a/		Test	
		Minimum	Maximum	Méthod b/	Date of publication
Cetane number		51	-	EN-ISO 5165	1992
Density at 15°C	kg/m ³	-	845	EN-ISO 3675	1995
Distillation point: 95%	C	-	360	EN-ISO 3405	1988
Polycyclic aromatic hydrocarbons	% m/m	-	11	IP 391	1995
Sulphur content	mg/kg	-	350	project EN-ISP/ DIS 14596	1996

a/ The values quoted in the specification are 'true values'. In the establishment of their limit values, the terms of ISO 4259, "Petroleum products - Determination and application of precision data in relation to methods of test", have been applied and, in fixing a minimum value, a minimum difference of 2R above zero has been taken into account (R = reproducibility). The results of individual measurements shall be interpreted on the basis of the criteria described in ISO 4259 (published in 1995).