TALL OF THE TAX OF CLIEN

			ENGINES				
18.							
19.	Continental						
20.	Tones A65						
20.	of the engine or engines at						
Take-e	(a) Sea Level 50 H.P. at 2100 revolutions per minute.						
	(b) Rated Altitude						
	Hourly consusea level at	umption at mean t above-mentioned engine.	23. Oil: (a)	***************************************	(b)		
	po p	[Number fitted	One Type	Sensenich	No		
24.	Airscrews			Diameter			
			(a) Landplane	Diameter	1	693	lhs
25.	Weight of aircraft empty (neluding water in the radiators)		(a) Landplane				lbs.
	(neluding wat	ter in the radiators,	(c) Skiplane				lbs.
			WEIGHT OF FUEL A				
					,	72	lbs.
26.	Fuel						108.
	(at 7	7.2 lbs. per gallon)	Ome				
	(a) Number of tanks. (b) Capacity of tanks. 10 Imp. gals.						
97	(b) Capacity	y or tanks				9	lbs.
27.	(at (9.0 lbs per gallon)			DESIGNATION OF		
	(a) Number	of tanks	0ne				
	(b) Capacity	y of tanks	, 1	Imp. gals.	. /	170	
28.	Weight allow	ved for crew		***************************************		****************	lbs
29.	Weight allow	ved for equipment.	excluding wireless at	pparatus			lbs
30.	Weight of wi	ireless apparatus					lbs
31.	Maximum co	mmercial load (pa	ssengers, goods) aut	thorized when t	he fuel and		
	oil to	anks are full				276	lbs
32.	36	tal maight authoria	od				IDB
	-Landplane Seaplane Seaplane					1220	108
	Seaplane						IDS
	Skiplane						108
		C	OMPULSORY CON	NDITIONS			
33.	Maximum to	tal weight authoriz	ed (write in full)	38400400 92	BILD TURE SHAD		
	Landplane	Twolwo.hune	ired and twenty	pounds			
	Seaplane						
	Skiplane						
34.	Minimum cr	rew necessary	One				
35.	Inspections and overhauls: See Air Regulations.						
36.	Stowage. See Air Regulations. Distribution of the load: The aircraft must always be so loaded that the centre of gravity position						
37.							
		thin the limits of	inches	and	inches behi	ind the pre	scribe
	datum.		lad must not in	r oiroumatana	overed the	number for	whiel
38.	. The number of passengers carried must not, in any circumstances, exceed the number for which seating accommodation is provided.						
39.	Except in er more than o	mergency the speed one minute in each	of the engine must flight or, if the flight	not exceed	2100 r.j hour, in each	o.m. for a t hour of fli	otal o
	must never	exceed2300	r.p.m.				
	The Ministe	er of Transport ha	ever exceed (a)ving regard to the	reports furnish	ned to him i	ssues the	presen
Ce	rtificate of Air	rworthiness dated A	ugust 1st., 194	16, in r	espect of the	above-men	ntione
air Oc	craft, in accordance tober, 1919, And This Certific	rdance with the Connex B, and with A cate is only valid, so	onvention for the Air Regulations, 193 abject to the above	Regulation of A	Aerial Navig	ation, date	d 13tl
the	e date shown o	on page 4 hereof.					
	Given at Ott	tawa this 19t1	day of	Aug	Not A	Lan	19.46

Superint Ment, Air Regulations.