

- a sidelight, 2 miles;
- a sternlight, 2 miles;
- a towing light, 2 miles;
- a white, red, green or yellow all-round light, 2 miles.

(c) In vessels of less than 12 metres in length:

- a masthead light, 2 miles;
- a sidelight, 1 mile;
- a sternlight, 2 miles;
- a towing light, 2 miles;
- a white, red, green or yellow all-round light, 2 miles.

### Rule 23

#### *Power-driven Vessels underway*

(a) A power-driven vessel underway shall exhibit:

- (i) a masthead light forward;
- (ii) a second masthead light abaft of and higher than the forward one; except that a vessel of less than 50 metres in length shall not be obliged to exhibit such light but may do so;
- (iii) sidelights;
- (iv) a sternlight.

(b) An air-cushion vessel when operating in the non-displacement mode shall, in addition to the lights prescribed in paragraph (a) of this Rule, exhibit an all-round flashing yellow light.

(c) A power-driven vessel of less than 7 metres in length and whose maximum speed does not exceed 7 knots may, in lieu of the lights prescribed in paragraph (a) of this Rule, exhibit an all-round white light. Such vessel shall, if practicable, also exhibit sidelights.

### Rule 24

#### *Towing and Pushing*

(a) A power-driven vessel when towing shall exhibit:

- (i) instead of the light prescribed in Rule 23(a)(i), two masthead lights forward in a vertical line. When the length of the tow, measuring from the stern of the towing vessel to the after end of the tow exceeds 200 metres, three such lights in a vertical line;
- (ii) sidelights;
- (iii) a sternlight;
- (iv) a towing light in a vertical line above the sternlight;
- (v) when the length of the tow exceeds 200 metres, a diamond shape where it can best be seen.