



920 Series Gurney Hot Water Boiler

Make due allowance for mains and risers when selecting size of boiler required.

When soft coal or wood is used as fuel, select a size larger boiler than for hard coal.

Direct-indirect radiation requires 50% more boiler capacity. Indirect radiation requires 75% increased boiler capacity.



No.	List Price	*Capacity, Feet	Equivalent in 1-Inch Pipe	Height of Flow, Inches	Width, Inches	Length, Inches	Grate, Inches	Flows, Inches	Returns, Inches	Approximate Shipping Weight, Lbs.	Smoke Opening, Inches	Size of Flue Required, Inches
924W	230.00	700	2,100	56	32	25	21×16	1-4	2-4	1,100	8	8×8
925W	287.50	900	2,700	56	32	31	21×22	2-4	2-4	1,600	8	8×13
926W	325.00	1,150	3,450	56	32	37½	21×28¼	2-4	2-4	2,100	8	8×13
927W	375.00	1,400	4,200	56	32	44	21×34½	2-4	2-4	2,600	10	12×12
928W	412.50	1,650	4,950	56	32	50½	21×40¾	2-4	2-4	3,100	10	12×12
929W	437.50	1,900	5,700	56	32	57	21×47	2-4	2-4	3,600	10	12×12

* See Page 2