Slip the left hand along the fling as far as the fwell of the 2d. Prefere, firelock; bring the piece down to the present; stepping back fix inches to the rear, with the right foot, and look steadfastly along the barrel of the firelock.

Pull the trigger firmly, and remain on the present, look- 3d. Fire. ing steadily along the piece until the next word of com-

mand.

1st. Bring up the right foot to the infide of the left heel, 4th. Load. and at the same time drop the firelock briskly down to the priming polition; the top of the cock oppolite the right breaft the muzzle raifed to the height of the peak of the cap, and pointing directly to the front, which will throw the firelock into the hollow of the right fide; the left hand continuing to grafp the piece at the fwell, holding it firm and fleady; feize the cock with the fore-finger and thumb of the right hand.

2d. Half-cock-by drawing back the right elbow brifkly,

bringing it down on the butt of the firelock.

1st. Draw the cartridge from the pouch. sth. Handie 2d. Bring it to the mouth, holding it between the fore- Cartridge.

finger and thumb, and bite off the top of the cartridge.

1st. Shake some powder into the pan.

6th. Prime.

2d. Shut the pan with the three last fingers. 3d. Seize the small of the butt with the above three fingers.

Ift. Turn the piece nimbly round to the loading position; 7th. Cast and the butt within two inches of the ground, the lock towards bout; the front, and the muzzle of the piece near the breast; the asitis to be right hand to be brought on that part of the barrel on which ed for the the fight is placed; both feet are to be kept fast in this sake of breposition.

2d. Drop the butt on the ground without noise, shake the powder into the barrel, putting in after it the paper and the

3d. Seize the top of the ramrod with the fore-finger and thumb.

1st. Force the ramrod half out, and seize it back-handed 8th. Draw exactly in the middle. Ramreds.

2d. Draw it entirely out, and turning it with the whole hand and arm extended from you, put it one inch into the barrel.

1st. Push the ramrod down, holding it as before, exactly 9th. Ram in the middle, till the hand touches the muzzle. down Car.