

Annex 1**ADDITIONAL PROVISION CONCERNING DEFINITIONS OF
MOTOR VEHICLE AND CYCLE**

Cycles fitted with an auxiliary internal combustion engine having a maximum cylinder capacity of 50 cm³ (3.05 cu. in.) shall not be considered as motor vehicles, provided that they retain all the normal characteristics of cycles with respect to their structure.

Annex 2**PRIORITY OF PASSAGE**

1. When any two vehicles are simultaneously approaching a road intersection by roads of which one does not enjoy priority over the other, the vehicle approaching from the left in countries where the direction of traffic is on the right, and from the right in countries where the direction of traffic is on the left, shall yield the right of way to the other vehicle.

2. The right of priority shall not necessarily apply in the case of tramcars and trains on roads.

Annex 3**REGISTRATION NUMBER OF VEHICLES IN INTERNATIONAL
TRAFFIC**

1. The registration number of a vehicle shall consist either of figures or of figures and letters. The figures shall be in Arabic numerals as used in United Nations documents and the letters in Latin characters. When other numerals or characters are used, they shall be repeated in the numerals or characters of the types mentioned above.

2. The number shall be legible in normal daylight at a distance of 20 m (65 feet).

3. When the registration number is displayed on a special plate, this plate shall be fixed in a vertical or nearly vertical position and in a plane perpendicular to the longitudinal axis of the vehicle itself. When the number is fixed to or painted on the vehicle itself, this shall be done on a vertical or nearly vertical surface at the back of the vehicle.

4. The rear registration number shall be illuminated as prescribed in annex 6.

Annex 4**DISTINGUISHING SIGN OF VEHICLES IN INTERNATIONAL TRAFFIC**

1. The distinguishing sign shall be composed of one to three letters in capital Latin characters. The letters shall have a minimum height of 80 mm (3.1 in.) and their strokes a width of 10 mm (0.4 in.). The letters shall be painted in black on a white ground of elliptical form with the major axis horizontal.

2. If the distinguishing sign is composed of three letters, the dimensions of the ellipse shall be at least 240 mm (9.4 in.) in width and 145 mm (5.7 in.) in height. The dimensions may be reduced to 175 mm (6.9 in.) in width and 115 mm (4.5 in.) in height if the sign carries less than three letters.

As regards the distinguishing signs for motorcycles, the dimensions of the ellipse, whether the sign is composed of one, two or three letters, may be reduced to 175 mm (6.9 in.) in width and 115 mm (4.5 in.) in height.