

2.4 Minimum distance separation

MINIMUM DISTANCE SEPARATION REQUIREMENTS
(in kilometres)

<u>Relation</u>	<u>Co-Channel</u>	<u>Adjacent Channels</u>			<u>I.F.</u>
	<u>0 kHz</u>	<u>200kHz</u>	<u>400kHz</u>	<u>600kHz</u>	<u>10.6/10.8 MHz</u>
A1-A1	78	45	24	20	4
A1-A	131	78	44	40	7
A1-B1	164	98	57	53	9
A1-B	190	117	71	67	12
A1-C1	223	148	92	88	19
A1-C	227	162	103	99	26
A-A	151	98	51	42	10
A-B1	184	119	64	55	12
A-B	210	137	78	69	15
A-C1	243	168	99	90	22
A-C	247	182	110	101	29
B1-B1	197	131	70	57	24
B1-B	223	149	84	71	24
B1-C1	256	181	108	92	40
B1-C	259	195	116	103	40
B-B	237	164	94	74	24
B-C1	271	195	115	95	40
B-C	274	209	125	106	40
C1-C1	292	217	134	101	48
C1-C	302	230	144	111	48
C-C	306	241	153	113	48

(U.S. Class C2 shall be considered as Class B for the purposes of the above table.)