

(5) When a ladder is to be used in the hold of a vessel which is not decked it shall be the duty of the contractor undertaking the processes to provide such ladder. It shall be equipped at the top with hooks or with other means for firmly securing it.

(6) The workers shall not use, or be required to use, other means of access than the means specified or allowed by this Article.

(7) Ships existing at the date of ratification of this Convention shall be exempt from compliance with the measurements in paragraph (2) (a) and (d) and from the provisions of paragraph (4) of this Article for a period not exceeding four years from the date of ratification of this Convention.

#### Article 6

(1) While the workers are on a ship for the purpose of the processes, every hatchway of a cargo hold accessible to the workers, which exceeds 5 feet (1 m. 50) in depth from the level of the deck to the bottom of the hold, and which is not protected to a clear height of 2 feet 6 inches (75 cm.) by the coamings, shall, when not in use for the passage of goods, coal or other material, either be securely fenced to a height of 3 feet (90 cm.) or be securely covered. National laws or regulations shall determine whether the requirements of this paragraph shall be enforced during meal times and other short interruptions of work.

(2) Similar measures shall be taken when necessary to protect all other openings in a deck which might be dangerous to the workers.

#### Article 7

When the processes have to be carried on a ship, the means of access thereto and all places on board at which the workers are employed or to which they may be required to proceed in the course of their employment shall be efficiently lighted.

The means of lighting shall be such as not to endanger the safety of the workers nor to interfere with the navigation of other vessels.

#### Article 8

In order to ensure the safety of the workers when engaged in removing or replacing hatch coverings and beams used for hatch coverings,

(1) hatch coverings and beams used for hatch coverings shall be maintained in good condition;

(2) hatch coverings shall be fitted with adequate hand grips, having regard to their size and weight, unless the construction of the hatch or the hatch coverings is of a character rendering the provision of hand grips unnecessary;

(3) beams used for hatch coverings shall have suitable gear for removing and replacing them of such a character as to render it unnecessary for workers to go upon them for the purpose of adjusting such gear;

(4) all hatch coverings and fore and aft and thwart-ship beams shall, in so far as they are not interchangeable, be kept plainly marked to indicate the deck and hatch to which they belong and their position therein;