

Regulation 34 - Restricted use of combustible materials

- 40 Existing paragraph 2 is replaced by the following:

"2 Vapour barriers and adhesives used in conjunction with insulation, as well as insulation of pipe fittings, for cold service systems need not be non-combustible, but they shall be kept to the minimum quantity practicable and their exposed surfaces shall have low flame spread characteristics."

- 41 Existing paragraph 7 is replaced by the following:

"7 Paints, varnishes and other finishes used on exposed interior surfaces shall not be capable of producing excessive quantities of smoke and toxic products, this being determined in accordance with the Fire Test Procedures Code."

- 42 Existing paragraph 8 is replaced by the following:

"8 Primary deck coverings, if applied within accommodation and service spaces and control stations, shall be of an approved material which will not readily ignite or give rise to toxic or explosive hazards at elevated temperatures, this being determined in accordance with the Fire Test Procedures Code."

Regulation 37 - Protection of special category spaces

- 43 In paragraph 1.2.1, the following third sentence is added:

"Where fuel oil tanks are below a special category space, the integrity of the deck between such spaces may be reduced to "A-0" standard."

- 44 The following new paragraph 4 is added:

"4 Permanent openings for ventilation

Permanent openings in the side plating, the ends or deckhead of special category spaces shall be so situated that a fire in the special category space does not endanger stowage areas and embarkation stations for survival craft and accommodation spaces, service spaces and control stations in superstructures and deckhouses above the special category spaces."

Regulation 38 - Protection of cargo spaces, other than special category spaces, intended for the carriage of motor vehicles with fuel in their tanks for their own propulsion

- 45 The following new paragraphs 5 and 6 are added:

"5 Permanent openings for ventilation

Permanent openings in the side plating, the ends or deckhead of cargo spaces shall be so situated that a fire in the cargo space does not endanger stowage areas and embarkation stations for survival craft and accommodation spaces, service spaces and control stations in superstructures and deckhouses above the cargo spaces.