

nd step
pattern;
e out of
through
tall and
a chin-
inch lin-
om edge
wrought
ples, one
4 inches
the chin-
the bot-
will be
e approv-
be 1 1-2
and hung
hooks to
& wash-
t, wrought
thick with
deal made
transour
ts, fitted
keep them
locks and
ed before
l and heel
ling to be
er edged
es to the
athered.—
ights with
solid pine
fixed to
the point,
e provided
also insert
ch ledged
and staple
ch. The
o, and the
ils inside.
post.
o, and erect

a Privy as per plan, removing and levelling the earth where may be directed. The sides of the soil pit to be lined with rubble masonry in mortar two feet thick, commencing ten feet below the surface or ground line. The roof to be covered with inch deal, grooved and tongued and cleaned upon the top side to receive the shingles, which are to be of pine, and shewing a gage of four inches to the weather,—sill 8x4—angle studs 4x4—intermediate studs 4x3 tennoned into the top and bottom plates—braces 4x3—top plate 4x4—rafters 4x2—joists 7x3. The whole to be properly framed and braced and covered with inch wrought and rebated clapboarding outside, and lined with inch deal, grooved and tongued inside. The floor to be two inch deal, grooved, and tongued, with a partition of two inch deal, dividing off a portion for women's Privy, which is to be fitted with seat and riser as will be directed. The men's Privy to be fitted with risers of two inch deal and cross bearers of pine 4x2 1-2 rounded on the top edge and firmly fixed. Two openings will be left for doors in men's Privy, and the women's to be fitted with an inch ledged door, hung with strong hooks and rides and thumb latch and handle. Two flues to be fixed from the soil pit through the roof, to cover the cesspool in the rear and form a trap as described for officer's Privy. Fix cedar posts 11 feet long, 4 feet in the ground, with 3 rails 25 feet long, tennoned and pined into posts, covering the same with inch wrought, grooved and tongued boarding, to form a screen in front of Privy. Paint the entire building externally, three times in oil.

Also for a Hospital at the same post, 42 feet by 38, inside measure.

Excavate.—Dig the trench to receive the external and internal foundation walls, including chimnies 4 feet below the ground line at the lowest end, which trenches are to be made perfectly level and even at the bottom; fill in and well raise round the walls as the work is brought up. The earth arising from the excavation to be carted and levelled where may be directed, and the superfluous earth, rubbish &c., removed from off the premises, that the whole may be left in a clean and perfect state—also to regulate the ground and form such surface drains as may be pointed out at the time of execution.

Mason.—The stone to be the best grey building ma-