
SAFETY MINE CAGES

MADE TO FIT YOUR SHAFT

We build these Cages to suit you and your workmen. They are Safe, Strong, and Reliable.




If you do your part by keeping the timbers in proper condition, and the bearings lubricated and reasonably free from rust, the Safety Device will do its work every time.

We supply these cages with either one or two sets of doors for inlet or exist, to suit your shaft.

Rails are also laid in the floor, if required, for convenience in handling the cars.

The top doors permit the carrying of long timbers, or the escape of the men in case of accident.

The hand rails are properly placed to safeguard the passengers in the quick ascent or descent.



HAVE YOU SEEN A COPY OF GUR NEW MINING CATALOGUE?

If not, drop us a card, and one will be sent at once.

MARSH ENGINEERING WORKS, LIMITED, Established BELLEVILLE, ONTARIO

Sales Agents: MUSSENS, LIMITED, Montreal, Toronto, Winnipeg and Vancouver

FOR SALE

2 Norwalk straight line three stage Compressors for charging air locomotives, having compound steam cylinders and two flywheels.

Air pressure 800 lbs. Steam pressure 110 lbs.

Size of steam cylinders—High pressure, 20 ins. diameter. Low pressure, 38 ins. diameter. Stroke, 36 ins. diameter.

Size of air cylinders-23 ins., 16 ins., and 8 ins. in diameter.

ALSO THE FOLLOWING LOCOMOTIVES:-

Maker	Size		Description	Dia., Driver	No. Wheels	Wheel Base	Weight	Length Overall
2 Porter	7"	x 12"	Simple	23"	4	4'0"	14000	13'4"
4 Porter	101/2"	x 14"	,;	26"	4	5'3"	30000	19'4"
2 Porter	7"	x 14"	"	24"	4	5'3"	20000	18'0"
1 Baldwin	11"	x 14"	"	28"	6	6'6"	40000	22'8"
1 Baldwin	11"	x 14"	"	28"	6	6'5"	34000	19'8"
1 Baldwin	9"	x 14"	. ,,	28"	4	5'6"	25000	17'0"

These locomotives are 3 ft. gauge and have a clearance height from top of rail of 4 ft. to 5 ft. 2 in. This machinery is all in working order and is open to inspection at Glace Bay.

DOMINION COAL COMPANY Limited, Glace Bay, N.S.