

All the windows shall be worked according to plans of detail, in fine hatched and carved stone, and according to the size of each block, such as directed in plans of detail.

The crowning of attics and towers above cornices and to the eaves shall be made of cut stone, with the exception of pediments and cornice of the little columns. The crowning of the centre for the front of block A, composed of pediments and little columns, shall be made of stone, except for the rear face and sides which shall be made of wood and galvanized iron. The putting out of the centre of blocks A, E, F shall be made of fine hatched cut stone, for such parts as are indicated on plans.

These three putting centers shall rise above the body of the building and shall be crowned by carved cornices and trophies, those of the main centre representing the arms of the Queen, and those of blocks E and F the arms of the Province of Ontario, the whole according to plans of detail.

All the quoins of centers, pavilions and puttings above basement shall be made of measurement and fine hatched stone, each block forming a header.

At the angles formed by the puttings of the centre of block A, the towers, such as shown on elevation plan, shall be made of cut stone as high as the base of the pyramid forming their tops.

The chimney stacks shall be made in the form shown on plans, of fine hatched stone, with mouldings, columns, &c., and the top shall be formed of one block of stone.

The counter-forts of the Library, above basement, shall be made of stone for the quoins, mouldings, cornices, pediments and crownings, all carved, the whole such as shown on the general plans and to be executed according to plan of detail.

The body of the external walls of all the building, including the library, excepting all cut stone works mentioned above and shown on the plans, shall be built in rubble masonry with embossment at the joints and pointed beds. The stone shall be laid in beds of from 7 to 10 inches thick, so that the thickness of two beds will correspond to that of one bed of angular cut stone. The stone shall be laid in beds of from 8 to 10 inches, with the exception of headers which shall have 16 inches. This stone shall be of the same quality as cut stone.

FLUES.

All the stone for stove or furnace flues shall be laid in the walls under the direction of the architect. The steps and interior landings in the doorways of the main entrance and of the two private entrances to the library, through block C, shall be made of cut stone, rough hatched on treads and tooled on risers. Each step shall be made out of one block, when not exceeding 8 inches and of two when over 8 inches. The joints and beds of these steps shall be cut and each step shall go at least 3 inches under the one above it. The landings of doorways shall be made, as far as practicable, of one block, fine hatched. The steps shall be tooled on the risers and fine hatched on the treads. The top shall be cut according to the slope of the steps.

The stairs in blocks A, C, E and F, from basement to third story, of centers A, C and F, and those of block C, from basement to ground floor, shall be made of stone, rough hatched on steps and fine tooled on risers. Each step shall be made of one block bonded in the partition walls. The joints and beds of these steps shall be cut and each step shall go 3 inches under the one above it. The bottom surface shall be cut so as to follow the course of the staircase.