



The GURNEY FOUNDRY COMPANY, LIMITED

920 Series Gurney Steam Boiler



Regular steam trimmings included, excepting in British Columbia where special fittings are required.

Make due allowance for mains and risers when selecting size of boiler required.

When soft coal or wood is used as fuel, select a size larger boiler than for hard coal.

Direct-indirect radiation requires 50% more boiler capacity. Indirect radiation requires 75% increased boiler capacity.

No.	List Price	*Capacity Feet	Equivalent in 1 inch Pipe	Height of Flow, Inches	Height, Water Line, Inches	Width, Inches	Length, Inches	Grate, Inches	Flows, Inches	Returns, Inches	Approximate Shipping Weight	Smoke Opening, Inches	Size of Flue Required, Inches
924S	\$255.00	425	1,275	56	48	32	25	21 X 16	1-4	2-2	1,100	8	8 X 8
925S	312.50	575	1,725	56	48	32	31	21 X 22	2-4	2-2	1,600	8	8 X 13
926S	350.00	725	2,175	56	48	32	37½	21 X 28½	2-4	2-2	2,100	8	8 X 13
927S	400.00	875	2,625	56	48	32	44	21 X 34½	2-4	2-3	2,600	10	8 X 13
928S	437.50	1,050	3,150	56	48	32	50½	21 X 40½	2-4	2-3	3,100	10	12 X 12
929S	462.50	1,125	3,375	56	48	32	57	21 X 47	2-4	2-3	3,600	10	12 X 12

* See Page 2