public; and the Inspector of boilers and machinery shall Disposal of retain the other triplicate for the purposes of this Act: triplicate certificate.

2. Except that if the steamboat is one of which the boiler Certificate of and machinery only is subject to inspection under this Act, inspection of boilers and the Inspector of boilers and machinery shall sign a certifi- machinery cate in the form B in the said schedule, in duplicate, and only. deliver the duplicates to the master or owner of the steamboat, who shall deliver one to the chief officer of Customs and cause the other to be posted up in some conspicuous part of the steamboat for the information of the public:

3 Any matter in dispute arising under this or any Decision of other sections of this Act, between an Inspector or the in certain Board of Inspection and the master or owner of any steam-cases. boat, and also any dispute between an Inspector or the Board of Inspection and an engineer, may be referred by either party to the Minister of Marine and Fisheries, who shall finally decide the same:

4. Each inspector shall keep a register of the inspections Register of and certificates made and granted by him, in such form and inspections. with such particulars respecting them as the Inspection Board shall from time to time require, and shall furnish copies thereof to the Board when required.

## INSPECTION OF BOILERS AND MACHINERY.

17. Any Inspector may, whenever he deems it necessary Testing of so to do, and some one of them shall at least once in every hydrostatic year, subject the boiler of every steamboat to a test by hydro- pressure. static pressure, and shall satisfy himself by examination and experimental trials, that such boiler is well made, of good and suitable material; the limit of such pressure shall not Limit of testo exceed one hundred and fifty pounds to the square inch in the case of a boiler made of iron plates, or one hundred and ninety pounds to the square inch in the case of a boiler made of steel plates; and the owner of the steamboat shall provide the necessary hand-pump and apparatus for such test, to be worked by the crew of the steamboat; and no Inspector shall Essential to make or deliver to the owner or master of any steamboat, any certificate. such certificate as is mentioned in the sixteenth section of this Act, without having first subjected the boiler of such steamboat to such test by hydrostatic pressure:

2. Before subjecting a boiler to a test by hydrostatic Proceedings pressure it shall be opened up for inspection, the man-hole by hydrostadoors and mud-plates removed, and the outside and inside the pressure. of the boiler cleaned, the furnace grates removed and the furnace swept out clean, so that satisfactory and efficient inspection can be made: when bulkheads are so placed as to prevent a close examination of the plates of the boiler, they