If you want sure delivery of sence we suggest that you get your order in now. We were fortunate in receiving an allotment of steel wire which, until exhausted, will enable us to fill all orders immediately.

In asking you to place your order now we do so to safeguard you against probable disappointment. It's not a question
of late delivery but no delivery that you must guard against. This is true of any wire sence. Orders will be shipped
promptly on receipt. Get yours in early.

| A Company of the Comp | prompt                               | пу оп г                      | eccipe.  | Get Andra   |
|--|--------------------------------------|------------------------------|--|---|
| Heavy "IDEAL" Fence Made throughout of Full Gauge No. 9 evenly Galvanized Hard Steel Wire. Carried in atock in 20, 30 and 40-rod rolls.  | Old Ontario<br>south of<br>North Bay | New Ontario<br>and<br>Quebec | Nova Scotia,<br>New Bruns'E,<br>Pr. Edward<br>Island | MEDIUM HEAVY  "IDEAL" Fence  Made throughout of Hard Steel Wire, evenly Galvanized. Carried in  |
| No. 4330 4 line wires, 33 inches high, uprights 22 inches apart. All No. 9 Hard Steel Wire, evenly galvanized. Spacing 11, 11, 11. Per Rod   | 41c4                                 | 13c                          | 44c  | rolls.  No. 630 6 line wires, 30 inches high.   |
| No. 5400 5 line wires. 40 inches high, uprights 22 inches apart. All No. 9 Hard Steel Wire, evenly galvanized. Spacing 10, 10, 10, 10. Per Rod.  | 52c                                  | 55c                          | 57c  | All Hard Steel Wire, evenly galvanized. Spacing 4, 5, 6, 7, 8. Per Rod. No. 641 6 line wires, 41 inches high, uprights 16½ inches apart.    |
| No. 6300 6 line wires, 30 inches No. 6300 high, aprights 22 inches apart. All No. 9 Hard Steel Wire, evenly galvanized. Spacing 4, 5, 6, 7, 8, Per Red   | 55c                                  | 58c                          | 60c  | No. 6410 Same as Style No. 641 with uprights 22 inches  |
| No. 6400 6 line wires, 40 inches No. 6400 high, uprights 22 inches apart. All No. 9 Hard Steel Wire, evenly galvanized. Spacing 7, 8, 9, 9. Per Rod.   |                                      |                              | 65c  | No. 726 The wires, 20 inches apart. All Hard Steel Wire, evenly galvanized. Spacing 3, 3½, 4, 4½, 5, 6. Per Rod                             |
| No. 7400 high, uprights 22 inches apart. All No. 9 Hard Steel Wire, evenly galvanized. Spacing 5, 6, 6, 7, 732, 832.   | 67c                                  | 70c                          | 72c  | No. 7261 Same as Style No. 726, but with uprights 8 inches apart. Per Rod   |
| spart. All No. 9 Hard Steel Wire, evenly   | 70c                                  | 73c                          | 75c  | inches apart. Per Rod   |
| Per Rod  | 75c                                  | 78c                          | 81c  |   |
| No. 842 8 line wires, 42 inches high. No. 842 uprights 1614 inches apart. All No. 9 Hard Steel Wire, evenly gal- vanized. Spacing 6, 6, 6, 6, 6, 6. Per Rod  | 1                                    |                              | 86c  | No. 936 uprights 13 inches apart. All Hard Steel Wire, evenly galvanized Spacing 3, 31/4, 41/4, 41/4, 5, 51/4, 6. Per                       |
| apart. All No. 9 Hard Steel Wire, evenly galvanized. Spacing 4, 5, 6, 7, 8, 8, 9.  | 76c                                  | 79c                          | 82c  | No. 949 9 line wires, 49 inches apart<br>All Hard Steel Wire, evenly galvanized<br>Spacing 4, 4, 5, 6, 7, 7, 8, 8. Per Red                  |
| All No. 9 Hard Steel Wire, evenly galvanized. Spacins 4, 5, 6, 7, 8, 8, 9. Per Rod   | 83c                                  | 860                          | 89c  | apart. All Hard Steel Wire, evenly gal<br>vanized. Spacing 3, 3, 3, 4, 4, 5, 6, 7, 7, 8<br>Per Rod.   |
| No. 935 9 line wires, 35 inches high. No. 9 Hard Steel Wire, evenly gal- vanized. Spacing 3, 3, 4, 5, 5, 6, 6. Per Rod. 049 9 line wires, 48 inches high   | OOL                                  |                              |  | apart. All Hard Steel Wire, evenly ga<br>vanized. Spacing 2½, 2½, 2½, 2½, 2½, 2, 2½, 3, 3½, 4, 5, 5½, 5½, 6. Per Rod.                       |
| All No. 9 Hard Steel Wire, evenly gal<br>vanized. Spacing 6, 6, 6, 6, 6, 6, 6, 6   | 92c                                  | 96                           | \$ 1.00  | A dhad thad to the said   |
| apart. All No. 9 Hard Steel Wire, eveni<br>galvanized. Spacing 3, 4, 5, 6, 7, 7, 8, 8<br>Per Rod. 200 9 line wires, 50 inche   | 31.04                                | \$1.0                        | 8 31.12  | Top and bottom wires No. 9 all other No. 13. Carried in stock in 10 and 20-rod rolls.   |
| apart. All No. 9 Hard Steel Wire, event  | 835c                                 | 1897                         | 920  | 1848 18 bar, 48 inches mg   |
| Per Rod.  No. 950 9 line wires, 50 inches high No. 950 uprights 16½ inches anart All No. 9 Hard Steel Wire, evenly gavanized. Spacing 4, 4, 5, 6, 7, 8, 8, 8. Per Rod.  1050 10 line wires, 50 inches and 1050 10 line wires, 50 inches high line wires, 50 inc | 92c                                  | 96                           | c, 1.0   | All Hard Steel Wire, evenly galvanize processors from bottom up, 134, 134, 134, 134, 24, 24, 24, 24, 3, 3, 3, 3, 3, 3, 4, 4, 4, 5, Per Rod  |
| No. 1050 10 line wires, 50 inche high, uprights 16½ inche apart. All No. 9 Hard Steel Wire, evenl galvanized. Spacing 3, 3, 3½, 4½, 5½, 6½, 8, 8, 8. Per Rod   | 7. 31.00                             | 131.0                        | 4 \$1.0  | 9 Spacing, from bottom up, 11/4, 11/4, 11/4, 11/4, 11/4, 11/4, 11/4, 12/4, 21/4, 21/4, 21/4, 21/4, 3, 3, 3, 3)/3, 4, 41/4, 5, 6, 6. Per Rod |

# 54c56c57c 56c58c61c 62c64c66c 71c73c75c

# nce

thes apart (alvanized) 11/4. 13/4. \$1.05 \$1.10 \$1.15 ches high

enly gai-2/5,2/5. 83c 85c 88c

### Improved "IDEAL" "IDEAL" Lawn Fence Stock Gates and Lawn Gates

Wire filling No. 9 throughout, same as Heavy "IDEAL."
Fence. No fence filling used. Each wire
put in by hand. Write for Price List and Catalogue. Improved "IDEAL"

Carried in stock in following sizes on

12 feet long, 51 inches high, each 13 feet long, 51 inches high, each 14 feet long, 51 inches high, each

### Fence Supplies, Brace Wire and Barb Wire Ideal Steel Posts, 11/211/27 long. \$0.60 \$ 0.65 \$ 0.68

| Ideal Fence Stretchers, each          | 112.50 | 13.75 | 14.20 |
|---------------------------------------|--------|-------|-------|
| Hand Stretcher, each                  | 1.50   | 1.65  | 1.75  |
| Universal Post Hole Digger, each      | 3.50   | 3.50  | 3.60  |
| Galv. Staples in 25-lb. boxes         | 2.20   | 2.30  | 2.40  |
| Galv. Staples in 100-lb, boxes        | 8.00   | 8.30  | 8.60  |
| No. 9 Brace Wire, per 25 lbs          | 2.10   | 2.40  | 2.50  |
| No. 9 Colled Spring Wire, per 100 lbs | 7.40   | 7.70  | 8.00  |
|                                       |        |       |       |
|                                       |        |       |       |

### Barb Wire

Our Guarantee—"Ideal" Fence is guaranteed to should be made,—to be made exactly as represented. If you are not satisfied with "Ideal," return it at our expense and get a new lot or your money back. This guarantee covers everything—no conditions—no loop-holes.

Reference—The Canadian Bank of Commerce.

### Ideal Fence and Spring Company of Canada, Limited

\$4.40 4.70

84.20

1050 McDougall St.

Length, fert

Farm Gates

Horizontal wires all No. 9, only 5 inches apart. Uprights No. 12 wire, 6 inches apart. Diagonals No. 13, fursish a strong close mesh chicken-proof and pig-proof. New patented brace tightener and latch—the biggest gate improvements in years.

WINDSOR, ONTARIO

435 Coristine Bldg., Montreal, Que.

### 11470

### The Pilot Superior Supplies Moist, Warm Air



By means of the properly-located water pan the warm air is kept pure and healthful, and the proper amount of moisture is insured. The heat of the furnace vaporizes the water and sends it up in just the right quantities, providing a balmy atmosphere. This humidifier also eliminates the danger of drying out furniture and warping woodwork. A PILOT SUPERIOR PIPELESS FURNACE can be installed in six hours.

Manufactured by

The Hall Zryd Foundry Co., Limited Hespeler, Ontario



to Drive. Holds Firmly III Place.

If you've been accustomed to the back-breaking job of digging post-holes, handling heavywood posts, filling in and tamping, you'll be delighted with the ease, speed and economy with which

#### PRESTON STEEL POSTS

are erected. The sharp bewelled point goes in with a few hammer-blows, and the anchor-plate binds the post so firmly that no replacements are required. Haul enough at one load to fence a 40 acre field—drive them in a day—have a good-looking, permanent fence. Write for Folder. METAL SHINGLE & SIDING COMPANY,

PRESTON, ONTARIO

### SQUARE DEAL FARM ENGINES

We Want to Demonstrate on Your Farm We will send you a Gilson Engine without charge
size you need—to prove what it
will make for you in dollars and
cents—toshow you how much help
you can do without—to show you
how much time it saves—how many back—breaking jobs it will do. Pay us on easy terms—as
the engine earns. Economy and dependability
have made the Gilson the best selling engine in
Canada. Write to day for catalog, price and Easy
Payment Plau.
Gilson MFG.



## Goer Like Sixty

PATENT SOLICITORS—Fetherstonhaught
& Co., The old-established firm. Patent
everywhere. Heed Office: Royal Hank
Buildings, Toronto. Ottawa Office: Begin Street.
Booklet free.

" Advocate " Advts. Pay.