

The GURNEY FOUNDRY COMPANY, LIMITED



917 Series Gurney Hot Water Boiler



No.	List Price	*Capacity, Feet	Equivalent in 1-Inch Pipe	Height of Flw., Inches	Width, Inches	Length, Inches	Grate, Inches	Flws, Inches	Returns, Inches	Approximate Shipping Weight, Lbs.	Smoke Opening, Inches	Size of Flue Required, Inches
913W	\$190.00	500	1,500	50 1/4	29 1/8	34 3/4	17 X 21	1-4	1-4	1,400	9	8 X 8
914W	230.00	750	2,250	50 1/4	29 1/8	43 1/2	17 X 30	2-4	2-4	1,725	9	8 X 8
915W	287.50	1,000	3,000	50 1/4	29 1/8	51 1/4	17 X 39	2-4	2-4	2,050	9	8 X 12
916W	325.00	1,250	3,750	50 1/4	29 1/8	60	17 X 48	2-4	2-4	2,375	9	12 X 12
917W	375.00	1,500	4,500	50 1/4	29 1/8	68 3/4	17 X 57	2-4	2-4	2,700	9	12 X 12

Make due allowance for mains and risers when selecting size of boiler required.

When soft coal or wood is used as fuel, select a size larger boiler than for hard coal.

Direct-indirect radiation requires 50% more boiler capacity. Indirect radiation requires 75% increased boiler capacity.

* See Page 2