

- 40 6-in. Rotary Tool Joints, 5 x 6—7 Pin and Box.
- 2 6 x 5 Forged Steel Swivel Bushings.
- 2 6 x 4 Forged Steel Swivel Bushings.
- 2 6 x 8¼-in. C C Steel Water Head Bushings.
- 2 6 x 10-in. C C Steel Water Head Bushings.
- 2 6 x 12½-in. C C Steel Water Head Bushings.
- 2 6 x 15½-in. C C Steel Water Head Bushings.
- 1 6-in. Tool Steel Saw Tooth Rotary Shoe.
- 1 8¼-in. Tool Steel Saw Tooth Rotary Shoe.
- 1 10-in. Tool Steel Saw Tooth Rotary Shoe.
- 1 8¼-in. x 16-in. Special Mogul Drive Shoe.
- 1 10-in. x 16-in. Special Mogul Drive Shoe.
- 1 12½-in. x 16-in. Special Mogul Drive Shoe.
- 6 18-in. x 6-in. Fish Tail Bits, 5 x 6—7 Pin.
- 8 14-in. x 6-in. Fish Tail Bits, 5 x 6—7 Pin.
- 12 12¾-in. x 6-in. Fish Tail Bits, 5 x 6—7 Pin.
- 12 11¾-in. x 6-in. Fish Tail Bits, 5 x 6—7 Pin.
- 3 6 x 6 x 36-in. Offset Steel Drilling Collars to fit 6-in. Drill Stem and 5 x 6—7 Bit.
- 80 Ft. S S 40 Special Steel Chain.
- 20 Ft. S S 124 Special Steel Chain.
- 300 Ft. 1¼-in. Manila Rope for Cat Line.
- 1000 Ft. 7/8 x 19 Steel Rope for Hoisting.
- 3000 Ft. 9/16 x 7 Steel Rope for Bailing.
- 6 7/8 Wire Rope Clips.
- 6 9/16 Wire Rope Clips.
- 1 6-in. Parker Releasing Spear, with Trip Device.
- 1 10-in. Kameron Over Shot to catch 6-in.
- 1 Mogul Reversible Tong with Jaws for 6-in. Drill Stem, 6-in. Tool Joints and 8¼, 10, 12½, 15½ Casing.

FITTINGS TO CONNECT UP PUMP AND ENGINE.

- 1 Parker Valve Trap.
- 2 Plain Oil Country Lubricators.
- 2 2-in. I. B. B. W. Stop Cocks.
- 1 1-in. I. B. B. W. Stop Cocks.
- 2 3-in. B. B. B. M. Gate Valves.
- 4 2-in. Brass Joint Flange Unions.
- 2 2½-in. Brass Joint Flange Unions.
- 4 1 x 4 Nipples.
- 12 2 x 6 Nipples.