

- 2 -

- ✓ 1 - Length 1" pipe 18" long,
- ✓ 1 - 4" tee, approximately 13" face to face, flanged
- ✓ 1 - 1/4 bend, 4" C.I. Pipe class "D" hub ends.
- ✓ 1 - Piece 4" C.I. pipe class "D" 23 $\frac{1}{2}$ " long, socket ends.
- ✓ 1 - " 4" C.I. " " "D" 5'2 $\frac{3}{4}$ " long / 1 end flanged
- 1 " socket,
- ✓ or to fit plan and tee selected.
- ✓ 2 - 2" x 10" clear fir boards 6' long
- ✓ 20 - 1/4" x 3" round iron spikes.

FOR TIMING PIPE ORDER

- ✓ 1 - Length standard cast iron pipe, flanged both ends, class "D" 6" diameter. Thickness .55", to be 49" from face to face of flanges.
- ✓ 1 - Length standard cast iron pipe flanged both ends, class "D" 6" diameter, .55" thick, to be 59 inches from face to face of flanges.
- ✓ 1 - Standard blind flange, cast iron, faced and drilled to fit flanges on above pipe lengths, with one hole, 1 $\frac{1}{2}$ " diameter, threaded, in center of flange.
- 1 - Standard blind flange, cast iron, faced and drilled to fit flanges on above pipe lengths.
- 3 - Gaskets and 3 sets of bolts for above pipe. The two lengths of pipe will be joined together on the job with a blind flange over each outer end. C.I. pipe to be tapped for 1" pipes in two places as shown on detail.

National Archives of Canada
Archives nationales du Canada

Parks Canada
Parcs Canada

RG 84, A-2-a, Vol. 1656
File/dossier K72
pt 1

001586A