

2. Mobile Sources

Implementation of the following mobile source nitrogen oxides control program to the extent required by Title II of the Clean Air Act:

(a) Light Duty Trucks (LDT) (up to 6000 lbs gross vehicle weight rating (GVWR)) and Light Duty Vehicles (LDV) -- standards for model years after 1993:

	5 yrs/50,000 miles (useful life)	10 yrs/100,000 miles
LDTs (0 to 3750 lbs Loaded Vehicle Weight (LVW)) and LDVs	0.4 grams per mile (gpm)	0.6 gpm
Diesel LDTs (0 to 3750 lbs LVW) and LDVs (before 2004)	1.0 gpm	1.25 gpm
LDTs (3751 to 5750 lbs LVW)	0.7 gpm ⁵	0.97 gpm

In model year 1994, 40% of each manufacturer's sales volume must meet the above standards. In 1995, the percentage shall increase to 80% and, after 1995, to 100%.

(b) Light Duty Trucks more than 6000 lbs GVWR
(after model year 1995):

	Gasoline 5 yrs/50,000 miles	Gasoline and Diesel 11 yrs/120,000 miles
LDTs (3751 to 5750 lbs Test Weight (TW))	0.7 gpm	0.98 gpm
LDTs (over 5750 lbs TW)	1.1 gpm	1.53 gpm

In model year 1996, 50% of each manufacturer's sales volume must meet the above standards. Thereafter, 100% of each manufacturer's sales volume must meet the standard.

⁵. This standard does not apply to diesel-fueled LDTs (3751 to 5750 lbs LVW).