

In particular,

(1) every said working place on shore and any dangerous parts of any said approach thereto from the nearest highway shall be safely and efficiently lighted;

(2) wharves and quays shall be kept sufficiently clear of goods to maintain a clear passage to the means of access referred to in Article 3;

(3) where any space is left along the edge of any wharf or quay, it shall be at least 3 feet (90 cm.) wide and clear of all obstructions other than fixed structures, plant and appliances in use; and

(4) so far as is practicable having regard to the traffic and working,

(a) all dangerous parts of the said approaches and working places (e.g. dangerous breaks, corners and edges) shall be adequately fenced to a height of not less than 2 feet 6 inches (75 cm.);

(b) dangerous footways over bridges, caissons and dock gates shall be fenced to a height of not less than 2 feet 6 inches (75 cm.) on each side, and the said fencing shall be continued at both ends to a sufficient distance which shall not be required to exceed 5 yards (4 m. 50).

#### *Article 3*

(1) When a ship is lying alongside a quay or some other vessel for the purpose of the processes, there shall be safe means of access for the use of the workers at such times as they have to pass to or from the ship, unless the conditions are such that they would not be exposed to undue risk if no special appliance were provided.

(2) The said means of access shall be:

(a) where reasonably practicable, the ship's accommodation ladder, a gangway or a similar construction;

(b) in other cases a ladder.

(3) The appliances specified in paragraph (2) (a) of this Article shall be at least 22 inches (55 cm.) wide, properly secured to prevent their displacement, not inclined at too steep an angle, constructed of materials of good quality and in good condition, and securely fenced throughout to a clear height of not less than 2 feet 9 inches (82 cm.) on both sides, or in the case of the ship's accommodation ladder securely fenced to the same height on one side, provided that the other side is properly protected by the ship's side.

Provided that any appliances as aforesaid in use at the date of the ratification of this Convention shall be allowed to remain in use:

(a) until the fencing is renewed if they are fenced on both sides to a clear height of at least 2 feet 8 inches (80 cm.);

(b) for one year from the date of ratification if they are fenced on both sides to a clear height of at least 2 feet 6 inches (75 cm.).

(4) The ladders specified in paragraph (2) (b) of this Article shall be of adequate length and strength, and properly secured.