



The GURNEY FOUNDRY COMPANY, LIMITED



917 Series Gurney Steam Boiler

No.	List Price	*Capacity, Feet	Equivalent in 1 inch Pipe	Height of Flow, Inches	Height, Water Line, Inches	Width, Inches	Length, Inches	Grate, Inches	Flows, Inches	Returns, Inches	Approximate Shipping Weight	Smoke Open- ing, Inches	Size of Flue Required, Inches
913S	\$215.00	300	900	50 1/4	39 1/2	29 1/8	34 1/4	17 X 21	1-4	1-4	1,400	9	8 X 8
914S	255.00	450	1,350	50 1/4	39 1/2	29 1/8	43 1/2	17 X 30	2-4	2-4	1,725	9	8 X 8
915S	312.50	600	1,800	50 1/4	39 1/2	29 1/8	51 1/4	17 X 39	2-4	2-2 1/2	2,050	9	8 X 12
916S	350.00	750	2,250	50 1/4	39 1/2	29 1/8	60	17 X 48	2-4	2-2 1/2	2,375	9	8 X 12
917S	400.00	900	2,700	50 1/4	39 1/2	29 1/8	68 1/4	17 X 57	2-4	2-2 1/2	2,700	9	8 X 12 or equivalent

Regular steam trimmings included, excepting in British Columbia where special fittings are required.

Make due allowance for mains and risers when selecting size of boiler required.

When soft coal or wood is used as fuel, select a size larger boiler than for hard coal.

Direct-indirect radiation requires 50% more boiler capacity. Indirect radiation requires 75% increased boiler capacity.

*See Page 2