

NEWFOUNDLAND—Continued.

		Character of light.	Interval of revolution or flash.	Number	Height of light above sea-level.	Distance visible, in nautical miles.	Character of light-house or vessel.	Height of tower from base to focal plane, in feet.	Character and order of illuminating apparatus.	Year lighted.	Remarks.
Int.	11 seconds bright, 9 seconds dark.			10a	74	10	Iron tower on keeper's dwelling; square; flat-roofed; painted alternate horizontal red and white bands.	-----	D., 4th ord.	1880	
				11	85	12	Granite; attached to keeper's dwelling.	-----	D., 11th ord.	1873	Visible between the bearings W. by N. and N. by E., over an arc of 270° .
				12							
Rev., red and white.	Every 45 seconds; flash 15 seconds; eclipsed 30 sec's.			13	150	16	Square, with vertical red and white stripes.	36	D., 1st ord.	1843	Red and white, alternately, in every direction seaward. Kept open of Spillers' point clears the Flower rocks.
				14							
F.				15	92	15	Wood, white; red roof	-----	C., 4th ord.	1857	Visible from seaward between the bearings WSW. and NE., illuminating an arc of $157\frac{1}{2}^{\circ}$.
				16							
F.				17	75	11	Wood; white	-----	D., 6th ord.	1874	Illuminates an arc of 320° .
				18							
Rev.	Every 20 seconds.			19	380	28	Circular; brick	34	C., 1st ord.	1858	When the S. part of the island bears N. N. E. 1. E. within the distance of 8 miles, the light is not visible, being obscured by the high land. The keeper's dwelling is white, and roof red.
F.				19a	195	16	Wood; white; keeper's dwelling attached; red roof.	-----	D., 6th ord.	1878	
				2							