

- 1 - Length 1' pipe 1/2" long,
  - 1 - 4" tee, approximately 1/2" face to face, flanged
  - 1 - 1/4 bend, 4" C.I. pipe class "D" hub ends.
  - 1 - Piece 4" C.I. pipe class "D" 25 1/2" long, socket ends.
  - 1 - " " " " " " 5' 8 1/2" long 1/2" 1" end flanged  
" " " " " " " " 1" socket,
- or to fit plan and tee selected.
- 2 - 2" x 10" clear fir boards 6' long
  - 20 - 1/4" x 3" round iron spikes.

FOR TIMING PIPE ORDER

- 1 - Length standard cast iron pipe, flanged both ends, class "D" 6" diameter. Thickness .80", to be 49" from face to face of flanges.
- 1 - Length standard cast iron pipe flanged both ends, class "D" 6" diameter, .80" thick, to be 50 inches from face to face of flanges.
- 1 - Standard blind flange, cast iron, faced and drilled to fit flanges on above pipe lengths, with one hole, 1 1/2" diameter, threaded, in center of flange.
- 1 - Standard blind flange, cast iron, faced and drilled to fit flanges on above pipe lengths.
- 3 - Gaskets and 3 sets of bolts for above pipe. The two lengths of pipe will be joined together on the job with a blind flange over each outer end. C.I. pipe to be tapped for 1" pipes in two places as shown on detail.