- (iii) evidence that the container was constructed to standards which, in the opinion of the Administration, were equivalent to the technical conditions set out in Annex II with the exception of those technical conditions relating to the end-wall and side-wall strength tests;
- (e) allowable stacking weight for 1.8 g (kilogrammes and lbs); and
- (f) such other date as required for the Safety Approval Plate, then the Administration, after investigation, shall notify the owner in writing whether approval is granted; and if so, this notification shall entitle the owner to affix the Safety Approval Plate after an examination of the container concerned has been carried out in accordance with Regulation 2.
- 2. Existing containers which do not qualify for approval under paragraph 1 of this Regulation may be presented for approval under the provisions of Chapter II or Chapter III of this Annex. For such containers the requirements of Annex II relating to end and/or side-wall strength tests shall not apply. The Administration may, if it is satisfied that the containers in question have been in service, waive such of the requirements in respect of presentation of drawings and testing, other than the lifting and floor-strength tests, as it may deem appropriate.

APPENDIX

The Safety Approval Plate, conforming to the model reproduced below, shall take the form of a permanent, non-corrosive, fire-proof rectangular plate measuring not less than 200 mm by 100 mm. The words "CSC Safety Approval" of a minimum letter height of 8 mm and all other words and numbers of a minimum height of 5 mm shall be stamped into, embossed on or indicated on its surface in any other permanent and legible way.