Merchant Shipping Acts, &c., Amendment.

Art. 3. Seagoing Steam Ships when under weigh shall

carry:

(a.) At the Foremast Head, a bright White Light so fixed as to show an uniform and unbroken Light over an Arc of the Horizon of 20 Points of the Compass, so fixed as to throw the Light 10 Points on each Side of the Ship, viz., from right ahead to 2 Points abaft the Beam on either Side, and of such a Character as to be visible on a dark Night with a clear Atmosphere at a Distance of at least Five Miles:

(b.) On the Starboard Side, a Green Light so constructed as to throw an uniform and unbroken Light over an Arc of the Horizon of 10 Points of the Compass, so fixed as to throw the Light from right ahead to 2 Points abaft the Beam on the Starboard Side, and of such a Character as to be visible on a dark Night with a clear Atmosphere at a Distance of at least

Two Miles:

(c.) On the Port Side, a Red Light, so constructed as to show an uniform unbroken Light over an Arc of the Horizon of 10 Points of the Compass, so fixed as to throw the Light from right ahead to 2 Points abaft the Beam on the Port Side, and of such a Character as to be visible on a dark Night with a clear Atmosphere at a Distance of at least Two Miles:

(d.) The said Green and Red Side Lights shall be fitted with inboard Screens projecting at least Three Feet forward from the Light, so as to prevent these Lights from being seen across

the Bow.

Art. 4. Steam Ships when towing other Ships shall carry Two bright White Mast-head Lights vertically, in addition to their Side Lights, so as to distinguish them from other Steam Ships. Each of these Mast-head Lights shall be of the same Construction and Character as the Mast-head Lights which other Steam Ships are required to carry.

Art. 5. Sailing Ships under weigh or being towed shall carry the same Lights as Steam Ships under weigh, with the Exception of the White Mast-head Lights, which they shall never

carry.

Art. 6. Whenever, as in the Case of small Vessels during bad Weather, the Green and Red Lights cannot be fixed, these Lights shall be kept on Deck on their respective sides of the Vessel ready for instant Exhibition, and shall, on the Approach of or to other Vessels, be exhibited on their respective Sides in sufficient Time to prevent Collision, in such Manner as to make them most visible, and so that the Green Light shall not be seen on the Port Side, nor the Red Light on the Starboard Side.

To make the Use of these portable Lights more certain and easy, they shall each be painted Outside with the Colour of the Light they respectively contain and shall be provided with

suitable Screens.