

- .2 chapter VI of the Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk adopted by the Assembly of the Organization by resolution A.212(VII), hereinafter referred to as 'the Bulk Chemical Code', as has been or may be amended by the Organization;

whichever is applicable."

Amend paragraph 20 to read:

" 'Gas carrier' is a cargo ship constructed or adapted and used for the carriage in bulk of any liquefied gas or other products listed in either:

- .1 chapter 19 of the International Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk adopted by the Maritime Safety Committee by resolution MSC.5(48) hereinafter referred to as 'the International Gas Carrier Code', as may be amended by the Organization; or
- .2 chapter XIX of the Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk adopted by the Assembly of the Organization by resolution A.328(IX), hereinafter referred to as 'the Gas Carrier Code', as has been or may be amended by the Organization;

whichever is applicable."

Regulation 4

Floodable length in passenger ships

Paragraph 1, line 3 delete "and" and insert "and".

Regulation 5

Permeability in passenger ships

Amend paragraph 4.1 to read:

"4.1 In the case of special subdivision required in regulation 6.5, the uniform average permeability throughout the portion of the ship forward of or abaft the machinery space shall be 95-35 b/v where:

b = the volume of the spaces below the margin line and above the tops of floors, inner bottom, or peak tanks, as the case may be, which are appropriated to and used as cargo spaces, coal or oil fuel bunkers, store-rooms, baggage and mail rooms, chain lockers and fresh water tanks, forward of or abaft the machinery space; and

v = the whole volume of the portion of the ship below the margin line forward of or abaft the machinery space."