


ENGINES

18. Number installed.....	One
19. Makes.....	DeHavilland
20. Types.....	Gipsy Major 1C
21. International power of the engine or engines at.....	
(a) Sea Level 125/130 H.P. at.....	2100 revolutions per minute. (International number of revolutions)
(b) Rated Altitude..... H.P. at.....	revolutions per minute. (International number of revolutions)
Hourly consumption at mean sea level at above-mentioned power per engine.	22. Fuel: (a).....(b).....
24. Airscrews { Number fitted..... One Types..... No.....	23. Oil: (a).....(b).....
25. Weight of aircraft empty (including water in the radiators):	(a) Landplane..... (b) Seaplane..... (c) Skiplane.....

1241 lbs.
lbs.
1286 lbs.



WEIGHT OF FUEL AND OIL

26. Fuel..... (at 7.2 lbs. per gallon)		137 lbs.
(a) Number of tanks..... One		
(b) Capacity of tanks..... 19 Imp. gals.		
27. Oil..... (at 9.0 lbs. per gallon)		18 lbs.
(a) Number of tanks..... One		
(b) Capacity of tanks..... 2 Imp. gals.		
28. Weight allowed for crew.....		170 lbs.
29. Weight allowed for equipment, excluding wireless apparatus.....		lbs.
30. Weight of wireless apparatus.....		lbs.
31. Maximum commercial load (passengers, goods) authorized when the fuel and oil tanks are full..... S.P. 204 lbs.	L.P.	259 lbs.
32. Maximum total weight authorized..... Landplane (Acrobatic) 1770 lbs.	(Normal)	1825 lbs.
Seaplane.....		lbs.
Skiplane (Acrobatic) 1770 lbs.	(Normal)	1825 lbs.

COMPULSORY CONDITIONS

33. Maximum total weight authorized (write in full)
Landplane (Normal) Eighteen hundred and twenty-five pounds
Seaplane }
Skiplane (Acrobatic) Seventeen hundred and seventy pounds
34. Minimum crew necessary..... One
35. Inspections and overhauls: See Air Regulations.
36. Stowage. See Air Regulations.
37. Distribution of the load: The aircraft must always be so loaded that the centre of gravity position must fall within the limits of inches and inches behind the prescribed datum.
38. The number of passengers carried must not, in any circumstances, exceed the number for which seating accommodation is provided.
39. Except in emergency the speed of the engine must not exceed 2100 r.p.m. for a total of more than one minute in each flight or, if the flight exceeds one hour, in each hour of flight; it must never exceed 2400 r.p.m.
40. The indicated air speed must never exceed (a)..... m.p.h. and (b)..... m.p.h. with flaps extended.

The Minister of Transport having regard to the reports furnished to him issues the present Certificate of Airworthiness dated June 15, 1945 in respect of the above-mentioned aircraft, in accordance with the Convention for the Regulation of Aerial Navigation, dated 13th October, 1919, Annex B, and with Air Regulations, 1938.

This Certificate is only valid, subject to the above compulsory conditions being fulfilled and until the date shown on page 4 hereof.

Given at Ottawa this 3rd day of July, 1945.

R. Graham
Superintendent, Air Regulations.

* If flown acrobatically the maximum weight must not exceed 1770 lbs.