

51 The following new paragraph 2.5 is added:

"2.5 Permanent openings in the side plating, the ends or deckhead of open and closed ro-ro cargo spaces shall be so situated that a fire in the cargo space does not endanger stowage areas and embarkation stations for survival craft and accommodation spaces, service spaces and control stations in superstructures and deckhouses above the cargo spaces."

**Regulation 54 - Special requirements for ships carrying dangerous goods**

52 The following new paragraph 2.4.3 is added:

"2.4.3 Natural ventilation shall be provided in enclosed cargo spaces intended for the carriage of solid dangerous goods in bulk, where there is no provision for mechanical ventilation."

53 The following new paragraphs 2.10 and 2.11 are added:

"2.10 In ships having ro-ro cargo spaces, a separation shall be provided between a closed ro-ro cargo space and an adjacent open ro-ro cargo space. The separation shall be such as to minimize the passage of dangerous vapours and liquids between such spaces. Alternatively, such separation need not be provided if the ro-ro cargo space is considered to be a closed cargo space over its entire length and shall fully comply with the relevant special requirements of this regulation.

2.11 In ships having ro-ro cargo spaces, a separation shall be provided between a closed ro-ro cargo space and the adjacent weather deck. The separation shall be such as to minimize the passage of dangerous vapours and liquids between such spaces. Alternatively, a separation need not be provided if the arrangements of the closed ro-ro cargo spaces are in accordance with those required for the dangerous goods carried on the adjacent weather deck."