

PAGE.	TRIAL No.	69	on coal from McAlloy's Creek Coal & Coke Co., Ltd.	PAGE.
3	"	78	"	"
3	"	112	"	Hillcrest Collieries, Ltd.
7	"	105	"	"
7	"	106	"	"
8	"	67	"	West Canadian Collieries, Ltd., Bell
8	"	80	"	"
8	"	68	"	"
8	"	81	"	"
8	"	70	"	East Canadian Collieries, Ltd.
8	"	79	"	"
8	"	100	"	Chamook Coal Co., Ltd.
9	"	101	"	"
10	"	71	on peat from McAlloy's Creek Coal & Coke Co., Ltd.	Department of Mines
11	"	72	"	"
11	"	73	"	"
12	"	83	"	"
12	"	84	"	"
12	"	85	"	"
15	General remarks-			
18				38
19				
20				

ILLUSTRATIONS.

Drawings.

1-37	Fig. 1. Chart showing the relation between the evaporation and caloric value per pound of fuel, and the thermal efficiency of the boiler and the grate	10
"	2. Chart showing the distribution of the heat losses as a fraction of the heat used for steam-raising	10
"	3. Diagram showing the relation between the loss due to the high temperature of escaping flue gas and the air supply ratio	12
"	4. Diagram showing the relation between the average air ratios for the trials and the average carbon dioxide contents of the flue gas	13
"	5. Chart showing that with the exception of three fuels, the ratio of air supplied for combustion to that used was less when a fuel was burned on a grate with $\frac{1}{2}$ " air space	14
"	6. Diagram showing the effect of a change in the rate of steaming upon the excess air supply	15
"	7. Diagram showing the relation between the heat loss due to unburnt solid fuel per pound of fuel fired, and the original ash content of the fuel	16
"	8. Diagram showing the relation which the sum of the percentage unaccounted for losses, and those due to radiation and unburnt gases bear to the air ratio	16
"	9. Diagram showing the boiler efficiencies at normal evaporation rates on a base representing the air ratio	17
"	10. Diagram showing the decrease in thermal efficiency based on ash and moisture free fuel consumed and the increase in the loss due to the high temperature of the flue gas, with an increase in the rate of combustion	18
"	11. Diagram showing the relation between the difference of draft in the furnace and flue and the mass flow of the gases	19