

SECTION 3

Assignable Frequencies based on Radiotelegraph Emissions

In general, in the frequency range 1600-4000 Kc/s. the frequencies assigned shall be integral multiples of 4 Kc/s. from 1600 to 3000 Kc/s. and integral multiples of 5 Kc/s. from 3000 to 4000 Kc/s. Communication channels wider than 4 Kc/s. or 5 Kc/s. may be assigned where the authorized band width of the emission requires the use of such wider channels. For example, two adjoining telegraph channels may be assigned for telephony, in which case the frequency assigned to a station should be the mid-frequency of such channels. The frequencies to be assigned to stations are given in the Table below. Departure from these assignments may be made in order to make more efficient use of the frequency space available.

The following Table indicates the assignments frequencies.

1600	1756	1912	2068	2224	2380
1604	1760	1916	2072	2228	2384
1608	1764	1920	2076	2232	2388
1612	1768	1924	2080	2236	2392
1616	1772	1928	2084	2240	2396
1620	1776	1932	2088	2244	2400
1624	1780	1936	2092	2248	2404
1628	1784	1940	2096	2252	2408
1632	1788	1944	2100	2256	2412
1636	1792	1948	2104	2260	2416
1640	1796	1952	2108	2264	2420
1644	1800	1956	2112	2268	2424
1648	1804	1960	2116	2272	2428
1652	1808	1964	2120	2276	2432
1656	1812	1968	2124	2280	2436
1660	1816	1972	2128	2284	2440
1664	1820	1976	2132	2288	2444
1668	1824	1980	2136	2292	2448
1672	1828	1984	2140	2296	2452
1676	1832	1988	2144	2300	2456
1680	1836	1992	2148	2304	2460
1684	1840	1996	2152	2308	2464
1688	1844	2000	2156	2312	2468
1692	1848	2004	2160	2316	2472
1696	1852	2008	2164	2320	2476
1700	1856	2012	2168	2324	2480
1704	1860	2016	2172	2328	2484
1708	1864	2020	2176	2332	2488
1712	1868	2024	2180	2336	2492
1716	1872	2028	2184	2340	2496
1720	1876	2032	2188	2344	2500
1724	1880	2036	2192	2348	2504
1728	1884	2040	2196	2352	2508
1732	1888	2044	2200	2356	2512
1736	1892	2048	2204	2360	2516
1740	1896	2052	2208	2364	2520
1744	1900	2056	2212	2368	2524
1748	1904	2060	2216	2372	2528
1752	1908	2064	2220	2376	2532