

	PAGE
Fig. 14—Curves showing pounds of moisture per pound of dry peat, for peat containing different per cents of moisture; per cents of dry peat available for power at different moisture contents, and per cents of the total moisture contained in the wet peat substance which is removed when the moisture content of the dried peat varies from 0 to 90 per cent	56
" 15—Curve showing the effect on the calorific power of wet peat by removing different per cents of the total moisture content	58
" 16—Curves showing the quantity of ammonium sulphate which can be theoretically obtained from fuels having a nitrogen content varying from 0.1 to 3.0 per cent	60
" 17—Diagrammatic section of the Mond by-product recovery producer gas system	74
" 18—Section of Mond gas producer	76
" 19—Section of Cerasoli producer	99
" 20— " " "	99
" 21—Plan of Mond plant designed for burning 100 tons of theoretically dry peat per day of 24 hours	102
" 22—Plan of Mond plant, designed for burning 100 tons of theoretically dry peat for 24 hours, which is to be erected in Italy	118
" 23—Map showing district supplied with gas by the South Staffordshire Mond Gas Company	136
" 24—Apparatus for controlling blowers in order to give constant gas pressure	139
" 25—Device employed for distributing fuel in producers at Staffordshire	141
" 26—Arrangement of automatic control of by-pass between suction and delivery of compressors	143
" 27—Map of Ostfriesland, showing bogs to be cultivated and the district served with electrical energy	164
" 28—Ground plan of power house	166
" 29—Details of Dolberg peat elevator employed at Wiesmoor	172
" 30—Profile of canal	185
" 31—Method of ploughing according to the one machine system	188
" 32—Plan of Mond by-product recovery producer gas plant for gasifying 120-150 tons of dry peat per day	198
" 33—Curves illustrating effect of increase of nitrogen content on the cost of generating power from peat	206
" 34—Curves showing effect of increase of fuel costs on cost of power	207
" 35—Curves showing cost of 1000 cubic feet of gas and of sulphate of ammonia recovered per ton of theoretically dry peat, for peat costing from 50c to \$3 per ton of theoretically dry peat	208