

The current minimum baseline configuration for new computers to be installed on the SIGNET network is:

- 486DX2/66MHz
- 256Kb cache memory
- 16MB RAM
- 1.44" diskette drive
- 300MB hard disk drive
- One (1) parrallel port and two (2) serial ports
- Serial or bus Microsfot mouse
- SVGA video adapter with 2MB on onboard RAM
- 15" MPR-2 low emission colour monitor
- Internal quad-speed CD-ROM (Optional)

**(b) Notebook**

- 486DX2/66MHz
- 16MB RAM
- 1.44" diskette drive
- 300MB hard disk drive
- One (1) parallel port and two (2) serial ports or one (1) parallel port and one (1) serial port with built-in mouse port
- Serial or bus Microsoft mouse
- SVGA video adapter with 2MB on board RAM
- Optional battery pack
- Standard power saving features
- Voltage selectable

**6. CD-ROM**

- NEC MultiSpin 4X I (internal), model 501, with NEC SCSI Interface Kit
- NEC MultiSpin 4XE (external), model 601, with NEC SCSI Interface Kit
- Tohsiba 3501 B (internal)with SCSI Cdaptec 1540 CF card
- Toshiba 3510 E1 (external)with SCSI Cdaptec 1540 CF card
- Mitsumi (IDE)

**7. Scanner**

- Hewlett Packard ScanJetIIs, color scanner, which comes with software to scan graphics.
- Omnipage 5.0 for Windows is recommanded to scan text.

**8. Software**

The following software packages are availabe on the network or on each workstation at no cost to the client and are supported by DFAIT (Corporate Licence):

- Dos 6.2
- Keaterm 2.2
- Quattro Pro 1.0
- Windows 3.1
- WordPerfect 5.2