

Shingles, 612 sq. feet.
 2 Windows 5' x 5' and frames, cotton and wire mesh.
 2 Windows 3½' x 5' and frames, cotton and wire mesh.
 4 Windows 3' x 5' and frames, glass and wire mesh.
 2 Windows 3' x 3½' and frames, glass only.
 2 Doors 2' 9" x 6'
 Hardware (hinges, nails, etc.) Paint (3 coats)
 FOR 2" CONCRETE FLOOR:
 5 bbls. Cement.
 1½ cu. yds. Sand.
 2¾ cu. yds. Gravel.



FRAME OF STRAW LOFT HOUSE.

Photo by Dr. Shutt.

The ventilator in the gable is removable so that the straw can be put in through this opening. A small hinged door would be just as serviceable. It could be shut during cold weather and opened when the weather was mild.

LIST OF MATERIAL REQUIRED FOR FARMER'S POULTRY HOUSE, DOUBLE ROOF
 AND STRAW LOFT.

	Board Feet
Studs, 2" x 4"—262¼ lin. feet.....	175.5
Plate, 2 pcs. 32' x 2" x 4"—64 lin. feet.....	43
Sill, 2 pcs. 32' x 2" x 4" } 2 pcs. 16' x 2" x 4" }	96 lin. feet..... 65
Rafters, 24 pcs. 10' x 2" x 4"—340 lin. feet.....	227
Floor, (T & G) 512 sq. feet (+10%).....	564
Roof Boards, 680 sq. feet.....	680
Shingles, 680 sq. feet	
One Roll Building Paper.	