



**IMAGE EVALUATION
TEST TARGET (MT-3)**



**Photographic
Sciences
Corporation**

23 WEST MAIN STREET
WEBSTER, N.Y. 14580
(716) 872-4503

1.5
1.6
1.8
1.9
2.0
2.2
2.4
2.5

**CIHM/ICMH
Microfiche
Series.**

**CIHM/ICMH
Collection de
microfiches.**



Canadian Institute for Historical Microreproductions / Institut canadien de microreproductions historiques

10

© 1986

Technical and Bibliographic Notes/Notes techniques et bibliographiques

The Institute has attempted to obtain the best original copy available for filming. Features of this copy which may be bibliographically unique, which may alter any of the images in the reproduction, or which may significantly change the usual method of filming, are checked below.

L'Institut a microfilmé le meilleur exemplaire qu'il lui a été possible de se procurer. Les détails de cet exemplaire qui sont peut-être uniques du point de vue bibliographique, qui peuvent modifier une image reproduite, ou qui peuvent exiger une modification dans la méthode normale de filmage sont indiqués ci-dessous.

- | | |
|---|---|
| <input type="checkbox"/> Coloured covers/
Couverture de couleur | <input type="checkbox"/> Coloured pages/
Pages de couleur |
| <input type="checkbox"/> Covers damaged/
Couverture endommagée | <input type="checkbox"/> Pages damaged/
Pages endommagées |
| <input type="checkbox"/> Covers restored and/or laminated/
Couverture restaurée et/ou pelliculée | <input type="checkbox"/> Pages restored and/or laminated/
Pages restaurées et/ou pelliculées |
| <input type="checkbox"/> Cover title missing/
Le titre de couverture manque | <input checked="" type="checkbox"/> Pages discoloured, stained or foxed/
Pages décolorées, tachetées ou piquées |
| <input type="checkbox"/> Coloured maps/
Cartes géographiques en couleur | <input type="checkbox"/> Pages detached/
Pages détachées |
| <input type="checkbox"/> Coloured ink (i.e. other than blue or black)/
Encre de couleur (i.e. autre que bleue ou noire) | <input checked="" type="checkbox"/> Showthrough/
Transparence |
| <input type="checkbox"/> Coloured plates and/or illustrations/
Planches et/ou illustrations en couleur | <input type="checkbox"/> Quality of print varies/
Qualité inégale de l'impression |
| <input type="checkbox"/> Bound with other material/
Relié avec d'autres documents | <input type="checkbox"/> Includes supplementary material/
Comprend du matériel supplémentaire |
| <input type="checkbox"/> Tight binding may cause shadows or distortion along interior margin/
La reliure serrée peut causer de l'ombre ou de la distorsion le long de la marge intérieure | <input type="checkbox"/> Only edition available/
Seule édition disponible |
| <input type="checkbox"/> Blank leaves added during restoration may appear within the text. Whenever possible, these have been omitted from filming/
Il se peut que certaines pages blanches ajoutées lors d'une restauration apparaissent dans le texte, mais, lorsque cela était possible, ces pages n'ont pas été filmées. | <input type="checkbox"/> Pages wholly or partially obscured by errata slips, tissues, etc., have been refilmed to ensure the best possible image/
Les pages totalement ou partiellement obscurcies par un feuillet d'errata, une pelure, etc., ont été filmées à nouveau de façon à obtenir la meilleure image possible. |
| <input type="checkbox"/> Additional comments:
Commentaires supplémentaires: | |

This item is filmed at the reduction ratio checked below/
Ce document est filmé au taux de réduction indiqué ci-dessous.

10X	14X	18X	22X	26X	30X
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
12X	16X	20X	24X	28X	32X

The copy filmed here has been reproduced thanks to the generosity of:


Library of the Public
Archives of Canada

The images appearing here are the best quality possible considering the condition and legibility of the original copy and in keeping with the filming contract specifications.

Original copies in printed paper covers are filmed beginning with the front cover and ending on the last page with a printed or illustrated impression, or the back cover when appropriate. All other original copies are filmed beginning on the first page with a printed or illustrated impression, and ending on the last page with a printed or illustrated impression.

The last recorded frame on each microfiche shall contain the symbol \rightarrow (meaning "CONTINUED"), or the symbol ∇ (meaning "END"), whichever applies.

Maps, plates, charts, etc., may be filmed at different reduction ratios. Those too large to be entirely included in one exposure are filmed beginning in the upper left hand corner, left to right and top to bottom, as many frames as required. The following diagrams illustrate the method:



L'exemplaire filmé fut reproduit grâce à la générosité de:


La bibliothèque des Archives
publiques du Canada

Les images suivantes ont été reproduites avec le plus grand soin, compte tenu de la condition et de la netteté de l'exemplaire filmé, et en conformité avec les conditions du contrat de filmage.

Les exemplaires originaux dont la couverture en papier est imprimée sont filmés en commençant par le premier plat et en terminant soit par la dernière page qui comporte une empreinte d'impression ou d'illustration, soit par le second plat, selon le cas. Tous les autres exemplaires originaux sont filmés en commençant par la première page qui comporte une empreinte d'impression ou d'illustration et en terminant par la dernière page qui comporte une telle empreinte.

Un des symboles suivants apparaîtra sur la dernière image de chaque microfiche, selon le cas: le symbole \rightarrow signifie "A SUIVRE", le symbole ∇ signifie "FIN".

Les cartes, planches, tableaux, etc., peuvent être filmés à des taux de réduction différents. Lorsque le document est trop grand pour être reproduit en un seul cliché, il est filmé à partir de l'angle supérieur gauche, de gauche à droite, et de haut en bas, en prenant le nombre d'images nécessaire. Les diagrammes suivants illustrent la méthode.



(All rights reserved.)

ADVANCE PROOF—(Subject to revision.)

This proof is sent to you for discussion only, and on the express understanding that it is not to be used for any other purpose whatever.—(See Sec 40, of the Constitution.)

Canadian Society of Civil Engineers.

INCORPORATED 1887.

TRANSACTIONS.

N.B.—This Society, as a body, does not hold itself responsible for the facts and opinion stated in any of its publications.

FRASER RIVER BRIDGE.

CANADIAN PACIFIC RAILWAY, MISSION BRANCH.

By H. J. CAMBIE, M. CAN. SOC. C. E.

To be read October 22nd, 1891.

To render the following description of the bridge over the Fraser River on the Mission Branch of the Canadian Pacific Railway intelligible, it is necessary to offer a few words of explanation as to the location, and the reasons therefor.

The Fraser River, after following a course nearly due south for 300 miles, breaks through the Cascade range of mountains by the Yale Cañon and continues on the same course to the Village of Hope about thirty miles from the boundary of the United States (49th parallel.) It then turns sharply to the west and flows in that direction for about 100 miles in a wide alluvial valley, till it empties into the Strait of Georgia. This is known as the lower Fraser and the lands on either bank are very fertile, forming the best agricultural district in British Columbia.

The main line of the Canadian Pacific Railway follows the right bank of the Fraser to Port Hammond, where it turns northward to Burrard Inlet and the City of Vancouver, while the Westminster Branch diverges to the city of that name situate on the Fraser River, about twenty miles from its mouth.

To connect the Canadian Pacific with the railway systems of the State of Washington, Mission Station, about forty miles from Vancouver, was selected as the most suitable point from which to branch off to the south, and the Fraser River had therefore to be crossed in that neighborhood.

The actual site of the bridge was selected in the longest straight reach in that part of the river, and which showed no signs of having changed its course in recent years. It is there a considerable depth all the way across—1,590 feet wide at high tide level, 42 feet deep near the north, and 25 feet deep near the south bank. A short distance above the bridge it is 200 feet narrower, and a similar distance below, 200 feet wider. In winter there is six feet of tide which decreases gradually for about twenty-five miles further up where it ends. Freshets usually occur in June or July and have risen as much as seventeen feet, continuing in flood for a couple of months.

With these characteristics it was hoped that there would not be much trouble with ice or driftwood, and that the bottom would be less likely to scour than elsewhere. Also that the water would not be dammed up to any appreciable extent by the piers, for on the south bank is a dyke six feet high, which reclaims from the overflow of the river about 10,000 acres of magnificent land. This dyke was completed in the winter of 1889-90 under the superintendence of Mr. G. A. Keefer, M. Can. Soc. C. E.

The bottom is of silt, which is probably of great depth, for the valley from Hope downwards has evidently at no very distant (geological) period been one of the great fiords or inlets which

reach from the Pacific Ocean, far into the Cascade range of mountains, and are found all the way from Puget Sound to Alaska.

These inlets are exceedingly deep, and this one which has been filled up during the lapse of ages by the silt brought down by the Fraser River, was no exception to the rule.

The work was started rather hurriedly, only four days being taken to prepare a plan and specification, and contractors having only three days in which to tender, nevertheless the work has not been materially altered since its commencement. The viaduct is of wood 3,000 feet long, and consists of pile trestle approach 150 feet, one span 100 feet, seven spans 150 feet, swing truss 239 feet over all, one span 150 feet, and 1,250 feet of pile trestle approach. Howe truss spans of 150 feet each were selected as being the largest which it is desirable to build in wood.

The chief difficulty lay in designing piers of moderate cost which should be safe in winter when there is thirty-five feet of water, a current of two and one half miles an hour, and at times ice which shoves with great force, and in summer when there is fifty-nine feet of water, a current of five miles an hour and drift-wood coming in tangled masses, sometimes nearly an acre in area, as well as trees of great size.

Piers were originally proposed with four rows of piles placed at two feet centres both ways, but the piles averaging fifty-five feet in length the butts were so large, that it was found impossible to drive them so close together, and consequently only three rows could be used, placed three feet centres across the current, that is in the line of the bridge, and two feet centres up and down stream.

Around these piles cribs were built of square timber, with ties nine feet apart for which spaces were left between the piles. The cribs are eleven feet wide outside measurement, and forty-one feet long, with noses at each end projecting five and a half feet farther and meeting in a right angle.

Ballast chambers were formed between the ties in two of the spaces—the centre row of piles being left out—and the cribs were sunk as built. When they reached bottom they were filled to the top with rock small enough to sink between the piles and form a solid mass. Rip-rap was then placed on the outside, eight feet deep next the cribs and extending fifty feet in all directions from them.

Some difficulty was experienced in sinking such a large mass of timber with small ballast chambers, and in some cribs ties near the bottom were allowed to extend six feet outwards, and two ballast platforms formed on each side, which arrangement was convenient for sinking the cribs during construction, but cannot be recommended where the bottom is soft, as in the present instance, as the surrounding riprap in settling into the mud, fell away from the platforms leaving a space through which the current scoured the material underneath to some extent before it was noticed and remedied.

The piles are driven about twenty feet into the bottom of the river, and are cut off at the level of high water neap tides, being thus wet to the top twice every day. The cribs are built to the same height and are expected to last for a very long time, as the water is fresh, very cold, and not known to be inhabited by any noxious insects. Resting on the piles are piers formed of framed bents twenty-five feet in height, which places the bridge seat just eight feet above the highest flood known, viz., that of 1882. These have outwaters with a slope of 1 to 1.

Two of the framed piers were in position before the flood of this year (1890) and one of them was tested by a boom of logs descending the river, which a tug was unable to control. They were of long lengths, many of them four feet and upwards in diameter, and struck with such force as to slide up the outwater several feet without jarring it in the least.

For reasons which it is unnecessary to discuss here the swing has been built with an opening of 100 feet on each side of the pivot pier, and far enough from the shore to give twenty-four feet of water in one channel and nineteen feet in the other. This pier is thirty feet in diameter, and being placed so far out in the current has caused a good deal of scour, so much so that the bottom of each channel has to be riprapped right across and for a considerable distance up and down the stream.

The substitution of mattresses of brush for the riprap, or a portion of it, was fully considered, but owing to the depth of water and rapidity of the current it was feared that difficulty would be experienced in sinking them exactly where required. It was found, moreover, that the amount of rip-rap necessary to ensure their remaining permanently in position would bring the cost up to a higher figure than the rip-rap alone.

The swing truss and gear was designated by Mr. P. A. Peterson, the Chief Engineer of the Canadian Pacific Railway Company, and has an arched upper chord, fifty of the sticks in which are about 6" x 12" and range, from seventy-eight to ninety-seven feet in length. These are of Douglas fir, sound and almost clear, and were sawn by one of the mills at Vancouver.

As a further instance of the facilities afforded by the timber of British Columbia for special classes of bridge work, it is worth mentioning that all the piles used in the false works of this bridge, reached up to the lower chords, and ranged from seventy to eighty-five feet in length.

It is expected that the track will be laid over the bridge early next month. (January, 1891.)

The general character of the bridge will be best seen by reference to the accompanying plans.

VANCOUVER, B. C., December 27th, 1890.

