

**CIHM
Microfiche
Series
(Monographs)**

**ICMH
Collection de
microfiches
(monographies)**



Canadian Institute for Historical Microreproductions / Institut canadien de microreproductions historiques

© 1997

Technical and Bibliographic Notes / Notes techniques et bibliographiques

The Institute has attempted to obtain the best original copy available for filming. Features of this copy which may be bibliographically unique, which may alter any of the images in the reproduction, or which may significantly change the usual method of filming are checked below.

- Coloured covers / Couverture de couleur
- Covers damaged / Couverture endommagée
- Covers restored and/or laminated / Couverture restaurée et/ou pelliculée
- Cover title missing / Le titre de couverture manque
- Coloured maps / Cartes géographiques en couleur
- Coloured ink (i.e. other than blue or black) / Encre de couleur (i.e. autre que bleue ou noire)
- Coloured plates and/or illustrations / Planches et/ou illustrations en couleur
- Bound with other material / Relié avec d'autres documents
- Only edition available / Seule édition disponible
- Tight binding may cause shadows or distortion along interior margin / La reliure serrée peut causer de l'ombre ou de la distorsion le long de la marge intérieure.
- Blank leaves added during restorations may appear within the text. Whenever possible, these have been omitted from filming / Il se peut que certaines pages blanches ajoutées lors d'une restauration apparaissent dans le texte, mais, lorsque cela était possible, ces pages n'ont pas été filmées.
- Additional comments / Commentaires supplémentaires:

L'Institut a microfilmé le meilleur exemplaire qu'il lui a été possible de se procurer. Les détails de cet exemplaire qui sont peut-être uniques du point de vue bibliographique, qui peuvent modifier une image reproduite, ou qui peuvent exiger une modification dans la méthode normale de filmage sont indiqués ci-dessous.

- Coloured pages / Pages de couleur
- Pages damaged / Pages endommagées
- Pages restored and/or laminated / Pages restaurées et/ou pelliculées
- Pages discoloured, stained or foxed / Pages décolorées, tachetées ou piquées
- Pages detached / Pages détachées
- Showthrough / Transparence
- Quality of print varies / Qualité inégale de l'impression
- Includes supplementary material / Comprend du matériel supplémentaire
- Pages wholly or partially obscured by errata slips, tissues, etc., have been refilmed to ensure the best possible image / Les pages totalement ou partiellement obscurcies par un feuillet d'errata, une pelure, etc., ont été filmées à nouveau de façon à obtenir la meilleure image possible.
- Opposing pages with varying colouration or discolourations are filmed twice to ensure the best possible image / Les pages s'opposant ayant des colorations variables ou des décolorations sont filmées deux fois afin d'obtenir la meilleure image possible.

This item is filmed at the reduction ratio checked below / Ce document est filmé au taux de réduction indiqué ci-dessous.

	10x		14x		18x		22x		26x		30x	
									✓			
	12x		16x		20x		24x		28x		32x	

The copy filmed here has been reproduced thanks to the generosity of:



Library
Agriculture Canada

The images appearing here are the best quality possible considering the condition and legibility of the original copy and in keeping with the filming contract specifications.

Original copies in printed paper covers are filmed beginning with the front cover and ending on the last page with a printed or illustrated impression, or the back cover when appropriate. All other original copies are filmed beginning on the first page with a printed or illustrated impression, and ending on the last page with a printed or illustrated impression.

The last recorded frame on each microfiche shall contain the symbol \rightarrow (meaning "CONTINUED"), or the symbol ∇ (meaning "END"), whichever applies.

Maps, plates, charts, etc., may be filmed at different reduction ratios. Those too large to be entirely included in one exposure are filmed beginning in the upper left hand corner, left to right and top to bottom, as many frames as required. The following diagrams illustrate the method:



hanks

L'exemplaire filmé fut reproduit grâce à la générosité de:

Bibliothèque
Agriculture Canada

ity
ility

Les images suivantes ont été reproduites avec le plus grand soin, compte tenu de la condition et de la netteté de l'exemplaire filmé, et en conformité avec les conditions du contrat de filmage.

lmed
n
pres-
li
n the
s-
nted


Les exemplaires originaux dont la couverture en papier est imprimée sont filmés en commençant par le premier plat et en terminant soit par la dernière page qui comporte une empreinte d'impression ou d'illustration, soit par le second plat, selon le cas. Tous les autres exemplaires originaux sont filmés en commençant par la première page qui comporte une empreinte d'impression ou d'illustration et en terminant par la dernière page qui comporte une telle empreinte.

N-
").

Un des symboles suivants apparaîtra sur la dernière image de chaque microfiche, selon le cas: le symbole \rightarrow signifie "A SUIVRE", le symbole ∇ signifie "FIN".


be
to
he

Les cartes, planches, tableaux, etc., peuvent être filmés à des taux de réduction différents. Lorsque le document est trop grand pour être reproduit en un seul cliché, il est filmé à partir de l'angle supérieur gauche, de gauche à droite, et de haut en bas, en prenant le nombre d'images nécessaire. Les diagrammes suivants illustrent la méthode.



MICROCOPY RESOLUTION TEST CHART

(ANSI and ISO TEST CHART No. 2)



APPLIED IMAGE Inc



1653 East Main Street
Rochester, New York 14609 USA
(716) 482-0300 - Phone
(716) 288-5989 - Fax

BETTER BELT LACING



By J. MACGREGOR SMITH, B.S.A.
 Professor Agriculture & Engineering, College of Agriculture, University of Saskatchewan

RECEIVED
 JUN 18 1910
 Int. Agr. Dept.

Practically every farmer owns and operates an engine, a feed grinder or some other power machine. He should be able to lace a belt. To the average man belt lacing always appears to be a very mysterious operation and in threshing time the whole gang gathers round the separator man as if he were a wizard, when he is lacing a broken belt. The methods of lacing belts are



legion and it is impossible to state which is the best, because there are many good ways. We do not want to convert you to our way of doing it, but if you have not already a very definite system, we will, by means of diagrams endeavor to show clearly three different ways and they will fulfill your requirements. With a little practice you can readily "catch on."




First of all, what is our problem? It is to make a smooth joint and one that will be as strong as the belt itself. The first step is to cut the ends of the belt square. Use a small try square. This is important and takes no more time than it does to do it as shown in Fig. 8. Next is the location of the holes. For small leather belts one row of holes will be found sufficient and should be spaced with some relation to the size of the belt.

Fig. 1, 2, 3, and 4 show a single row of holes in each case. Fig. 7 shows a double row especially adapted to rubber and canvas belts. Fig. 8 shows how the work should not be done. With leather belts use a good belt punch, but for rubber and canvas belts the holes should be made with an awl and not with a hollow punch, which cuts off many strands and materially weakens the belt. The tine of an old pitchfork makes a very good tool after being sharpened a little at the point, the other end being bent to form a handle.

SINGLE LACING


Fig. 9 shows an example of single lacing. The lace is straight on the pulley side and crosses on the side away from the pulley. Starting on the pulley side the ends are put through the holes 1, 1', and then across to 2, 3, 4 and 5, here the lace is again put through hole 4 (marked 6) and



hole 5 (marked 7) then to 8, 9, 10 and 11, the other half of the belt is finished in exactly the same way. There are different ways of finishing, either a square knot can be tied, or the ends tucked in around some of the other laces. In case the belt runs over an idle pulley a good way to finish it would be to run from 11 to 1 in both cases and punch another hole at the point indicated by X, and finish as in Fig. 10.

DOUBLE LACING

Fig. 10 shows an example of this lace. The lace is straight and double on the pulley side and crossed on the side away from the pulley. Starting up through the holes 1, 1, follow the holes as numbered to the position 10 (which is also the first hole). From 9 the lace goes down through 10 up through 11, down through 12 and up through 11 again. When it is pulled tight the same



applies to the opposite side of the joint. This will leave only one thickness of lace in the middle, which will allow the belt to fit the crowned pulley better. The loops 10-11, 11-12 makes the double lace rise on to the pulley without any jar, whereas, if it was made three ply in the middle this would not be the case. Another method of finishing is shown to the right, a loop is formed and pushed through the last hole, a short piece of lace is inserted and the loop pulled tight. This can easily be removed with a pair of pliers. Burning the end of a lace makes it hard and it can be more easily pushed through the holes.



Example of Single LACING Showing Side of belt away from the Pulley

DOUBLE RINGS LACE


The single hinge lace is similar, the only difference being the lace passes through each hole once instead of twice. Therefore we will not go into details with it. The double hinge lace is harder to describe but by the aid of numbers we hope to make it clear. Starting as shown in Fig. 11 the path of the lace B is as follows:

Between belt 1 and belt 2 and up through hole 2 ; then

"	"	1	"	2	"	"	"	1	;	"
"	"	1	"	2	"	"	"	3B	;	"
"	"	1	"	2	"	"	"	4B	;	"
"	"	1	"	2	"	"	"	3B	;	"
"	"	1	"	2	"	"	"	4B	;	"
"	"	1	"	2	"	"	"	5B	;	"
"	"	1	"	2	"	"	"	6B	;	"
"	"	1	"	2	"	"	"	5B	;	"
"	"	1	"	2	"	"	"	6B	;	"
"	"	1	"	2	"	"	"	7B	;	"
"	"	1	"	2	"	"	"	8B	;	"
"	"	1	"	2	"	"	"	7B	;	"
"	"	1	"	2	"	"	"	8B	;	"
"	"	1	"	2	"	"	"	9B	;	"
"	"	1	"	2	"	"	"	10B	;	"
"	"	1	"	2	"	"	"	9B	;	"
"	"	1	"	2	"	"	"	10B	;	"

Lace A goes between belts 1 and 2 and down through hole 2 ; then


"	"	1	"	2	"	"	"	3A	;	"
"	"	1	"	2	"	"	"	4A	;	"
"	"	1	"	2	"	"	"	3A	;	"
"	"	1	"	2	"	"	"	4A	;	"
"	"	1	"	2	"	"	"	5A	;	"
"	"	1	"	2	"	"	"	6A	;	"
"	"	1	"	2	"	"	"	5A	;	"
"	"	1	"	2	"	"	"	6A	;	"
"	"	1	"	2	"	"	"	7A	;	"
"	"	1	"	2	"	"	"	8A	;	"
"	"	1	"	2	"	"	"	7A	;	"
"	"	1	"	2	"	"	"	8A	;	"
"	"	1	"	2	"	"	"	9A	;	"
"	"	1	"	2	"	"	"	10A	;	"
"	"	1	"	2	"	"	"	9A	;	"
"	"	1	"	2	"	"	"	10A	;	"



Example of Double Hinge Lace Showing Side of belt away from the Pulley.


This lace is recommended for a belt running over small pulleys, as a windstacker. It is also good for a drive belt. The advantage of beginning at the center of the belt is that two men can lace at the same time, one to the right and the other to the left. However all laces shown can be started at one side if desired. Care being taken not to pull it too tight. One end should not be put through two holes in succession, and both ends of the lace must be passed between the ends of the belt to the opposite side before either is put through the next hole.

1. The diagram shows a cross-section of a belt with a central slot. The slot is labeled "Belt 1" and "Belt 2". The belt is shown passing over a pulley. The pulley is labeled "Pulley". The belt is shown in two positions: one where it is on the pulley and one where it is off. The belt is shown in two positions: one where it is on the pulley and one where it is off.



Double Hinge Lace for belts running over small pulleys

Regarding the "Bootleg" lace we have had no experience, but one writer says: "Wherever possible, especially for rubber and cotton belts, the bootleg lacing is used, but it must be confessed this form lacks much of popularity. In respect that it gives uniform and continuous belt contact; in that good stout twine serves for it as well as the most expensive whang leather; in that it is easily and quickly made; and that it will outlast any other lacing known, it is pretty nearly perfect. In that it looks 'perfectly horrid' and in that it is quite likely to knock a thumb off an incautious operator or spectator, it is imperfect. This form of lacing is called 'bootleg' not because of any relation to booze but because it is made exactly as the old-fashioned bootlegs were sewn up."



Some readers may be able to tell what their experience has been with this type or with any especially good forms they may have used.

In closing let us remind you that a leather belt runs with the hair or smooth side next to the pulley, and a rubber belt with the seam (near the center of one side) away from the pulley.





