







23 WEST MAIN STREET WEBSTER, N.Y. 14580 (716) 872-4503 Ca

State It

25



Technical and Bibliographic Notes/Notes techniques et bibliographiques

The Institute has attempted to obtain the best original copy available for filming. Features of this copy which may be bibliographically unique, which may alter any of the images in the reproduction, or which may significantly change the usual method of filming, are checked below.

L'Institut a microfilmé le meilleur exemplaire qu'il lui a été possible de se procurer. Les détails de cet exemplaire qui sont peut-être uniques du point de vue bibliographique, qui peuvent modifier une image reproduite, ou qui peuvent exiger une modification dans la méthode normale de filmage sont indiqués ci-dessous.

	Coloured covers/		Coloured pages/	
$\overline{}$	Couverture de couleur		Pages de couleur	0
				be
	Covers damaged/		Pages damaged/	th
	Couverture endommagée		Pages endommagées	si
				ot
	Covers restored and/or laminated/		Pages restored and/or laminated/	fir
$ \mathcal{I} $	Couverture restaurée et/ou pelliculée		Pages restaurées et/ou pelliculées	si
				or
	Cover title missing/	<u> </u>	Pages discoloured steined or foxed/	
	Le titre de couverture manque		Pages décolorées, techetées ou niguées	
<u> </u>	La titla de converture mandre		rages decolorees, taciletess ou piquees	
	Calcurat mana/	_	Denne detected/	
	Coloured maps/		Pages détachée	TH
	Cartes geographiques en couleur		rages detachees	sh
				TI
	Coloured ink (i.e. other than blue or black)/		Showthrough/	w
	Encre de couleur (i.e. autre que bleue ou noire)		Transparence	
				M
	Coloured plates and/or illustrations/		Quality of print varies/	di
	Planches et/ou illustrations en couleur		Qualité inégale de l'impression	en
				ba
	Bound with other meterial/		Includes supplementary material/	rig
	Relié avec d'autres documents		Comprend du matériel supplémentaire	re
				m
	Tight binding may cause shadows or distortion		Only edition available/	
	along interior margin/		Seule ádition disponible	
	La reliure serrée peut causar de l'ombre ou de la			
	distortion la long de la marge intérieure			
			Pages wholly or partially obscured by errata	
	Blank loover added during restoration may		slips, tissues, etc., have been retilmed to	
	annear within the text. Whenever nossible these		ensure the best possible image/	
	beve been omitted from filming/		Les pages totalement ou partiellement	
	Il se peut que certaines pages bianches aigutées		obscurcies par un teulliet d'errate, une pelure,	
	lore d'une restauration annaraissant dans le texte		etc., ont ete tilmees a nouveau de taçon a	
	mais loreque cele était nossible, ces nages n'ont		obtenir la meilleure image possible.	
	nas átá filmáas.			
]	Additional comments:/			
	Lommentaires subdiementaires:			

10X	14X	18X	2	2X	26X		30X
1	2X	16X	20X	24X		28X	3

Th 80

> Th po of fil

1 t

The copy filmed here has been reproduced thanks to the generosity of:

Library of the Public Archives of Canada

The images appearing here are the best quality possible considering the condition and legibility of the original copy and in keeping with the filming contract specifications.

Original copies in printed paper covers are filmed beginning with the front cover and ending on the last page with a printed or illustrated impression, or the back cover when appropriate. All other original copies are filmed beginning on the first page with a printed or illustrated impression, and ending on the last page with a printed or illustrated Impression.

The last recorded frame on each microfiche shall contain the symbol \longrightarrow (meaning "CON-TINUED"), or the symbol ∇ (meaning "END"), whichever applies.

Maps, plates, charts, etc., may be filmed at different reduction ratios. Those too large to be entirely included in one exposure are filmed beginning in the upper left hand corner, left to right and top to bottom, as many frames as required. The following diagrams illustrate the method:



L'exemplaire filmé fut reproduit grâce à la générosité de:

La bibliothèque des Archives publiques du Canada

Les images suivantes ont été reproduites avec le plus grand soin, compte tenu de la condition et de la netteté de l'exemplaire filmé, et en conformité avec les conditions du contrat de filmage.

Les examplaires originaux dont la couverture en papier est imprimée sont filmés en commençant par le premier plat et en terminant solt par la dernière page qui comporte une empreinte d'impression ou d'illustration, soit par le second plat, selon le cas. Tous les autres exemplaires originaux sont filmés en commançant par la première page qui comporte une empreinte d'impression ou d'illustration et en terminant par la dernière page qui comporte une telle empreinte.

Un des symboles suivants apparaîtra sur la dernière image de chaque microfiche, selon le cas: le symbole → signifie "A SUIVRE", le symbole V signifie "FIN".

Les cartes, planches, tableaux, etc., peuvent être filmés à des taux de réduction différents. Lorsque le document est trop grand pour être reproduit en un seul cliché, il est filmé à partir de l'angle supérieur gauche, de gauche à droite, et de haut en bas, en prenant le nombre d'images nécessaire. Les diagrammes suivants illustrent la méthode.



1	2	3
4	5	6

etails du odifier une mage

S

errata to

peiure, on à

32X



SHORT LINE RAILWAY.

dee map al Sud

MR. LIGHT'S REPORTS UPON THE SURVEY OF THE NORTHERN OR QUEBEC ROUTE FOR THE SHORTEST AND MOST ADVAN-TAGEOUS RAILWAY LINE FROM MONTREAL TO HALIFAX AND ST. JOHN, N. B., RECOMMENDING

A COMBINATION LINE

(Combining the Quebec and Etchemin Valley with the Lake Megantic routes) for the same.

PRINTED BY ORDER OF THE BOARD OF TRADE AND CITIZENS' COMMITTEE OF QUEBEC.

QUEBEC.

1885.



PREFACE TO REVISED SUPPLEMENTARY REPORT.

The Board of Trade and Citizens' Committee of Quebec have thought it expedient to publish the accompanying official report on the Short Line Railway, with the view of meeting the altered aspect of the case, as shewn forth in the recent report and maps of the Government Engineer of Dominion Railways, where he advocates the adoption of certain lines which, I did not understand, to be even under consideration, at the date of my first report,—(26th March.)

The lines first surveyed by Messrs. Vernon Smith and Ambrose Duffy, passed North of Moosehead Lake.

The line now advocated passes through the said Lake to Mattawamkeag, and in order to meet this altered view of the matter, a revised (or supplementary report) was submitted (10th May) in place of the first,—but it has not appeared, having, it is presumed, arrived too late,—hence the necessity of publishing it in this form.

It will be apparent that material differences exist in the tables of distances, as given by the Government Chief Engineer, and those given by myself; Mr. Schreiber's being invariably the shorter when the Southern lines are considered.

Mr. Schreiber commences his distances at *Montreal*, and passes directly East over the St. Lawrence,—while my calculations are taken round by *Lachine*, where the Canadian Pacific Railway Company actually mean to pass the St. Lawrence by a Bridge, and to which point they have nearly completed a double track railway from Mile-End.

From Quebec Gate Barracks Station west to Lachine is 11 miles — which distance, *must* be retraced East to get opposite Montreal, and will thus add some twenty (20) miles to all Mr. Schreiber's Southern route figures.

The Government Chief Engineer has ignored the "Combination Line" in the arrangement of his map; this line will shorten the Quebec connections by 27 (twenty-seven) and 25 (twenty-five) miles, respectively, to St. John and Halifax; Vide pages 9 and 10, tables 14 and 17, of Mr. Schreiber's report, and appendix 6 of mine, as follows : Montreal to St. John via Quebec and Hartland (table 14).... 508 miles.

Saving by "Combination Line"..... 27

tha

(See Mr.

kea, No.

cula

Que feet

tual

at a

the ing

royn

to all

pose

way the S

the ."

and

addit betw

still h

such 40 fee

all the

stated

thus

facts |

surve

Adam

and A

Light,

Chaud

which

his re furnis

answe

Montreal to Halifax via Quebec and Hartland (table 17).... 735 miles. "Chesuncook (app. 6)... 710 "

Saving by "Combination Line"...... 25

In all calculations of distances East of Passadumkeag and Mattawamkeag, I have, of course, assumed that the existing lines of travel will be used for the present, as no survey had been made of the line, between Mattawamkeag and St. Andrew's; while Mr. Schreiber has traced on his map a direct line across the eastern part of Maine, from Mattawamkeag to St. Andrew's, through a difficult country which has not been surveyed, (see page 8 of his report) and has calculated three of his distances on this basis.

This road may not be constructed for many a year, and should it even be built, my knowledge of the country, acquired during (10) ten years service as Chief Engineer of the New Brunswick Government Railways, convinces me that the connection between it, and the Province of *Nova Scotia* will be through St. John, and over the existing lines of railway; the details of the several lines are accurately shown in my appendix 1 and 6-(attached,) and will be seen to be much longer than those dotted by Mr. Schreiber in his map.

The country between Moosehead Lake and Mattawamkeag,—a distance of some 65 miles,—has also been very imperfectly surveyed, and the line which Mr. Schreiber says "takes the first place" pesses over a supplementary summit 950 feet in height, between the Penobscot and Kennebec rivers, which cannot apparently, be avoided. (See Mr. Moses Burpee's report, page 40.) This summit destroys the usefulness of this part of the line as an Inter-provincial *freight* line railway, virtually lengthening it very materially, (see appendix 4 (four) of my supplementary report) and would have the inevitable effect of turning such traffic as might have passed Portland, down south over the existing "Bangor and Piscataquis" Railway, into contiguous American sea-ports.

This détour via Passadumkeag would lengthen the distance to the Maritime Provinces some 84 miles. On page 6 of his report, Mr. Schreiber says "the line" "to Halifax via Moosehead, Mattawamkeag, Hervey, Fredericton and Salisbury (line No. 6) takes the first place, being one mile shorter than via north of Moosehead Lake, Canterbury, Fredericton and Salisbury." The only line surveyed north of Moosehead Lake was that examined by Messrs. Vernon Smith and Ambrose Duffy, who found excellent lines. (See Mr. Smith's report, ending page 52, and Mr. Duffy's, ending page 26.

In my supplementary report it has been shown that the line from Montreal to Halifax via Quebec and Chesuncook, is 10 miles shorter 508 miles. 481 "... 27 " 735 miles. 710 "

and Mattas of travel the line, behreiber has faine, from ntry which s calculated

nd should it ing (10) ten lovernment nd the Prothe existing ately shewn nuch longer

amkeag, —a rveyed, and pesses over Penobscot ed. (See Mr. a usefulness ailway, virfour) of my t of turning er the exists American

distance to report, Mr. tawamkeag, first place, Canterbury, h of Mooseof Ambrose ort, ending

ie line from iles shorter than the line between the same points decomposite and Obesuncook. (See appendix 6, tables 5 and 6.) It is ther form size miles shorter that Mr. Schreiber's line "No. 6" (page 6 of his report.) When the data afforded by the imperfect surveys between Mooschead and Mattawamkeag are discounted, added to the further fact that 118 miles on line No. 6, are not surveyed at all, the above will be considered a close calculation on Mr. Schreiber's part.

On page 13 of Mr. Schreiber's report, all the northern lines via Quebec to St. John and Halifax are set down as having grades of 35 feet to the mile, and curves of 10° (tep) degrees, making them virtually equal to 109 feet on the mile. (See appendix 4.) This, I am at a loss to understand; true, there is one short grade of 35 feet to the mile between Hochelaga and Mile-End, common to all trains passing from Montreal to Halifax, also, three short curves of 10° degrees round Bedford Basin, some four miles from Halifax, equally common to all lines; but these have no connection whatsoever with my proposed Chesuncook Line.

There are such grades and curves on the New Brunswick Railway between Hartland—(the objective point of last year's survey of the St. Charles line)—and Canterbury, but as I have before remarked the "Combination Line" would strike Canterbury and not Hartland, and would therefore avoid these objectionable grades and curves, in addition to saving 25 miles of distance. If I had found a dead level between Quebec and Hartland, the usefulness of my survey would still have been destroyed by being connected *there*, with a road having such grades and curves, but I repeat that maximum grades of 35 to 40 feet per mile, and minimum curves of 4° degrees, can be obtained all the way from Quebec to Moneton on the "Combination Line," as stated in my supplementary report.

Mr. Schreiber, in his report speaks of thirty (30) lines of railways; thus inferring an exhaustive examination of the subject,—but, the facts show that only five (5) through lines have been, (but imperfectly) surveyed, viz:

"No. 1."-From "St. Lambert to Mattawamkeag," by Messrs. R. Adams Davy, Moses Burpee, and Parker Spofford.

"No. 2."--From "Megantic to Hervey" by Messrs. Vernon Smith, and Ambrose Duffy.

"No. 3."—From "St. Charles to Hartland" by Messrs. A. L. Light, and Y. B. Fellows.

"No. 4."-From "St. Roch to Edmonston" by Mr. Crawford.

"No. 5."-From "River du Loup to Edmonston" by the same.

Mr. Wicksteed also made a careful barometrical examination from Chaudiere Junction to the Allaguash River, via the Etchemin valley which I shall have occasion to mention further on. On page 51 of his report, Mr. Schreiber institutes certain "queries" to which he furnishes the replies and comments. I quote them here with my answers.

MR. SCHREIBER.

Query No. 1.

"Mr. Light, in pages Nos. 2 and 8 of his report expresses a belief that the maximum grades between Quebec and Moncton, by way of Chesuncook and Hervey, would be 85 feet to the mile, and that the surveys of last season have established that the grades above mentioned can be obtained between Chesuncook and Hervey."

"Mr. Vernon Smith's survey, the only one made between Chesuncook and Hervey last season, shews maximum grades of 53 feet to the mile."

MR. LIGHT.

Answer No. 1.

The following are my reasons for this belief :

1st. A careful barometrical examination, which I made myself last Spring from Quebec as far as "Baker's Brook"—three-quarters of the distance to Chesuncook when a most satisfactory line was found. On the remaining fourth part of the line, which I did not examine, Mr. Vernon Smith reports "that from Lake Chesuncook towards Quebec there is a fine level open valley which might be utilized for a direct line to Quebec."

2nd. A subsequent careful examination of the ground by Mr. Wicksteed, C. E., made last Autumn, having for result the corroboration of my figures.

3rd. The testing of the summit by spirit levels, further confirming the same.

I will, in reply, quote the last clause of Mr. Vernon Smith's report, page 32:-" On the whole the route proposed presents a very favorable line for the construction of an economical first-class railway. On the profile shewn there is no gradient exceeding 1 per 100, or 58 feet per mile, and no curve of over 4 degrees, or 1,433 feet radius. With the exception of three places (each of less than 6 miles in length), there is no necessity for even this gradient. By slightly increasing the earth-works I believe that on a re-survey the objectionable points may be greatly improved, and that the whole distance from Hervey to Chesuncook may be covered with gradients not exceeding 35 feet per mile, and with no curve exceeding. 3 degrees, or 1,910 feet radius."

" Mr. distance via Mat " This

Che ed.

M

line v

the tr

vince

save a

and

inten

lonial

very

would

other

"T

ME. CHRRISER.

The line between Quebec and Chesuncook has not been surveyed.

Query No. 2:

Mr. Light states page 3 that this line would have a marked effect on the trade with the Maritime Provinces * * * as it would save about 300 miles to St. John and 150 to Halifax.

"This saving it is presumed, is intended to be over the Intercolonial Railway route, but it is very approximate; the results would be somewhat similar to other short lines to the South."

Query No. 3.

"Mr. Light on page 6 gives the distance from Montreal to Halifax via Mattawamkeag at 769 miles." "This should be 720 miles."

MR, LIGHT.

I slways considered that a survey of this line was most important, and strongly recommended to Mr. Schreiber that it should be made, by telegram dated 18th August, 1884 His reply was a *peremptory refusal*. Mr. Wicksteed's barometrical examination was subsequently ordered, having the result already stated of corroborating my figures.

Answer No. 2.

"This saving of distances is of course, over the Intercolonial Railway route there being no other existing line to compare with.

The distances, I give are as correct as is possible from the data on hand, and are therefore not "very approximate."

P The lower altitude of the main summit on this line is alone equal to a saving of about 40 miles of distance,-not to speak of a number of supplementary summits on the "Megantic Line" with 'deep intervening depressions involving a vast amount of rise and tall which can be only properly equated when a correct profile is submitted. I have already (in the body of my report) made mention of the supplementary summit between Moosehead Lake and Mattawamkeag 950 feet in height, (See Mr. Moses Burpee's report page 40.). It is surely evident that such extraordinary summits overcome with grades of 74 feet to the mile, and curves of 8° degrees must render this line entirely unfit for an inter-provincial freight line railway.

Answer No. 3.

I estimate the distance via Lachine—(for reasons already mentioned)—while Mr. Schreiber measures directly from Montreal; this accounts for 20 (twenty) miles of the extra distance he names.

ny reasons

netrical exade myself peo as far as ree-quarters esuncook ory line was ning fourth h I did not a Smith reke Chesunc there is a which might rect line to

careful exund by Mr. ide last Auilt the corros.

the summit r confirming

note the last Smith's rethe whole esents a very construction st-class railshewn there eding 1 per nile, and no ees, or 1,433 e exception of less than 6 is no necesadient. By carth-works s-survey the ay be greatt the whole to Chesunith gradients per mile, and g. 3 degrees,

MR. LIGHT.

V.Lan

2ndly. East of Mattawamkeag, I measure the distance over the existing lines of railway, through St. John to Halifax; while Mr. Schreiber estimates over 113 miles of country which is *unsurveyed*. (See his report, page 8.)

This fact accounts for the further variance in our figures. I have taken my measurements over the existing lines of railway from a practical conviction that the same will be in use for many a year to come. The details of my distances will'be found in Appendix 6, tables 10 and 11, supplementary report, and are as correct as an intimate knowledge of the country and the use of accurate time tables will permit.

Query No. 4.

"Mr. Light gives on page 6 the distance from Montreal to St. John via Mattawamkeag at 493 miles." This should be 450 miles.

Query No. 5.

"Mr. Light gives on page 7 the distance from Montreal to Hervey via Quebec as 248 miles."

"This should be 406 miles."

"He also gives the distance from Montreal to Mattawamkeag as 240 miles."

"This should be 328 miles.

Mr. Schreiber concludes by saying :

"I have not looked into the matter of distances, &c., beyond the 7th page, but I fear they may be no more accurate than those I have remarked upon."

Answer. No. 4.

My reply to "Query No. 3" also covers this ground, and repetition would be unnecessary.

Answer No. 5.

What I did say was, "the distance from Montreal to Hervey via Quebec To BUILD is 248 miles." (See page 55, Engineer's report.)

The omission of these two little words to build makes all the difference in the statement.

The "inaccuracy" Mr. Schreiber professes to have discovered in my figures, is owing to the fact that the words "to build" have here again been omitted.

MR. LIGHT.

This is a point which can b very easily verified. Сомр

K T

jght

nd b

natte

tteni

ppea

horte

nd "

St T

ilesiles l

53 mi

32 n

ation

rainst

ommo

loosét

kes tl

e dét

an th s line

nd sha bjectio

ammit

nnage

ost va

ilway

He

n: Or

TI

T

ine No

Maxin ine No

Maxin ine No

Maxin

ttawamkeag,

nce over the way, through ; while Mr. ver 118 miles s unsurveyed. 8.)

for the further res. I have ents over the lway from a that the same any a year to f my distances pendix 6, taapplementary rrect as an inf the country ate time tables

o. 4.

ery No. 3" also and repetition ary.

0. 5.

was, "the disto Hervey via is 248 miles." teer's report.) hese two little s all the differ nt.

Mr. Schreibe covered in my the fact tha d" have here

IT

which can b

MR. SCHREIBER.

"It is pretty evident that Mr. ight has been pressed for time, ad has not been able to give the natter of this report his personal tention."

I have given it, on the contrary, very careful consideration.

MR. LIGHT.

To sum up :--On page 6 of his report Mr. Schreiber says, "It thus ppears that the line via Moosehead Lake and Mattawamkeag is the nortest both to St. Andrew's and St. John," viz :--(Lines Nos. "1" nd "2.")

The distance to St. Andrew's and St. John by the said lines is 401 iles—and 451 miles respectively—when the détour of 2C (twenty) iles by Lachine is added this distance becomes 421 miles and 471 miles.

The distance by the "Combination Line" to the above places is 53 miles, and 481 miles respectively;—making, *it is true*, an increase 52 miles to St. Andrew's, and 10 miles to St. John by the "Combiation Line"—but, this extra mileage becomes as nothing when placed gainst the extraordinary summits, steep grades, and sharp curves, mmon to Lines "Nos. 1 and 2" of Mr. Schreiber.

On page 6 Mr. Schreiber further says "line (No. 6) to Halifax via loosehead Lake, Mattawamkeag, Hervey, Fredericton and Salisbury kes the first place."

He states this line (on page 8) to be "720 miles" in length—adding the détour at Lachine it becomes 740 miles; or 30 (thirty) miles longer han the "Combination Line"— and has the same serious drawbacks s lines "Nos. 1 and 2") in the shape of high summits, steep grades ad sharp curves. These lines Nos. 1, 2 and 6 pass over the same bjectionable ground west of Mattawamkeag, while owing to the low ummits and easy gradients on the "Combination Line," double the nnage could be hauled with the same power,—rendering this the ost valuable route for the purposes of an inter-provincial freight ilway.

TABULATED STATEMENT.

COMPARING MR. SCHERIBER'S BEST LINES NOS. "1," "2" AND "6" WITH THE "COMBINATION LINE."

add for Lachine détour..... 20 " =40 miles. Maximum grades 74 feet per mile, curves 10 ° degrees.

VII

COMBINATION LINE."

Montreal to St. Andrew's via Quebec, Chesuncook, and Canterbury	453 miles
Maximum grades 58 feet per mile, curves 4° degrees.	- 2
Montreal to St. John via Quebec, Chesuncook, and Can- terbury	481 miles
Maximum grades 53 feet per mile, curves 5° degrees.	
Montreal to Halifax via Quebec, Chesuncook, and Can-	- 1

terbury 710 miles.

Maximum grades, Quebec to Moneton, 35 feet per mile, curves 4 ° degrees.

Further,—Lines Nos. "1, 2 and 6," pass so near the American seaboard, that they will inevitably throw the bulk of the heavy freight traffic into American Ports.

This question of inter-provincial routes, is one of vital importance, not only to the City and Province of Quebec, but to the Dominion in general. Fuller examinations of the country should be made, in order to arrive at a wise solution of the matter. The fact is that the country has not been half surveyed,—for instance : of lines "Nos. 1 and 2," recommended by Mr. Schreiber as the shortest route both to St. Andrew's and St. John;— 58 miles are unsurveyed, while line "No. 6" to Halifax,—of which he speaks as "taking the first place," has also 113 miles not surveyed; thus aggregating on these three lines alone,—174 miles of unsurveyed country. Fuller examinations, would I am confident result vastly in favor of the "Combination Line;" that is, if Canadian interests are to be specially considered.

A. L. LIGHT.

Dori

tion

real

a brid

legre

John,

placii

Bruns

Chest

Chaubridg

with wicka S will t: heigh gevin. Juncti lu Su contin head c ed dur ake T n suc. route i Mariti passag avora

Dn

REVISED SUPPLEMENTARY REPORT

s. an-

453 miles.

nd

....

.... 481 miles s.

an-.... 710 miles. le, curves 4 °

the American he heavy freight

tal importance e Dominion in nade, in order to the country has s, 1 and 2," reto St. Andrew's No. 6 " to Halis also 113 miles one,—174 miles am. confident. t is, if Canadian

L. LIGHT.

On the proposed "Short Line Railway" to connect Montreal with the Maritime Provinces, with special reference to a Combination Line.

Ottawa, 10th May, 1885.

COLLINGWOOD SCHREIBER. Esq.,

Chief Engineer, Government Railways,

&c., &c., &c.

SIR,-In my report on Surveys, dated 23rd of March, I directed attention to a line designated "The Combination Line," to connect Monreal with the Maritime Provinces.

I feel convinced that this line, if established, in connection with a bridge over the St. Lawrence at Quebec, will satisfy, in a marked degree, the traffic requirements of Montreal, Quebec, St. Andrews, St. John, St. Stephen, Fredericton, Halifax and the ports further East, placing all localities on a fair and equal footing.

This Combination Line will run westerly from Canterbury, New Brunswick, to Lake Chesuncook, in the State of Maine, and from Lake Chesuncook, by the valleys of the Famine and Etchemin Rivers, to Chaudière Junction, opposite Quebec, and from thence through the bridge, and North Shore Railway to Montreal.

At Canterbury and Harvey the Combination Line will connect with the railway system of the Maritime Provinces (the New Brunswick and St. John and Maine Railways).

Starting from Chaudière Junction, the line proceeding easterly will traverse the valleys of the Etchemin and Famine Rivers to the neight of land, near the village of St. Justin, in the Township of Lanrevin. The summit is 950 feet above the starting point at Chaudière Junction; 509 feet lower than the summit on the line *via* the Rivière lu Sud, about 20 miles to the North. From St. Justin the line will continue its course South-East, and nearly direct to the vinicity of the nead of Lake Chesuncook, where it will connect with the line surveyed during the past season by Mr. Vernon Smith, C. E., between that Lake and Canterbury above named.

The country from Chaudière Junction to Lake Chesuncook lies n such a low valley or depression that it forms the natural direct oute for a line of railway between the Province of Quebec and the Maritime Provinces, and presents an unexceptionable channel for the passage of freight to the seaboard. Mr. Vernon Smith reports equally avorably on the line between Lake Chesuncook and Canterbury. This line has all immense advantage in its lower summit and easier gradients, equivalent fully to a virtual saving of 25 miles o straight and level road (see Appendix No. 4). Grades of 35 to 40 fee to the mile, and possibly less, can certainly* be obtained both way from Quebec to Moncton without any great additional expenditure for earth and rock excavations and masonry; these items of cost being alone affected by the reduction of grades.

d

hd

ac

el

m

thi

la

car

' T

ll n

ppo

ces

al,

om

A

o roi Otta

P. I

ryiı

ntia -thi

n fre

11 to

awa

ll to

Fre

ald 1

lage

tern

ntre

Ins

engi for

t a

en (

ngo

Sho

Lac Bs.w

The grounds for this opinion are as follows :----

The Etchemin summit, 950 feet above the Chaudière Junction, in overcome in about 50 miles, being an average ascent of only 19 fee per mile; the ascent to the Etchemin and Famine Valleys, along which the line would pass, is generally regular, there being but three breaks viz., one small waterfall at St. Anselme, and another at St. Claire, each about 8 feet in height, and a stretch of level, about one mile long, a Standon, all of which can be easily overcome by 35 feet grades.

East of the summit, on the descent to Lake Chesuncook, the principal impediments are the three upper branches of the St. John River which will be crossed within a distance of 20 miles. They lie about 100 feet below the summit level. The two which I have personally examined are in gentle depressions, with no formidable highlands in tervening.

The distance from the summit to Lake Chesuncook, is about 50 miles; half of this distance, at the southern end, would be on the streams flowing into the Allequash and into Lake Chesuncook, me serious difficulties will be met here.

The surveys of last season, by Mr. Smith, have established that the grades above mentioned, can be obtained from Chesuncook to Canterbury.

The eastern extension of the Combination Line from Canterbur to Harvey, would give St. John a good connection: while anothe extension from Canterbury, along the right bank of the St. John would continue this system of easy gradients to Fredericton, at which place the River St. John must be bridged, and the line continued via the head of Grand Lake, for the most part through a flat country, to Salisbury, there intersecting the Intercolonial Railway, 15-miles wes of Moncton.

This line would have a marked effect on the trade with the Mari time Provinces, and would go far to compensate for the increase distance to these ports, as compared with the railways in operation t Portland, Boston and New York. (See synopsis of distances from Callender to St. John and Halifax via Chesuncook, Appendix 6.) 1 would save about 150 miles of railway to Halifax and nearly double that distance to St. John, over the Intercolonial Railway.

The proposed line should be thoroughly constructed with rail and bridges, sufficiently strong to carry the Consolidation Engines (now so much in use in Pennsylvania) capable of hauling a gross load of 800 to 1,000 tons, over its grades, or nearly double that which could be hauled on the Intercolonial Railway with the same power, and a li the additional cost per train mile.

* In my first supplementary report, dated 26th March, I said : "grades of 35 to 40 fee to the mile, and possibly less, can I think be obtained." The subsequent publication of Mr Vernon Smith's and Mr. Wicksteeds reports has rendered this a certainty, therefore I here state it. ver summit and of 25 miles o s of 35 to 40 fee ained both ways l expenditure for ns of cost being

lière Junction, is ; of only 19 fee eys, along which out three breaks at St. Clairc, each one mile long, a set grades.

ancook, the prine St. John River They lie about have personally le highlands in

cook, is about 50 yould be on the Chesuncook, no

established that Chesuncook to

rom Canterbury : while another of the St. John ericton, at which e continued vi flat country, to , 15 miles west

e with the Mari r the increased in operation to distances from ppendix 6.) 1 l nearly double by.

cted with rails lation Engines ing a gross load at which could power, and a

des of 35 to 40 fee publication of Mr. ty, therefore I here The railways from the Province of Quebec to the Ports of Boston d Portland, although apparently shorter, have to ascend the higher nds of the Watershed, near the Boundary, and have therefore ach higher summits and steeper gradients.

The Ogdensburg and Portland Railway passes over a summit of White Mountains in New Hampshire, 1890 feet above the sea rel, with maximum grades of 116 feet to the mile, and minimum rives of 9° degrees (633 feet radius).

This difference in summit heights alone, between the New mpshire (American) and the Etchemin (Canadian) lines, to say thing of the easier grades and curves of the latter, would equate in e latter's favor equal to a virtual reduction of 34 miles in distance, carriage of heavy freight. (See Appendix No. 4).

In carrying Western freight via Ottawa to Quebec, much of it Il naturally pass over the North Shore Railway and by means of the posed Bridge at Quebec to the several Ports of the Mantime Proices; consequently it would follow that some point west of Monal, and not Montreal itself, should be the starting point from which omparison of distances should be made.

A clear saving of 30 miles distance to Hull, as compared with route following the C. P. Railway to Carleton Place, and thence Ottawa, would be effected by taking Chalk River Station on the P. Railway as the diverging point. Crossing the Ottawa and rying the line to Hull along the North shore of the river, via the ntiac and Pacific Junction Railway, of which 30 miles, or about third of its length are built, would so reduce the length as will be n from the following table of distances :—

awa wig () P Reilway to Carlaton Place and Chall	2 miles.
River Station	126 "
	128 "
tion	95 ""
Saving	33 miles.
	-

Freight from Montreal to Quebec via North Shore Railway, ald pass by St. Martin's Junction, as at present; but no railway nager would haul Western freight, destined for Quebec and tern ports, an additional 12¹/₂ miles past St. Martin's Junction, into ntreal and out again; in all an unnecessary 25 miles haulage.

Instead of hauling freight this extra distance, a loop line, 10 miles ength, by a level route, could be cheaply and easily constructed for \$100,000) between St. Thérèse and Terrebonne, which would et a saving of 30 miles of distance; this, added to the saving been Chalk River and Hull, already mentioned, would give a clear ing of 63 miles.

Should the alternative line, from Lachute to Quebec, be adopted, Lachute made the distributing point, a further saving of about 17 es would be made, [making 80 miles in all.] This saving of actual distance, added to a virtual saving of 3 miles, by reduction of summit heights as already stated, would operate in favor of Canadian, as compared with American Ports, by reducing the distances to the former.

For instance, the distance from Lachute to St. John, vid

Quebec and Ohesuncook, is...... 485 miles The distance from Lachute to Portland, via Mile End, La-

chine, Portland and Ogdensburg (the shortest route) is.. 353

ue

ut,

ect

roo

00

en

nd

rill

ie s Lain

icre

ista

ista

istar

V

N

· Sl 1e ".I

fax, a

vhich

urves

nd P

ddednd 44

listan

istan

(S

48

If the "cut off" from Chalk River Junction to Hull, via the Pon tiac and Pacific Junction already named, be used, this distance will b reduced to 65 miles.

The easier grades and curves on the Quebec line would materially reduce this latter distance, in as much as the strongest freight engine will haul forty loaded cars over the Canadian line, whereas the same engine could only haul 17 loaded cars over the Portland and Ogdens burg Railway, thus nullifying the shorter distance to Portland, a compared with that to St. John.

This admitted—the Canadian Sea-ports of . Andrews an L'Etang, some sixty miles West of St. John—for the omnice, and can able of being made good harbors—are actually about as near Montrea as Portland.

To instance one of the beneficial effects which a low system of gradients would have on the trade with the Maritime Provinces :-

the coal and minerals of the latter could, by this Combination Line, be carried for less than half a cent per ton per mile.

The line would pass directly through the extensive coal fields a the head of Grand Lake, New Brunswick, mentioned in the reports the Geological Survey, one seam alone of which is estimated to contain one hundred millions of tons of coal, so near the surface that i may be quarried and not mined.

This mineral, at present almost excluded from commerce in the isolated district, could be carried as return freight, ensuring loade trains both ways; and bituminous coal, reported to be excellent f forging and other purposes, could be delivered at Quebec, Montre and Ottawa, for \$3, \$3.86 and \$4.33 per ton. (See Appendix No. 5.)

I have prepared several tables of approximate distances from Calender to Lake Chesencook,—the common point of divergence of the projected lines from Montreal to St. John and Halifax via Quebec an Lake Megantic.

These tables are as nearly correct as the present state of the su veys will admit, and shew that if each line runs into and out of Mo treal by the proposed modes of ingress and egress, there will be saving in distance from Montreal *via* Quebec of at least 10 miles; th saving, to be effected by the adaption of what has been here terms the "Combination Line." l saving of 3 , would operate is, by reducing

vid	·	
La-	485	mile
) is	353	
. 7	132	
•••••	34	**
•••••	98	·` "

ull, via the Pon distance will b

vould materiall t freight engine nereas the same nd and Ogdens to Portland, a

Andrews an m ice, and caj as near Montre

low system of ne Provinces :nis Combination nile.

ve coal fields a in the reports timated to con surface that

mmerce in th nsuring loade be excellent faitbec, Montre pendix No. 5. ances from Cu vergence of th via Quebec an

tate of the su nd out of Mo there will be t 10 miles; th en here terme Another line has been advocated, which from the stand-point of nebec's interests, extends not the slightest advantage sought after, ut, is on the contrary diametrically inimical to such interests, all conection with it, from Quebec being perfectly impracticable.

This line, termed the "International," has been traced via Sherrooke and Lake Megantic, to be carried across the State of Maine through loosehead Lake, and from thence to Mattawamkeag, on the Maine entral Railway.

The disadvantages to Quebec of such a line may be briefly stated : 1st. No connection from the City of Quebec can be made with it, nd *if it could*, the extra length would destroy its usefulness.

2nd. Instead of being a short line to the Maritime Provinces, it rill have the effect of actually diverting Western trade from them, to be several United States harbours in the neighbourhood of Bangor, Iaine.

3rd. By it, the distance to Halifax and St. John, from Montreal, is acreased some 57 miles, and 10 miles, respectively, as compared with istances via the "Combination Line."

istance from Montreal to Halifax via Megantic, Matta-

Saving in favor of Quebec..... 57

44.

11

66

 $\mathbf{44}$

Saving via Quebec..... 10 Vide table 10—Appendix 6.

Nor would this Mattawamkcag connection materially benefit Hafax, as it is but 89 miles shorter to Montreal than by the Intercolonial, which saving would be greatly nullified by the sharp grades and urves and high summits of the "International" line.

Should the International connection be made via Greenville, on he "Bangor and Piscataquis" Railway, and that line utilized to Milo nd Passadumkeag, as has been suggested, some 34 miles must be ided—making the increased distance to St. John and Halifax 91 miles nd 44 miles respectively—instead of 57 and 10, as before stated.

istance "	from	Montreal "	to	Halifax "	via 1 via (Passadun Quebec	nkeag	. 801 . 710	miles "
					,	•.	` c	91	"
istance	from	Montreal	to	St. John	ı via	Passadu	mkeag	525	- 4
. 66	5	*6	1	"	via	Quebec.		481	56

(See Appendix 6, table 11.)

The distances to build from Montreal to Harvey, the intersecting point of the Maritime system via Quebec, and from Montreal via Mattawamkeag are nearly equals as follows, viz:

Saving via Megantic..... 8

8t. .

ler Dari

The

he

om

llo

axi

Im

aula

ost o

vi

vi

ost of

vi

vi

Th lest lu lebec on w the S ut lu Que

nada

50

In conclusion, the proposed "Combination Line" for the projected Short Line Railway between Montreal and the ports of St. John and Halifax is based on true commercial principles. It passes over the lowest summits, and with far easier gradients and curvature than can be obtained by any other line crossing from the valley of the St. Lawrence to the Atlantic seaboard, permitting of the hauling of forty loaded cars, against twenty the other way; in fact, a line which must bring the freight of the West to the ports of the Maritime Provinces, and the coal of those Provinces to Ontario and Quebec, thus ensuring the prosecution of economical inter-provincial freight relations.

The link between Lake Chesuncook and Lake Megantic, while not making the line via Sherbrooke an interprovincial trunk line, would nevertheless give the Maritime Provinces direct communication with the Eastern Townships, and a new market for their coal, and would create a short route to the City of New York, and the building of this link (Lake Chesuncook to Lake Megantic) in connection with that which I propose from Lake Chesuncook to Quebee, would complete a system which would meet every requirement of both freight and passenger business, including that of the passenger business for Europe, which I have no doubt will be got from the United States, via the Passumpsic Railway and Sherbrooke—if Louisbourg becomes, as expected, a port of call for Ocean steamers.

SUMMARY.

Comparison between projected Short-Line from Montreal to the Ports of St. John and Halifax via Quebec and Lake Megantic.

East of Canterbury the lines diverge to St. John and Fredericton. West of Canterbury to Lake Chesuncook, the Trunk line will be in common.

West of Lake Chesuncook, the Quebec line passes by the valley of the Famine and Etchemin Rivers, to Chaudière Junction and Quebec, and via North Shore Railway to Montreal.

The International Link passes by Lake Megantic, Sherbrooke and Lachine to Montreal.

Distances from Montreal to Lake Chesuncook (common point)-

Saving by Quebec.

min Lake Megantic (vide Annendix 6 table 5)	088	miles
the land meganito (rade uppendix o, table of	000	ALLA LC
via Quebec (vide Appendix 6, table 6)	278	46 F
via Lachute (common point for Western business) to		1
Chesuncook by Megantic	325	46 -
Onchast	075	× 4 6
Quebec	210	27/x L

e intersecting treal via Mat-

	248 240	miles.
-		"
	0	

f St. John and asses over the ature-than can of the St. Lawg of forty loade which must ime Provinces, thus ensuring elations.

legantic, while cial trunk line, communication their coal, and nd the building onnection with would complete oth freight and usiness for Euited States, via arg becomes, a

Montreal to the egantic. nd Fredericton ank line will b

by the valley Junction an

Sherbrooke an

a point)— 288 mile 278 to 325 275 50

	(the intersecting point of the Maritime system) is the same by either line, viz. :
	The distance to build from Montreal to Harvey via Quebec and om Montreal to Mattawamkeag via Megantic are nearly equal, as pllows:
	Montreal to Harvey via Quebec248 milesMontreal to Mattawamkeag via Megantic240 "
	Saving by Megantic 8 "
	aximum gradients via Megantic line (vide Chief Engineer's Railway Report, 1882)
	nmmit above sea level via Portland and Ogensburg R'y 1890 " via Megantic, height unknown to me, said to be 2000 " via Quebec and Etchemin River
	ost of completing projected line between Montreal and Chesuncook (see Appendix 7.)
	via Lake Mcgantic, including Lachine Bridge \$10,240,000 via Quebec, including Quebec Bridge
	Saving via Quebec \$ 1,770,000
	ost of completing projected line between Montreal and Mattawam- keag, (see Appendix 8.)
-	via Lake Megantic, including Bridge
ľ	Saving via Quebec \$ 700,000
1. CB	The line from Quebec to Chesuncook would pass through the test lumber lands of Maine, the lumber would be shipped from nebec, and the freight be worth millions of dollars to Canada. This on would be lost, by lines passing through the more Southern part the State. (See Mr. Edward Jack's letter, one of the most intelli- nt lumber explorers of New Brunswick, (Appendix 3.) The line a Quebec and Chesuncook will make Northern Maine tributary to mada.
	the second se

The distances East of Chesuncook, between the latter place and t. John and Halifax, are not affected, therefore need not be considered here,-they are given however in tables 7, 8, 9, 10, 11 and 12, in comparison with the Intercolonial (vide Appendix 6.)

The mileage to be built West of Lake Chesuncook to Montrealvia Megantic is..... 215 miles. 111 via Quebc is he mileage to build East of Lake Chesuncook to Harvey

Montreal t	o Harvey via Quebec	248	miles.
Montreal t	o Mattawamkeag via Megantic	240	46
1	Saving by Megantic	8	66 , ·
mmm and	ionto nia Magantia lina (mida Chief Fugina	an'a D	

ximum	gradients	via	Megantic line (vide Chief Engin	neer's	Rai	lway
	· ·		Report, 1882)		74	feet.
		via	Quebec		40	

The Southern line *via* Megantic and Passadumkeag passes through a sterile part of Maine and is intersected by several United States Railways, which will inevitably cause the trade of Canada to flow to United States scaports.

The line via Quebec and Chesuncook traverses about 77 miles less of American territory than the Southern line via Megantic and Mattawamkeag, and 114 miles less than that via Passadumkeag. (Vide Appendix 6, table 12.)

There are two lines now to Sherbrooke from Montreal,—one by the Grand Trunk, the other via St. John's, Farnham, Waterloo and Magog. Why build a third line, when the counties South-east of Quebec are destitute of railways?

The bridge at Quebec does away with the necessity of the Lachine Bridge:

The bridge at Lachine does not save the building of the bridge at Quebec, which must be constructed eventually to connect the Pacific with the Intercolonial, and thereby complete our national railway.

The Lachine Bridge is incomplete until a new line, some 120 miles long, is built to Smith's Falls or Carleton Place, which line is an essential part of a contemplated through route (via Lachine Bridge) to Portland, thus duplicating the line between Ottawa and Montreal, while an extension to Quebec is unprovided.

What does Canada want with a second line to Portland, while her own seaports are not connected by the shortest commercial line with Montreal ?

The freight which is taken accross the St. Lawrence above Montreal will naturally flow to New York, Boston and Portland, while, if directed via the North Shore Railway through Quebec, it must find its way to the Canadian Maritime Ports.

I remain, Sir,

Your obedient Servant,

(Signed),

A. L. LIGHT, {M. Inst. O. E., Great Britain. Mem. American Asso. C. E. Chief Engineer Government Railways,

Province of Quebec.

COMPARISON between the several routes for the projected Short Line Railway between Nontreal and the

ed States Railda to flow to

it 77 miles less tic and Matta-(Vide Appen-

treal,-one by Waterloo and South-east of

of the Lachine

of the bridge of the Bridge meet the Pacific nal railway. line, some 120 which line is an hine Bridge) to and Montreal,

land, while her ercial line with

nce above Mon-rtland, while, if ec, it must find

JOMPARISON between the several routes for the projected Short Line Railway between Montreal and the Ports of St. John and Halifar, that is, by the two lines, by Sherbrooke and Megantic and the Combination Line via

Quebec.

O. E., Great Britain. Imerican Asso. C. E. ent Railways, of Quebec.

+ The distances via Passadumkeag and Mattawamkeag are based on the assumption that the extension Rativard from there to Moncton Difference in favor of 000'004 Quebec. 46969988448 Quebec and Combination onded car 8,470,000 10,500,000 200 481 710 710 710 710 710 761 761 761 761 761 Line Via 20 loaded cars. Sherbrooke. 11,200,000 10,240,000 John Locality. St. John St. John St. John St. John St. John Halifar.. Halifax ... Halifax. Halifax. Cost, including Bridges over St. Lawrence in both cases, via Combination lines to including Bridges in both cases, to Mattawamkeag versus Combination line to Chesuncook, (see Appendix 7)..... Mattawankeag, to.... Mattawamkeag, to..... Haulage Power, Consolidation Engines. ria Megantic and Passadumkeag, to From Montreal, via Megantic and Passadumkeag, to..... DESCRIPTION OF LINE. via Combination line. (see Appendix 8)..... qo op Greatest Altitude above sea level, say Curves Minimum..... Grade Maximum per mile ... do qo do 90 Harvey, , do op qo qo qo q de p Cost,

5

will be carried to St. John and over the existing lines of railway.

• These estimates are based on the assumption that the Syndicate carry out their intention of bridging the St. Lawrence at Lachine, and building a line from Lachine to Sherbrooke. In the last estimate we the Combination Line to Harvey, the Quebec Bridge and connecting lines are estimated for single track, in order to institute a fair comparison with the Lachine Bridge.

These tables of distances have been prepared with great care :-1st. From a personal examination of some 500 inles of the lines during the past season. 2nd. From time-tables where existing lines are used. 3rd. From the best maps extant (where surveys have not been made.) 4th. From an accurate personal knowledge of the general features of the three Provinces; having being Chief Engineer of Government Railways for a long period in the Provinces of Nova Scotia, New Brunswick and Quebec, and are therefore as nearly correct as can be made without final location surveys.

The height of the summit, above sea level, on the International Railway via Lake Megantic is unknown to me. It is of paramount importance that it should be examined before a decision is arrived at. It has been variously reported, by competent Engineers, at 2,400 and 2,000 feet respectively above sea level. This difference in altitude is equivalent to an additional mile of level line for every 20 feet of extra height, thus virtually lengthening the International line, if the lower height is taken 40 additional miles for purposes of heavy traffic. (See Appendix 4.) D

T

T

A

A

rinc eng

ata lans ost o t ffer c nnu

nnu n I Ç N

B.-

h great care :-the lines during g lines are used. not been made.) heral features of of Government va Scotia, New orrect as can be

ne International s of paramount on is arrived at ers, at 2,400 and ce in altitude is 20 feet of extra ine, if the lower yy traffic. (See

DVANTAGES TO RESULT FROM PROJECTED QUEBEC RAILWAY BRIDGE.

Imperial and National.

To connect and complete the Canadian Transcontinental Railway. "the railway system of Canada on both sides of the St. Lawrence, and at the most eastern point where it

is possible to span the river.

The only effective mode of making this connection to ensure safety and regularity.

A connection for the Intercolonial at Quebec with the North Shore Railway, establishing competition.

Access for the Grand Trunk to the new Quebec Docks, thus removing the motive which impels the Grand Trunk Railway to refuse to sell the North Shore.

rincipal of Bridge—The Cantilever.

ength of Central Span-1442 feet.

" of the Firth of Forth now in course of construction-1700 feet.

ata carefully worked out by me, and by Mr. Brunlees, the Eminent English Engineer.

lans ready.

ost of Bridge proper \$5,000,000 for double track, if single track with trestle approaches \$3,000,000.

ffer for construction of Bridge—4 p.c. guarantee for 25 years, materials duty free.

nnnal	outlay	on	Bridge -	-Capital	\$5.	.000.	.000.
undar	ULLIGY .		DINGU				

Working expenses 1 p.c.,	\$ 50,000
Sinking fund 1 p.c	50,000
Interest @ 4 p.c	200,000

\$300,000

nnual revenue on opening of Bridge based on actual movement of trains :---

Intercolonial Rai	lway	7.	
Quebec Central	"		
Grand Trunk	"		
North Shore	44	82,622 cars at @ \$4	330,52

Surplus after meeting all annual charges......\$ 30,528

B.-See Mr. Sbanly's letter annexed.

APPENDIX 2.

Montreal, 23rd March, 1885.

MY DEAR SIR,-Referring to our conversation of a few days age as to the traffic likely to be served by the proposed Cantilever Bridg over the St. Lawsence above Quebec, it would seem not extravagan to count on eight trains each way, with an average of 20 cars to train, for every working day in the year. Of the Eastern-bound car all, of the West-bound perhaps one-fourth, would be fully loaded and therefore toll-paying.

An average charge of Four Dollars per loaded car, taking pas senger and freight service together, would be not more than a reason able toll.

West.

RESULT :- 160 Cars bound East, 40

[Copy]

200 Cars at \$4.00\$800 per day. Annual Revenue (313 days).....\$250,400.

The several lines converging on the river at and opposite to Que bec will, as regards Through Traffic, have been built in vain if the fail to furnish the amount of business indicated by these figures.

The photographed drawing of the bridge conveys an impressiv idea of the grandeur of the structure.

There would, and could, be nothing to compare with it on thi continent, for there is only one river St. Lawrence.

As to reducing the Masonry in Piers and Approaches it would be a pity for the sake of any small economy to take away from the design anything that, wanting, would in the least detract from th majesty of its appearance.

Yours very truly,

· DIEC

Doj

iv

m

m

alls

rov

bw

ng

ten

ove

no

d d he nt i

ra

the

mb d o

e w

ese

dw

cini and

alit illio

sh:

ite.

est: S

St e Da

nefi n of

L.

A

I

(Signed,) W. SHANLY.

A. L. LIGHT, Esq., C. E.

N.B.-If the coal mines are developed as anticipated the cars wi run full both ways.

> (Signed,) A. L. L.

APPENDIX 3.

Ottawa, 11th March, 1885.

arch, 1885.

a few days age antilever Bridge not extravagan f 20 cars to stern-bound car fully loaded an Dopy

ar, .taking pas

\$800 per day. \$250,400.

opposite to Que in vain if the ese figures.

vs an impressiv

with it on thi

oaches it would away from the letract from the

· Die

SHANLY.

SIR.—In reply to your enquiries as to the timber on the St. John iver, I beg to say, that more than three quarters of the timber maining on the St. John and its tributaries is on its upper waters, mely on that portion of the St. John which is above the Grand alls, including, of course, the branches of that river which lie in the rovince of Quebee and in the State of Maine. Much of this is not wavailable on account of the cost of portaging as well as the ngth of river driving required to bring it to the sea board and other tendant difficulties, which the construction of a railroad would reove. Such a road would be the means of bringing to the St. Lawnce for shipment to Great Britain vast quantities of spruce deals d other lumber. There is also a great deal of cedar in this country. he traffic in cedar shingles and sleepers is becoming a very impornt industry; both of these are now being carried from Edmunston rail to Bangor and Boston.

The proposed railroad will be the means of employing thousands the habitants residing on the shores of the St. Lawrence, while the mber camps in Quebec and Maine will consume the farmers hay d oats, as well as give employment to their sons and horses during e winter.

I do not hesitate to say that the construction of this road through ese timber lands will be a great public boon to the French farmers d woodsmen residing on the South side of the St. Lawrence in the inity of and below the city of Quebec. There is here a great deand for more employment, where a portion of the country is of poor ality for farming. It would certainly also be the means of bringing illions of dollars worth of lumber to the banks of the St. Lawrence . shipment.

As to the quantity of timber in this country I can make no estinte. I know that it is very large and to get data on which to base estimate would demand the expenditure of time and money.

Should this railroad be taken to the Southward of the head of St. John, most of the benefits accruing from its construction down a Daagwaam and crossing the Alleguash will disappear, and the nefits instead of being conferred upon the French laboring populan of Quebec, will be conferred on the people of the State of Maine.

Yours respectfully,

(Signed,)

EDWARD JACK, Crown Land Surveyor.

3 - - -

A. L. L.

ted the ears wi

L. LIGHT, Esq., C. E.

18

APPENDIX No. 4.

14

EFFECTS OF HIGH SUMMITS, GRADES AND CURVES.

he of Bro

nea at : and

mil

was

fair

S

d e:

e co

and

· Se s is

nce celle t co Tl

en b

Th

hap

L. I

Cos re at. riage ollov

nk L ing :

In deciding which of the lines is the most eligible for practical business purposes, the comparison of the heights of their respective summits, is a matter of paramount importance. It may be remarked mical speed of 12 miles an hour) it is held as a maxim, that in the system with the speed of 12 miles an hour) it is held as a maxim, that in the system is the second sec that in the case of heavy freight trains (running at their most econoconsumption of fuel, an additional 20 feet of elevation passed over, is equivalent to an additional mile of straight and level line.

The summit by the Etchemin is 509 feet lower than that by the Rivière-du Sud, the saving of fuel in the carriage of freight by the former line, rather than by the latter, due to the difference of altitude alone, would be sufficient to carry the whole freight traffic over 2 miles of level track.

REMARKS ON CURVES.

The question of curvature is also one of the highest importance According to L. H. Vose, Professor of Civil Engineering in Bowdoin College, and other eminent scientific and practical authorities, the resistance due to curvature, to freight trains upon a 10 ° curve, is equa to a grade of 24 feet per mile, or 2.4 feet for each degree of curvature A I0 \circ curve, combined with a 53ft grade per mile, therefore is as great an obstacle to heavy freight traffic, as a 77 feet per mile grade on a straight line.

APPENDIX No. 5.

GEOLOGICAL SURVEY OF CANADA, 1878-1879. 20 II.

" Assuming the average thickness of the surface seam around the head of Grand Lake at 20 inches, and allowing the available yield of coal for a seam one foot thick to be 1,000 tons per acre, (Richard Brown, F.G.S., estimates that each acre of coal, one foot in thickness (in Cape Breton) contains 1,500 tons, taking the specific gravity at 1,250, we have, from the coal basin of Newcastle and Coal Creek, and Salmon River, which may be stated to contain about 100 square miles, a total available yield of coal, due allowance being made for waste, of over 100,000,000 tons for this limited area alone—it may fairly be presumed that with economical management and a proper er most econo-system of working, a large portion of this enormous quantity might im, that in the "be profitably extracted."

Ottawa, March 10th, 1885.

SIR,-I have been at the Coal Mines at Newcastle, Grand Lake, d examined the same, they are worked in a very primitive manner, e coal being hauled in carts a distance of from 3 to 5 miles, to the and Lake.

So far as I could ascertain, about 6,000 tons are raised per year, s is used for house and blacksmith purposes; it carries, in some innces, a good deal of sulphur and leaves considerable ash, it is an cellent cokeing coal, and so-fer as I can learn, is one of the very t coals in use for heavy forgings.

The beds are close to the surface, in some instances being on it, en but 12 feet below.

The coal is delivered from the beds on the surface for \$1 per ton, haps rather under that sum.

(Signed,)

EDWARD JACK.

Crown Land Surveyor for New Brunswick.

L. LIGHT, C. E.,

Chief Engineer Government Railway, Province of Quebec.

Cost of delivering bituminous coal from the mines near Grand te at Quebec, Montreal and Ottawa at 4 cent per ton per mile for riage and \$1.50 per ton for mining and loading on cars would be follows :--

AT QUEBEC.

nk Lake to Quebec, 300 miles transportation @ 1 c. p. mile...\$1.50 ing and loading on cars..... 1.50

Cost of delivery......\$3.00

RVES.

le for practical heir respective y be remarked eir most econopassed over, is line.

ian that by the freight by the cnce of altitude t traffic over 23

est importance ng in Bowdoin authorities, th P curve, is equa ee of curvature , therefore is as er mile grade on

AT MONTREAL.

Grand Lake to Quebec, 300 miles. Quebec to Montreal, 173 "

Transportation 473 miles @ ½ c. per mile
mining and toading on cars
Cost of delivery\$
AT OTTAWA.
Grand Lake to Quebec, 300 miles. Quebec to St. Martin's Junction, 160 " St. Martin's Junction to Ottawa, 107 "
Transportation
Cost of delivery\$

2

3.

Ca Cl Hi Ma St. Ch

4.---

16

APPENDIX No. 6.

STANCES FROM CALLENDER TO CHESUNCOOK BY 4 DIFFERENT ROUTES.

b. 1—Traversing the Canadian Pacific via Carleton Place and Ottawa to Montreal; thence back to Mile End and Lachine to Chesuncook. Total distance 633 miles as per details :—

Callender to Montreal	345	miles
Montreal back to Lachine	11	- 64
Lachine to Sherbrooke	104	46
Sherbrooke to Lake Megantic	69	**
Lake Megantic to Chesuncook	104	66 ·

Total distance 633 miles

2.—From Callendar via Carleton Place and Ottawa to Montreal, then back to St. Martin's Junction to Chaudiere Junction and by Etchemin Valley to Lake Chesuncook. Total distance 623 miles.

Callender to Montreal	345	miles
Montreal back to St. Martin's Junction	12	66
St. Martin's Junction to Chaudiere Junction	161	66
Chaudiere Junction to Chesuncook	105	. 16

Total distance...... 623 miles.

3.—Callender to Lake Chesuncook via Chalk River Station and Pontiac and Pacific Junction Railway to Hull and Montreal; then back by St. Martin's and Chaudiere Junction, and by the Etchemin Valley Combination Line to Chesuncook. Total distance 587 miles, as per details:—

Callender to Chalk River Station	99 miles.	
Chalk River Station to Hull by Pon. & Pac. Junc. R'y	92	** '
Hull to Montreat by Canadian Pacific Railway	118	"
Montreal back to St. Martin's Junction	12	**
St. Martin's Junction to Chaudiere Junction	161	66
Chaudière Junction to Chesuncook	105	"

Total distance...... 587 miles.

4.-By North of the Ottawa :--

\$2.3 1.5 \$3.8

mile

Callender to Lake Chesuncook, via Chalk River Station and Pontiac and Pacific Junction Railway to Hull, thence by St. Thérèse and North Shore Railway, and Quebec bridge to Chaudière Junction, and Etchemin Valley to Chesuncook :--

Total distance	556	miles.
Callender to Chalk River, by Canadian Pacific R'y.	99	46
Chalk River to Hull, by Pon. and Pac. R'y	92	"
Hull to St. Thérèse, by Can. Pae. R'y	. 99	41
St: Thérèse to Chaudière Junction, via N. S. R'y	161	66
Chaudière Junction to Chesuncook	105	66
	-	

Total distance...... 556

No. 5	-Distance from Montreal to Chesuncook, via Lachine and Lake
	Total distance 288 miles
	Montroal to Laching
1	Lohing to Shawhagha
1 a a 1	Charling to Sherbrooke
	Sherbrooke to Lake Megantic
β1 [*] .	Lake Megantic to Chesuncook 104 "
1.1	Total distance 288 "
No. 6	-Distance from Montreal to Chesuncook, via St. Martin's Junc- tion and Quebec :
	Total distance 278 miles.
	Montreal to St. Martin's Junction 12 "
	St. Martin's Junction to Chaudière Junction
	Chaudière Junction to Chesuncook 105 "
	Total distance
No. 7	-Distance from Montreal to Halifax, by Grand Trunk to Levis and Levis to Halifax, by Intercolonial Railway :
	Total distance
•	Montreal to Levis 172 "
	Levis to Halifax
•	Total distance
	Distance to St. John, New Bruntwick 760 "
No. 8	-Montreal to Halifax, via Lachine, Megantic and Chesuncook :
	Total distance 720 miles.
	Montreal to Lachine, via Can. Pac. R'y. 11 "
	Lachine to Sherbrooke 104 "
	Sherbrooke to Megantic
	Megantic to Chesuncook 104 "
•	Chesuncook to Canterbury 111 "
	399 miles.
	Canterbury to Moncton
	Moneton to Halifax
	391 "
	· · · · · · · · · · · · · · · · · · ·
	Total distance
	Montreal to St. John :
	Montreal to Canterbury, as above
	Canterbury to Harvey
	Harvey to St. John
	and the second se
	A

No

No.

18

18 1 6	19
	No. 0. Montreal to Holifor and St Martin's Innotion Onches and
2 2 2	Chesuncook :
	Montreal to St. Martin's Trunction 19 miles
121. 101	St Martin's Junction to Chesnneook 266 "
	Chesuncook to Canterbury
 Image: A second s	389 miles.
	Canterbury to Moncton
	Moneton to Halifax 187 "
	Montreal to Halifax, total distance 710 "
	Montreal to St. John :
8	Montreal to Canterbury, as above No. 9
4	Uniterbury to Harvey 20
	narvey to St. John
	Total distance 481 "
5	
20	No. 10Montreal to Halifax via Lachine, Mattawamkeag and Vance-
S. 12	boro :
- 11 K	
	Montreal to Lachine 11 miles
	Lachine to Sherbrooke
	Maga Diver to Motto membrane 126 "
	Mouse rever to Mattawankeag
	Vanceboro to St John 91 "
	491 miles
	St. John to Moneton
	Moncton to Halifax 186 "
	276 miles
1 A A	the second s
1 1	Total to Halifax
1	To St John as above 491 "
	N. 11 M. J. L. L. Fr. 10. INT. L. T. L. M. J. C. 11.
es.	No. 11.—Montreal to Halliax, via Lachine, Lake Megantic, Greenville,
K	Milo, rassadumkeag and vanceboro :
100	Montreal to Sherbrooke 115 miles.
	Sherbrooke to Moose River
	Moose River to Greenville
	Greenville to Milo 55 "
	Milo to Passadumkeag 27 "
6	Passadumkeag to Vanceboro' 83 "
6	vanceboro' to St. John 91 "
	St Tahn to Manatan 525 miles.
	Monoton to Holifar
	Dedicion to Halliax
No. No.	801 **
A	

	No.	12	-Miles in Ma	aine, U.S.	л 		· •	
. <i>¥</i> .	a	Via	Lachine, La	ke Megant	ic, Green	ville and Passa	dumkeag	:
			Moose Rive	r to Green	ville	61 mil	les.	
Perc. 4			Greenville	to Milo	23			
* .		•	Milo to Pas	sadumkea	*	27		
		'	Passadumka	age to Van	abora'	Q0 4		
			1 absauumrt	ag to van			· 000 -	milon
	r	77.	T. 1 T.				220 1	nnes.
	0.	v ia	Lachine, La	ke Megant	ic and Ma	attawamkeag :-		
			Moose Rive	r to Matta	wamkeag	136 mi	les.	
			Mattawamk	eag to Va	nceboro'		"	
r .				0.00			192	"
	C.	" Co	mbination L	ine." via	Lake Che	suncook	116	"
		-						
		' Syn	opsis of dista	inces and :	miles to b	ouild :		
1 74	A848 -		*					Miles
							1.1	to
	1-1	Iontre	al to Halifax via	N Shore R'v	Quebec and	Intersolonial R'w	Distances.	Bulla
			St. John	do	do	do do	760	
z. 11	2-N	lontre	al to Halifax via	N. Shore R'y	, Quebee, R	iv. Ouelle, Edmunst	on	
	12		* '		Gr	and Falls and Monet	on 756	284
		2	St John	do	do Riv.	du Loup, do do	771	264
	3-N	lontre	al to Halifax via	N. Shore R'v	. Quebec. Ch	esuncook. Canterbu		90
					, , , , , , , , , , , , , , , , , , , ,	and St. Jol	hn 754	248
			St. John	do	· do	do do	481	248
	4N	lontre	al to Halifax via	N. Shore R'y	, Quebec, Cl	hesuncook, Caterbu	y, 710	970
					r te	edericton and Monct	on /10	300
		Lanknu	St. John	do	do and	d Canterbury	481	248
	014	tontre	ai to mannax via	Sherbrooke,	D. Megantie	, mattawamkeag a St Jol	na 769	240
-4			St. John	do	do	do	493	240
							~	

APPENDIX No. 7.

Approximate estimate of the cost of the number of miles of new railway required to connect Montreal with Lake Chesuncook, the most cligible common point of divergence via Quebec and via Lake Megantic respectively :--

MONTREAL CONNECTIONS.

Mile End Station to Lachine including heavy land and	,
other damages, say	\$1,000,000
* Lachine Bridge complete with permanent approaches	3,000,000
Lachine to Sherbrooke (new line) 104 miles @ \$30,000	
per mile	3,120,000
Lake Megantic to Chesuncook 104 miles @ \$30,000 p. mile	3,120,000

\$10,240,000

f is fo

n d o:

M Q

M

La La Mo

8 n

Qu Ch

Che

* This Bridge has been variously estimated at from one and a half to four millions. It is designed for single track with about half a mile of trestle work on the Southern end. The Victoria Bridge cost seven millions. If designed for double track on the same substantial manner as the Quebec Bridge; it will certainly cost three millions of dollars.

20

QUEBEC CONNECTIONS.

‡ Quebec Double Track Bridge complete with the most solid and permanent work and	
approaches	\$5,000,000
8 miles new (double track) railway connecting	- , ,
the Bridge with North and South Shore	
system @ \$40,000 per mile	320,000
Chaudiere Junction to Chesuncook via Etche-	
min and Famine Valleys 105 miles @	
\$30,000 per mile	3,150,000

\$8,470,000

Saving by Quebec system...... \$1,770,000

[‡] The net cost of this Bridge according to my estimate and carefully revised by Mr. James Brunless, the eminent English Engineer, is £887,000 stg., or \$4,319,000; the balance of the \$5,000,000 being for contingencies, administration, engineering and other expenses.

It is designed for a double track with solid approaches of arched masonry. The cost can be reduced to \$3,000,000 by changing the design to single track, with approaches of steel trestle work, instead of arched masonry.

APPENDIX 8.

Approximate estimate of the cost of the two lines, one via Lachine, Megantic and Moosehead Lake to Mattawamkeag. The other via Quebec and Chesuncook to Harvey.

LACHINE TO MATTAWAMKEAG.

Mile End to Lachine, 7 miles includindg heavy land and	
other damages	\$ 1,000,000
Lachine Bridge	3,000,000
Lachine to Sherbrooke, 104 miles @ \$30,000 per mile	3,120,000
Moose River to Mattawamkeag, 136 miles @ \$30,000 per	*
mile	4,080,000
s	
•	\$11,200,000
	And the state of t

QUEBEC CONNECTION.

8 miles single track to connect North and South Shore	
lines @ \$30,000 per mile	\$ 240,000
Quebec Bridge, single track	3,000,000
Chaudière Junction to Chesuncook, 105 miles @ \$30,000	
per mile	3,150,000
Chesuncook to Harvey, 137 miles @ \$30,000 per mile	4,110,000

\$10,500,000

of new le most Megan-

miles.

Miles

to Build

284 264

98

248

248

356

248 240

240

00,000 00,000

.**20,00**0 .**20,00**0

240,000

and a ut half Bridge 10 subthree

Report on the Line Instrumentally Surveyed.

COLLING WOOD SCHREIBER, Esq.,

Chief Engineer Government Railways,

&c., &c., &c.

lo o

0

n

tł

in

81

th W

er.

no

ea

25

Ri

wi

the

the

lev

boi

lev

to t

and

laic

Chi

sur

Sain

the

cold

18 S)

actu

SIR,—Acting on your instructions of the 16th July last, I have made a careful instrumental survey of the line running up the south branch of the Rivière-du-Sud, designated as line No. 2 in the report on the barometical reconnaissance of July last.

The initial point of the survey is on the line of the Intercolonial Railway, 4 12 miles west of Saint Charles Station, and 12 miles east of Chaudière Junction.

An alternative starting point presents itself, which, with a view to accommodate traffic between Quebcc and Levis, might leave the Intercolonial Railway immediately east of St. Charles Station, instead of 4 miles west of it. Trains could thus run on either the main line to Chaudière or the branch to Levis. The eastern connection lengthens the line about one mile, but saves 3 miles of construction.

From the first named point, the line runs nearly east 14.22 miles, to a point near the Village of St. Raphael, there attaining an elevation of 257 feet above the initial point. Near the 15th mile, the line crosses the Rivière-du-Sud, a shallow stream full of boulders, which would require a bridge, with two spans of 100 feet each, at an elevation of 75 feet above the waterlevel. The work would be light on this length, the gradients easy and the curves of large radius. The earth is generally a sandy loam interspersed with boulders, little if any solid rock being apparent.

From the above crossing, the line of survey follows the course of the Rivière-du-Sud to the 27th mile, at which point it turns abruptly to the south, up the Valley of the Rivière-aux-Pins, following that river to its source, where the height of land on the south side of the St. Lawrence, is passed on the 39th mile, at an elevation of 1459 feet above the initial point. This line, between the 14th and 39th mile. did not prove so satisfactory as was hoped. Following the valleys of the rivers named, and being confined within comparatively narrow limits, by their abrupt banks, the alignment is tortuous and the grades irregular, in some places rising rapidly with the streams, while in others the ground is comparatively level. On ascertaining this fact, a number of cross sections, were taken at intervals, extending beyond the south side of the river, a gently rising side hill here gradually ascends to a height of several hundred feet, extending longtitudinally, and for the greater part, parallel to the line from the summit, somewhat further than the 14th mile.

Another line (marked in blue on the small scale map) was traced by means of the cross sections taken on the side hill, this gave good results; moderate work, minimum curves of 4° (1,432 feet rad.) and no grade exceeding 52.8 feet per mile. The grades can be reduced to 45 feet per mile, by turning south, up the south-west branch of the Rivière-aux-Pins for about half a mile, crossing the stream and returning down the western bank, by these means gaining the additional distance required for the easier grade. This change would necessitate additional height to the viaduct over the north-west branch of the Rivière-du-Sud, leaving the remaining work practically unchanged, as the sloping ground would admit of any grade down to 40 feet per mile.

The maximum 52.8 grade, shewn on the profile, is 14.37 miles long. From the north-west branch of the Rivière-du-Sud to the foot of the incline, the grade is 39 feet to the mile, with minimum curves of 4° (1,432 feet radius), the aggregate length of these grades is 25 miles, and the work will be comparatively easy on the whole distance; three bridges, each about 1,000 feet in length and 70 feet in depth in centre, being the only important structures required.

ave

outh

port

nial

st of

view

a In-

ad of

ie to

hens

ailes,

ation

osses

ould

on of

ngth,

gen-

rock

se of

ptly

that

the

feet

mile,

ys of

ades

le in

fact,

ond

v as-

ally,

me-

aced

rood

and

The adoption of the line, via St. Charles Station, would necessitate another trestle bridge, (1,500 feet in length, and 100 feet in depth in the centre), over the River Boyer, near the station; the rest of the work would be of a simple character.

After passing the summit, the line gradually descends south-easterly to the head waters of the River St. John, with varying gradients, none exceeding 52.8 feet per mile, and minimum curves of 4° . The earth-works here will be the heaviest on the division. averaging about 25,000 cubic yards per mile.

The International Boundary is passed on the 58th mile, near the River Daagwaam, a tributary of the Saint John, it is a shallow stream with boulder bed, requiring two spans of 60 feet each, 25 feet above the water level.

From the crossing of the Daagwaam to the South West-branch of the River St. John, the line is straight and the ground practically level. The latter stream is also quite shallow with low banks and a boulder bed. Two spans of 100 feet each, 35 feet above the water level, are required here.

From the St. John the line was run as nearly direct as possible to the discharge at the North end of Yule Lake, between the 78th and 79th mile. This stream will require a bridge of 50 feet span laid 20 feet above the water.

From the discharge, the line was carried to the dam at the foot of Churchill Lake, on the Alleguash River, the terminating point of the survey.

The Alleguash is shallow, with a boulder bed, similar to the Saint John. It will require two spans of 100 feet each, 30 feet above the water.

The entire distance surveyed from the initial point on the Intercolonial Railway to the River Alleguash is 96-54 miles; this distance is shortened about 4-54 miles by changes in the line, reducing the actual length to 92 miles, or five per cent. longer than an air line between the points. By inserting a tunnel 3,000 feet in length at Robber street, a mile more can be saved, reducing the distance to 91 miles. This has not been taken into consideration.

The distance from the initial point West, along the Intercolonial Railway, to Chaudiere Junction is 12 miles, making about 104 miles from Chaudiere Junction to the Alleguash River. Of this distance 57-59 miles are in the Province of Quebec and 46-41 miles in the State of Maine; 92 miles will have to be constructed.

it p ta

g m St

of

Ju

Ri

So

Cl

du

no di:

W

ap Et

con to thi

ma

ma

ave

cej

roc

per wł

The portion of the survey between the Rivers St. John and Alleguash, was not so satisfactory as could have been desired; a summit of 350 feet (ascending East) was found between the rivers, which cannot be overcome on the line surveyed, with grades of 52-8 feet per mile. Two dotted lines are shewn on the small scale map, by either of which these and perhaps easier grades can be obtained. Of these two dotted lines, the one best calculated to reduce the grades is that running South from the River Daagwaam, intersecting the Yule line West of its crossing of the South-West branch of the River St. John, passed at this point approximately at 100 feet higher level than on the line surveyed. The ascent is thus practically modified and the desired grades obtained.

This line would have been surveyed on the return of the party but for the lateness of the season (November). The snow which had already fallen to a depth of fifteen inches, on these high places, was hourly becoming deeper, the party were without snow shoes and were 60 miles from the nearest settlement. Moreover, the "caches" of provisions left at intervals, had been robbed, leaving no alternative but to abandon the woods as quickly as possible, or risk starvation.

In order to avoid the summit mentioned, another line was examined atid its height estimated by the barometer; it runs some distance North of the line surveyed, crossing the Saint John River near "Seven Islands." A line generally direct and level can be obtained between the rivers, with a summit not exceeding '40 feet in height. As this survey proved so satisfactory, the Western end of the line was also examined. It was established by spirit level, that the height of land immediately South of the St. Lawrence in the Province of Quebec, could be passed some 8 miles further East, at Lac Boillard, 200 feet lower than on the line surveyed via Riviere aux Pins

This line (via Lac Boillard) leaves the North-West branch of the Riviere aux Pins, near the surveyed line, at the 25th mile and the head of the 39 foot grade. It is possible that this grade may be continued all the way to the summit owing to the lower altitude of Lac Boillard summit. The portion between the summit and Seven Islands, a distance of some 30 miles, also descends gently through a country favorable for railway construction.

This Northern line, and the line instrumentally surveyed, measure the same distance respectively (on the accompanying map), from St. Charles Station to a common point on the Mooselue River, from which point an extension Eastward could be made as readily as from the line surveyed. Owing to the more level character of the mile not

onial miles tance

Alle-

mmit vhich et per either these s that e line John, on the e departy h had was were s" of native ion. as exie disr near tained eight. e was ght of Que-1, 200

of the d, the e conf Lac Seven ugh a

reyed, map), River, ily as f the country, which requires much less angular deflection, the distance would be lessened by this line by about 4 miles, while for purposes of heavy freight the lower summits it passes over, will virtually shorten it many miles.

The fact that this line runs for some 20 miles, only a short distance from the International Boundary, would render it more useful to the Province of Quebec than one passing to a greater distance, as it would be the means of opening up several fertile and inaccessible parishes in the Eastern part of the Province, while, owing to its distance from any of the centres of trade in Maine, the Northern part of that State (including the fertile Aroostook Valley) would be made tributary to the Dominion.

COMBINATION LINE.

I beg leave to direct attention to line (marked No. 3 on the general map) which was explored as far as the summit and favorably mentioned in my report on the reconnoissance made in July last. Starting from Chaudiere Junction it would traverse the valleys of the Etchemin and Famine Rivers to the height of land near the village of St. Justin,

This summit is 950 feet above the starting point at Chaudiere Junction, or 509 feet lower than the summit on the line surveyed by Riviere du Sud. From St. Justin the line would continue its course South-East and nearly direct to the vicinity of the head of Lake Chesuncook, from whence it would connect with the line surveyed during the past season between that Lake and Canterbury.

From data on hand there is every reason to believe that grades not exceeding 35 to 40 feet to the mile can be easily obtained in both directions, by this route from Chaudière Junction to Canterbury.

• This line appears to me to possess advantages peculiar to itself, which I have deemed it my duty to point out in a special report.

COST.

I submit an estimate of cost of line by Rivière du Sud, in the appendix No. 1. I am quite satisfied that the cost of the line via Etchemin to Chesuncook would be somewhat less in amount, as the country is better, the grades easier and the work lighter. I am unable to make a detailed schedule of quantities for the whole distance, from the data on hand. Of 96 miles of the line surveyed, only 89 miles may be said to be approximately located.

I have taken out the quantities on the 39 miles where an approxinate location has been established; these calculations give a full average which may be applied to the whole mileage, and can be accepted with confidence, as representative of the whole work.

Where quantities could not be obtained, as in solid rock, loose rock, and masonry, the same average per mile was taken as was experienced on the Miramichi District of the Intercolonial Railway, which passes over a similar country. According to this estimate, the cost of the road fully equipped with stations, shops, wood sheds, water service, &c.; with the exception of rolling stock would be \$24,841 per mile. See Appendix No. 1 my

thi

of

O'I the

fac

cou

roa

onl

The plans and profiles accompanying the report are given in Appendix No. 2.

The field work done this season, consists of 4 lines baromerically examined, viz :---the direct, the Yule, the Rivière du Sud, and the line by the Seven Islands, including some supplementary examinations considered necessary,—aggretating 573 miles. The lines instrumentally surveyed, including offsets and cross sections amount to 207 miles, making 780 miles in all. (See Appendix No. 3.)

Tables of grades and curves are given in Appendix 4.

It will be seen on examining these tables that 2.05 miles of curves have been put down at 6. As they can be reduced to 4 by a reasonable expenditure of earthwork, I have so rated them in the report.

The part of the line surveyed through the Province of Quebec passes its whole length through the County of Bellechasse.

After leaving St. Charles, it passes near the thriving villages of St. Gervais, St. Rafaël, Armagh, Lafayette, St. Paul du Bûton and St. Magloire. The greater part of this distance, even up to the crown of the summit, is under a fair state of cultivation. The land, although in some cases stoney, is generally good and well watered, fit either for grazing purposes or the raising, of cereals. After crossing the summit all settlement ceases, although the climate is milder and the lands on the Southern slope are of better quality, well fitted for settlement and covered with forests of fine spruce, intermixed with ridges of large birch, maple, elm and other hard woods, which extend to the International Boundary.

After entering the United States the same description of land and fine timber extends throughout to the River Allaguash. Here there are no settlements. The lands are all in the hands of lumberers, who, from an experience of the disastrous fires caused by the farmers, discourage all settlement. These lumbermen import most of their supplies required for the North-Western part of the State from Quebec by St. Jean Port Joli and Seven Islands. The North-Eastern portion comes from St. John, N.B.

A railway constructed on any of the lines here mentioned would pass through the finest timber lands in Maine and would certainly do all the business of this fine country in the way of transport of supplies; and the sawn lumber as well as the squared birch and other hard woods that cannot be floated would be carried either to Quebec or St. John. A demand for such lumber is rapidly increasing as the finer woods, such as walnut and pine are rapidly disappearing. This would have the effect of virtually making the country tributary to the Dominion. See Appendix No. 5.

I cannot conclude without expressing my appreciation of the efficient assistance rendered me in the prosecution of the survey by my principal assistant, Mr. Edwin Forse, C.E., who has done everything in his power to make the examination a success.

I would also speak of the willing services of the other members of the force Messrs. O'Sullivan, Cunningham, F. Forse, S. Hill, O'Donnell, Guay, Olivier and Perron, who have one and all executed their various tasks with intelligence and zcal, and to my entire satisfaction.

The service was an arduous one, being prosecuted through a country the last 60 miles of which was entirely wild, destitute of roads and other means of transportation, where the barest necessaries only were carried by portageurs.

I have the honor to be, Sir,

Your obedient Servant,

(Signed,) A. L. LIGHT,

Chief Engineer Government Railways,

Province of Quebec.

Ottawa, 23rd March, 1885.

ped

cep-

0.1

ı in

the

ions ent-

207

s of by a

e re-

ebec

es of d St:

on of ough ither the i the ettledges o the

and here who, dissupc by tion

ould inly t of and r to sing tary

> the by

APPENDIX No. 1.

28

SHORT LINE RAILWAY.

QUEBEC TO ALLAGUASH.

ESTIMATE of Line via the Rivière du Sud, running South of Yule and Churchill Lakes to the Allaguash River-92 miles.

970 2,514,000 122,176 323,840	Right of way and damages@ Acres clearing (80 miles)" Cubic yards Embankment" " " Rock excayation" " " Loose rock ""	\$ 25 0 1	c. 00 30	\$ 20,000 24,250	с. 00
970 2,514,000 122,176 323,840	Right of way and damages@ Acres clearing (80 miles)	25 0 1	 00 30	20,000 24,250	00
970 2,514,000 122,176 323,840	Acres clearing (80 miles)	25 0 1	00 30	24,250	
2,514,000 122,176 323,840	Cubic yards Embankment " " " Rock excayation " " " Loose rock " "	0 1	30		00
122,176 323,840	" " Rock excavation" " " Loose rock ""	1		754,200	00
323,840	" " Loose rock " "		50	183,264	00
10,000		0	50	161,920	00
19,200	Lineal rods fencing (30 miles) "	1	25	24,000	00
. 8,000	Cubic vards 1st class Masonry "	. 12	00	96,000	00
5.000	" " 2nd " " "	8	00	40,000	00
13.000	" " Culvert " "	5	00	65,000	00
242,880	Sleepers (2 centres)	0	.20	48.576	00
9,568	Tons Steel rails and fastenings "	. 30	00	287.040	00
92	Miles Track laving	250	00	23,000	00
276.000	Cub. vds. Ballast (3.000 c. vds. per				
,	mile)	0	30	82,800	00
700	Lineal feet Steel Bridging	60	00	42,000	00
3 000	" " " Trestle "	40	00	120,000	00
195	Wift h m Timber in Cattle-grands "	20	00	2,500	00
0	Passanger and Freight Stations "	1 500	00	13,500	00
	Wood Shade	400	00	8,600	00
5	Water Tenka with numping Fu-	100	00	0,000	00
J	water ranks, with pumping mi-	2 000	00	15 000	00
-	Engine House with 19 stells (5,000	00	15,000	00
1	Machine Shep and firtures	•••••	••••	20,000	00
1	Machine Shop and fixtures	7 000		20,000	00
D	Milles slaing	1,200	00	30,000	00
				00 077 CEO	00
0.1	All Clautin marine' and Engineer			\$2,011,000	00
	Add-Contingencies and Engineer-	1	τ.,	007 705	00
	ing, 10 per cent			201,765	00
	Matel antimited and for 1st stores				1
• 7	Total estimated cost for Jst class road			60 005 11H	00
	as above			\$2,285,415	00
	A			404 044	00
	Average per mile			\$24,841	00

1st

2n

3rd

4th

5th

APPENDIX No. 2.

le and

unt.

)0000)0000)7600)4000)0000

50,00 65 00

<u>15 00</u> 41 00 29

1	45	The maps and profiles which accompany this report, consist :
in the second se		1st.—Of a map and profile on the same sheet, of the whole line, on a scale of 1,000 feet to the inch, horizontal, and 100 feet vertical.
		2nd —A Topographical Map of 400 feet to the inch, shewing an approximated location of of 65 miles, and the general character of the country in the immediate vicinity of the line, the rivers, mountains, &c.
-		3rd.—A Profile, on the same horizontal scale of 400 feet to the inch, 20 feet to the inch vertical.
a la a	and the second	4th.—A map and profile of the country between the Rivers St. John and the Allaguash, scale 5,000 feet to the inch horizontal and 100 feet vertical; shewing the line and profile as surveyed over the intervening summits; also, two dotted lines where
*		better grades can be obtained; further shewing the grades that can be obtained east and west of the St. John River, near Seven Islands.
	2	5thTache's Map of the Province of Quebec, on a scale of 14 miles
S.		to the inch, shewing in general all routes which have been examined.
		1
	No.	
100	12	state of the state
2		
2		
	A Contraction of the second	
2		
2		
2		
	A de la contra de la	
	1	

APPENDIX No. 3.

BAROMETRICAL OBSERVATIONS, GENERALLY WITH TWO ANEROIDS.

	Milles.
Direct line, Chaudière Station to Alleguash River	100.00
Yule do do do	114.00
Rivière-du-Sud, from St. Charles Station do	96.00
Rivière-aux-Pins, via Seven Islands to Mooseluc.	85.00
Rivière-aux-Pins to St. Magloire and River Daagwaam	25.00
From River Daagwaam, across portage, to South-West St. John.	10.00
Daagwaam to St. Justin Summit (spirit levels)	12.60
St. Magloire to north-west branch of St. John River	10.00
From forks of the S. W., up ditto and up South Branch of St.	N.
/ John	25.00
From Dam at Churchill Lake to Chamberlain Farm	25.00
Around South end of Yule Lake	7.00
From Churchill Dam to Harveys, foot of Unsaskis Pond	18.00
From foot of Unsaskis Pond to Seven Islands	14.00
From Seven Islands to Black River Lake	10.00
From Seven Islands to St. Pamphile	22.00
- m	

573.09

APPENDIX No. 4.

INSTRUMENTAL SURVEYS. -

Lines chopped, chained and levels taken and checked.

	Miles.
From 4 miles west St. Charles Station to Alleguash River	96.54
Offsets on do do do Cross Sections do do do }	46.00
From Summit, via Long Lake, to Robber Street	15.00
From do to Lac Boillard and two intermediate summits.	12.00
Raphael, including offsets and sections	$25.00 \\ 12.40$
	206.94
Total number of miles surveyed, examined and checked	-779.94
Number of miles of levele checked	122.76

4000

				4	Ø .				1123
· · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·			15 			.90	217
			· · ·	14 13 14 14				.70	5 m 16 18
DS.	14 - 14 - 14 - 14 - 14 - 14 - 14 - 14 -	vi stanisti vi			·	RLY.		02	ۍ ن ^ي ر
A:log	100	The st			•	TE	feel		
00.00			-1			VES	00	.60	
14.00			· 4	iĝ.	54	P	T		
96.00	and the second sec	÷.	e .		· [] ,	DNI	pe	40	les
85.00	· · · · · ·	2.5			M	IQN	ate		Mi
10.00	See.			18 ·	Sth	CE	A	30	:
12.60	26		5	es.	.9	As			
10.00			Þi	MEI	OI	•		00	
95.00		T.	A	2	O _N	1.1	•	GA GA	
25.00			K	6-	WO			00	
7.00		4	H	H	FR	1		L Ci	
18.00		No.	A.	AS					
14.00		M.	щ	DE	ED			.00	
22.00	1 de	19	A	AG	SOA	18.4	1		. 4
79.00	and the second	ENI	A.	ALL	PROI			°.80 .90	
13.00	per la constitución de la consti	dd	н	0	24			80	
÷ .	and the second se	A	H	F	ADE	ILY		···	
Lave?			HO	EC	JR	LER	eet	-00	-6
	No.		Ĭ	EB	5	AST	0	ô Ŀ	0.4
er :		2	Ø	6	0	E	F	60	2.6
Iiles.		b ^a rj.		G	LN	DN	per	• •	Mil 0.
96.54				5 -	WE	NDI	te	00	:
46.00	1		` ~	•	ATE	CE	Ra	4.13	
15.00					ST	As		30 40	. :
12.00			*		*		1		-
5.00		3.			-			.30	0.68
2.40	1		er '		10	•		-00	
								401	
6.94		194							1
		7. 2	1 .	. 14			-	/	
9.94			2		ck				10
0 70				4.1	120		: ;;;;	Distanc	ile
2.76	-	5	1		1 . 1	3 12	and the	- 1	NO

Of the remaining distance to the Allaguash, 28 miles, probably one-half will require a maximum grade of 1.00 per 100, but this maximum will probably not be required at any one place, for a greater distance than 5 miles.

81

6. 00. 2.30

2.58 5.15 9.20 1.14

5 60

...... 0.28 0.57

0.25 0.72

0.19 0.47 3.21

10 to 20 20 to 30 30 to 40 40 to 50 50 to 60 60 to 65

....

0.61

2.44 77.0

0.38

0.38

0.38 0.28

.....

1.54

14.00

3.21

0.38

0.95

0.38

0.28

22.22

1.25 0.49 10.45

8.33 0.72 0.68 0.75 0.91

..... 0.68

..... 0.34

0.47

APPENDIX No. 4.-Continued.

SHORT LINE RAILWAY.

QUEBEC TO ALLAGUASH. -

We Va

ac

the parals be log req

sea boo tity of o

ere wh less that as v at s will M.1

STATEMENT SHEWING APPROXIMATE ALIGNMENTS.-From 0 to 65th mile.

		• •					
From—To	Tan- gents.	20	ʻ 3 0	40	50	60	Total Miles.
		Rad. 2865'	Rad. 1910'	Rad. 1432'	Rad. 1146.	Rad. 955'	, , , , , , , , , , , , , , , , , , ,
Miles.	Miles.	Miles.	Miles.	Miles.	Miles.	Miles.	Miles.
0 to 10	9.23	0.77				······	10.00
10 to 20	6.82	0.51	1.61	0.38		0.68	10.00
20 to 30	6.83	0.55	1.36	1.06		0.20	10.00
80 to 40	8.06		1.60			0.34	10.00
40 to 50	7.04	0.25	1.34	0.54		0.83	10.00
50 to 60	7.87	1.13	1.00				10.00
60 to 65	5.00	,			9ª 1		5.00
4 (d	50.85	3.21	6.91	1.98		2.05	65.00

Note .-- Total curvature -- 22 per cent of whole distance.

Of the remaining distance to the Allaguash 28 miles.

The curvature will not exceed above average."

32.

APPENDIX No. 5.

Either of the lines crossing the Saint John River and its branches would open extensive sources of industry to the inhabitants of the valley of the Saint Lawrence, as they will give a ready means of access to the sea for manufactured wood of all kinds.

65th

Cotal

files.

liles.

10:00

10.00

10.00

10.00 10.00 10.00 5.00

65.00

The head waters of the Saint John and other rivers which take their rise on the range of hills lying South of the Saint Lawrence, pass not only through lands covered with a growth of hard wood, but also through or adjacent to large tracts of black spruce which cannot be successfully utilized at present owing to the distance which the logs have to be driven before reaching the sea, as well as to the time required for the same; much of this timber being unable to reach the sea until the expiration of two years, and at a cost of men, driving, booming, etc., of \$2 per M.F.B.M. There is also a considerable quantity of pine left by the timber makers, as well as an enormous quantity of cedar, which railway communication will render available.

Should either of these lines be built, mills will immediately be erected on the various streams which will be crossed, and the lumber when sawn will be delivered at much cheaper rates, as well as within less than half the time, at the seaboard on the St. Lawrence by rail, than it can now be done by rivers. Hay, oats, provisions and supplies as well as river drivers and laborers for the woods can also be carried at so much cheaper rate than at present from the St. Lawrence, as will reduce the cost of producing deals at least two dollars per M.F.B.M.







Compiled from EUGENE TACHE'S Map of the Province of Quebec.

SHEWING SEVERAL PROPOSED LINES FOR THE

SHORT LINE RAILWA

Between MONTREAL and the Cities of ST. JOHN and HALIFAX,

Via QUEBEC and CHESUNCOOK and

* _____Via MEGANTIC and METTAWAMK

WITH SPECIAL REFERENCE TO A

Combination Line.



nce of Quebec. LWAY

HALIFAX,

TAWAMKEAG,

ine.

L. PISCATOS

SCATONQUE















