

**CIHM  
Microfiche  
Series  
(Monographs)**

**ICMH  
Collection de  
microfiches  
(monographies)**



**Canadian Institute for Historical Microreproductions / Institut canadien de microreproductions historiques**

**© 1994**

The  
con  
ma  
of  
sig  
ch



This  
Ce d

10:



Technical and Bibliographic Notes / Notes techniques et bibliographiques

The Institute has attempted to obtain the best original copy available for filming. Features of this copy which may be bibliographically unique, which may alter any of the images in the reproduction, or which may significantly change the usual method of filming, are checked below.

L'Institut a microfilmé le meilleur exemplaire qu'il lui a été possible de se procurer. Les détails de cet exemplaire qui sont peut-être uniques du point de vue bibliographique, qui peuvent modifier une image reproduite, ou qui peuvent exiger une modification dans la méthode normale de filmage sont indiqués ci-dessous.

- Coloured covers/  
Couverture de couleur
- Covers damaged/  
Couverture endommagée
- Covers restored and/or laminated/  
Couverture restaurée et/ou pelliculée
- Cover title missing/  
Le titre de couverture manque
- Coloured maps/  
Cartes géographiques en couleur
- Coloured ink (i.e. other than blue or black)/  
Encre de couleur (i.e. autre que bleue ou noire)
- Coloured plates and/or illustrations/  
Planches et/ou illustrations en couleur
- Bound with other material/  
Relié avec d'autres documents
- Tight binding may cause shadows or distortion  
along interior margin/  
La reliure serrée peut causer de l'ombre ou de la  
distorsion le long de la marge intérieure
- Blank leaves added during restoration may appear  
within the text. Whenever possible, these have  
been omitted from filming/  
Il se peut que certaines pages blanches ajoutées  
lors d'une restauration apparaissent dans le texte,  
mais, lorsque cela était possible, ces pages n'ont  
pas été filmées.

- Coloured pages/  
Pages de couleur
- Pages damaged/  
Pages endommagées
- Pages restored and/or laminated/  
Pages restaurées et/ou pelliculées
- Pages discoloured, stained or foxed/  
Pages décolorées, tachetées ou piquées
- Pages detached/  
Pages détachées
- Showthrough/  
Transparence
- Quality of print varies/  
Qualité inégale de l'impression
- Continuous pagination/  
Pagination continue
- Includes index(es)/  
Comprend un (des) index

Title on header taken from: /  
Le titre de l'en-tête provient:

- Title page of issue/  
Page de titre de la livraison
- Caption of issue/  
Titre de départ de la livraison
- Masthead/  
Générique (périodiques) de la livraison

- Additional comments: /  
Commentaires supplémentaires:

This item is filmed at the reduction ratio checked below/  
Ce document est filmé au taux de réduction indiqué ci-dessous.

10x	12x	14x	16x	18x	20x	22x	24x	26x	28x	30x	32x
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>						

The copy filmed here has been reproduced thanks to the generosity of:



University of Manitoba  
Winnipeg

The images appearing here are the best quality possible considering the condition and legibility of the original copy and in keeping with the filming contract specifications.

Original copies in printed paper covers are filmed beginning with the front cover and ending on the last page with a printed or illustrated impression, or the back cover when appropriate. All other original copies are filmed beginning on the first page with a printed or illustrated impression, and ending on the last page with a printed or illustrated impression.

The last recorded frame on each microfiche shall contain the symbol  $\rightarrow$  (meaning "CONTINUED"), or the symbol  $\nabla$  (meaning "END"), whichever applies.

Maps, plates, charts, etc., may be filmed at different reduction ratios. Those too large to be entirely included in one exposure are filmed beginning in the upper left hand corner, left to right and top to bottom, as many frames as required. The following diagrams illustrate the method:



L'ex  
géné

Les  
plus  
de la  
cont  
filma

Les  
papi  
par  
dern  
d'im  
plat  
orig  
pren  
d'im  
la d  
emp

Un  
dern  
cas:  
sym

Les  
film  
Lors  
repr  
de l  
et d  
d'im  
illus

duced thanks

L'exemplaire filmé fut reproduit grâce à la générosité de:

University of Manitoba  
Winnipeg

et quality  
d legibility  
th the

Les images suivantes ont été reproduites avec le plus grand soin, compte tenu de la condition et de la netteté de l'exemplaire filmé, et en conformité avec les conditions du contrat de filmage.

s are filmed  
ding on  
ted impres-  
iate. All  
ning on the  
impres-  
n a printed




Les exemplaires originaux dont la couverture en papier est imprimée sont filmés en commençant par le premier plat et en terminant soit par la dernière page qui comporte une empreinte d'impression ou d'illustration, soit par le second plat, selon le cas. Tous les autres exemplaires originaux sont filmés en commençant par la première page qui comporte une empreinte d'impression ou d'illustration et en terminant par la dernière page qui comporte une telle empreinte.

ofiche  
g "CON-  
"END"),

Un des symboles suivants apparaîtra sur la dernière image de chaque microfiche, selon le cas: le symbole  $\rightarrow$  signifie "A SUIVRE", le symbole  $\nabla$  signifie "FIN".


ned at  
arge to be  
filmed  
er, left to  
nes as  
trate the

Les cartes, planches, tableaux, etc., peuvent être filmés à des taux de réduction différents. Lorsque le document est trop grand pour être reproduit en un seul cliché, il est filmé à partir de l'angle supérieur gauche, de gauche à droite, et de haut en bas, en prenant le nombre d'images nécessaire. Les diagrammes suivants illustrent la méthode.



# MICROCOPY RESOLUTION TEST CHART

(ANSI and ISO TEST CHART No. 2)



1.0

4.5

2.8

2.5

5.0

5.6

3.2

2.2

6.3

7.1

3.6

8.0

9.0

10

11.2

12.5

14

16

18

20

22.5

25

28

31.5

35

40

45

50

56

63

71

80

90

100

112

125

140

160

180

200

22.5

25



1.1



2.0



1.8



1.25



1.4



1.6



APPLIED IMAGE Inc

1653 East Main Street  
Rochester, New York 14609 USA  
(716) 482 - 0300 - Phone  
(716) 288 - 5989 - Fax

# REPORT

ON

Storage Battery and Overhead Wire Systems

OF

## Electric Street Railways

FOR THE

CITY OF WINNIPEG,

BY

H. N. RUTTAN, M. Inst. C. E., M. Can. Soc. C. E.,

CITY ENGINEER.

---

PRINTED BY ORDER OF THE COUNCIL.

---

WINNIPEG:

THE STOVEL COMPANY, PRINTERS.

1891.

Storage

**Elect**

CIT

H. N.

PRIN

# REPORT

ON

Storage Battery and Overhead Wire Systems

OF

## Electric Street Railways

FOR THE

CITY OF WINNIPEG,

BY

H. N. RUTTAN, M. Inst. C. E., M. Can. Soc. C. E.,

CITY ENGINEER.

---

PRINTED BY ORDER OF THE COUNCIL.

---

WINNIPEG:

THE STOVEL COMPANY, PRINTERS.

1891.

*His W*

GEN  
report o

The  
during  
Washing  
Montrea

My  
trolly”  
would p

State  
maintena  
do not p  
or set of  
intended  
The ques  
one whic  
or compa  
pend as m  
of the stre  
ditions, po

Some i  
large and  
of the bus  
places.

My tha  
several cit  
panies, fron

CITY ENGINEER'S OFFICE,

WINNIPEG, MAN., 4th JULY, 1891.

*His Worship, the Mayor, and Council of the City of  
Winnipeg:*

GENTLEMEN,—I have the honor to submit herewith my report on Electric Railways.

The report has been compiled from information obtained during visits to Minneapolis, St. Paul, Dubuque; Chicago, Washington, Philadelphia, New York, Boston, Lynn, Montreal, Ottawa and Toronto.

My observations were chiefly directed to the "overhead trolley" and "storage battery" systems as those which would probably be most suitable for Winnipeg.

Statements of the cost of construction, operation and maintenance of both systems are given. These estimates do not pretend to absolute accuracy for any particular place or set of conditions. It will be understood that they are intended to show a comparison of the two systems only. The questions of the values of street railway franchises is one which it is most difficult to show by any set of figures or comparative statements. The values of franchises depend as much upon the enterprise and good management of the street railway companies as they do upon local conditions, population, grades, climate, etc.

Some instances might be given of railways in cities of large and dense population which are not doing one quarter of the business of railways similarly situated in other places.

My thanks are due to the officers and engineers of the several cities, electric railway and manufacturing companies, from whom I experienced the greatest kindness,

and secured most valuable assistance and information, including documents and records which have been of great service to me.

Your obedient servant,

H. N. RUTTAN,  
*City Engineer.*

---

#### OVERHEAD SYSTEM AND TRACKS.

In Minneapolis the general practice is to place poles in the centre of the street between tracks, which are from  $3\frac{1}{2}$  to 4 feet apart. On narrow streets this has the effect of driving the vehicle traffic to the sides of the street, as the centre cannot be used on account of the poles; on many streets there is barely room for a wagon to pass between the car and the curbstone. If street railway traffic goes on increasing in Minneapolis as it has done in the past year, it will be in a short time dangerous or quite impossible to use ordinary vehicles on some of the streets. In Boston, where the wiring is done from the sides of the street, even in the case of long spans, the overhead system appears much less objectionable.

There is no good reason why telegraph and telephone poles, where in suitable positions, should not be used to support the cross-wires of the overhead system. They are so used in Ottawa, where it has been found that very few extra poles are necessary.

In cases where the streets are not very far apart, the "loop" system of tracks has many advantages. Single tracks only are necessary; the cars running down one street and up a parallel street. The loops are interwoven like those of a chain—the cars running in one direction on one link, and in the opposite direction on the other—thus giving street-car connection in both directions to within at the most one block of every street. This system is used to

a great  
the pr  
the do  
Th  
follows  
For  
weighi  
Tier  
with d  
ballast  
roadbed  
For  
50 lbs.  
above, w  
side of r  
tudinal  
material  
track, T  
paved.  
It ha  
lighter s  
above the  
Mech  
leverage  
seat and  
well as to  
pieces wh  
In Wa  
is used.  
wheel flan  
chipping  
severe, par  
grooves ar  
On the  
on a longit  
ment mate  
both sides.

a great extent in Philadelphia, and for all streets, except the principal business streets, has many advantages over the double track system.

The system of track construction recommended is as follows :

For paved streets a girder rail 6 inches in height, and weighing 70 lbs. per yard.

Ties 7 feet long, 6x6 inches, spaced 30 inch centres, with double tie at joints. Six inches clean gravel or stone ballast under ties, on thoroughly consolidated and drained roadbed.

For unpaved streets a T rail, 4 inches high, of about 50 lbs. per yard, laid on ballasted ties, 2 feet centres, as above, with longitudinal strip 4x6 inches spiked to ties outside of rail, and chamfered one inch on outside ; and longitudinal strip 3x4 inches spiked to ties inside rail. Road material to be trimmed up to strip inside and outside of track, T rail to be changed to girder rail when streets are paved.

It has been a common practice to use girder rails of lighter sections than that above specified, and to raise them above the ties by chairs spiked to the ties.

Mechanically the chair track is objectionable, the side leverage on the rails having a tendency to loosen the rail seat and chair spikes, and the track is expensive to lay, as well as to maintain, on account of the large number of pieces which have to be handled and accurately fitted.

In Washington a girder rail of the flange groove section is used. This rail has the disadvantages of binding on the wheel flanges and wearing them on the insides, sometimes chipping or breaking them, making the traction more severe, particularly on curves, and in a cold climate the grooves are not easily cleared of ice and snow.

On the asphalt pavement in Washington this rail is laid on a longitudinal bed of concrete, and bedded in the pavement material which is brought into contact with it on both sides.

## DUBUQUE STREET RAILWAY.

The Dubuque Street Railway Co., of which Mr. J. A. Rhomberg is president, placed a trial car of the Electro Dynamic Co., (known as the "Edco," from the initial letters of its name), on their line in August, 1890. Mr. Rhomberg was so satisfied with the working of the trial car that he has concluded an arrangement with the Edco Co. to equip his line with storage battery cars. At the date of my visit to Dubuque, 25th May, 1891, four of the new cars were in operation, and others were being got ready. It is expected that 15 cars will be in operation this fall. Both the railway company and the public appear to be satisfied with the operation of the storage battery system.

The heaviest grade on the line is about four (4) per cent. The loaded cars experience no difficulty in surmounting it.

The cars run smoothly and make no more noise than an ordinary vehicle on a paved street. The freedom from noise is, of course, due to the form of motor used.

The Dubuque Installation may be considered one of the most perfect storage street railway systems now in use, an extended description of the details of the system may, therefore, be of interest.

The cars are 14 feet in length, and seat comfortably 22 people. They are fitted with two 15 H. P. motors each.

The storage battery equipment for each car consists of two sets of 80 cells, one of which is being charged while the other is in use on the car. Each set of batteries is carried in two iron boxes or trays, containing 40 cells each, which are placed under the car seats. The batteries which are being charged are placed on a platform, level with the car floor. A travelling truck is used in transferring the battery trays between the platform and the cars. The battery trays are provided with racks which are worked

by pin  
man h  
1600  
changi  
less tin  
All  
in cars  
Pho  
Two of  
truck.  
Elec  
capacity  
Stor  
weight o  
of 180 a  
Batter  
cars run  
Recon  
Aver  
Aver  
Aver  
cells, two  
As a  
two volts  
down to  
per cent.  
as a marg  
The ra

Two H  
for about  
Street Rail  
A contr  
Co. to supp  
factured by

by pinions on the cars, truck, and charging table. One man handles with ease a battery tray weighing between 1600 and 1700 pounds. Two minutes is allowed for changing the batteries, though the change can be made in less time.

All electrical connections are made automatically, both in cars and on charging table.

Photographs of the car and transfer truck are enclosed. Two of the battery trays are shown in position on the truck.

Electrical equipment data: 1 generator, 50,000 watts capacity; E. M. F. 250 volts, intended to run six cars.

Storage battery: 2 sets of 80 cells each, per car; weight of cells each, 40 lbs., cells said to have a capacity of 180 ampere hours.

Batteries are changed every three hours, in which time cars run 21 miles.

Record of running four cars on 24<sup>th</sup> May, 1891:

Average E. M. F. of batteries coming in, 160 volts.

Average E. M. F. of batteries going out, 175 volts.

Average time taken to charge each battery of eighty cells, two hours.

As a rule E. M. F. is not allowed to go below 160 volts, two volts per cell, though it is stated that it may safely run down to 144 volts. It appears, therefore, that about 50 per cent. of the storage capacity of the battery is reserved as a margin of safety.

The rails used for the line are about 52 lb. girder rails.

#### WASHINGTON.

Two Edco storage battery cars have been running for about four months on the lines of the Washington Street Railway Co.

A contract has been made with the Electro-Dynamic Co. to supply six more cars, which are now being manufactured by the J. G. Brill Car Company, Philadelphia.

It is stated that there is a guarantee for three years that the operation of these cars will not exceed, in cost, that of the overhead system in the same place.

A failure of the batteries took place once, about five weeks after the first cars were placed on the line. The Edco Co. claim that the failure was due to accident or improper usage. No trouble has been experienced since, though the arrangements for charging and changing the batteries are imperfect.

The charging is done from the wires of the overhead system, using a resistance to get the required E. M. F. The batteries are changed at the sides of the car. The new equipment is to be similar, with the exception of the size of the cars, to that described for Dubuque.

Mr. C. O. Mailloux, consulting engineer of 32 Liberty St., New York, states that a plant to cost \$500,000 has been arranged for and is now being installed by him for another Washington company.

In Washington both the overhead and storage systems are used by the same Co., the storage being used on certain streets where overhead wires have been prohibited.

#### PHILADELPHIA.

The street railways in this city are operated by cable or animal power. Up to the present time the city authorities have refused to permit the erection of the overhead system.

#### NEW YORK.

The Julian storage battery cars which were run for some time on Fourth Avenue, New York, were taken off on account of a lawsuit and injunction obtained by the Electro-Dynamic Co. for an alleged infringement of the Faure patents, held by the latter company, on storage batteries. It was learned that the cars referred to were exhibition cars, used for the purpose of advertising the system, and were run at a great disadvantage, being

obliged  
horse ca  
unavoid  
Ther  
York at

The c  
End Str  
overhead  
This  
to electri  
typical st  
modernize  
increase in  
and of its  
traffic, and  
unfavorabl  
guarantee  
is much su  
Reports  
electric syst  
several peo  
Upon en  
the officials  
that no dea  
that those r  
and such lik  
system of ra  
The follo  
to Mr. Arth  
national Elec  
civic authori

DEAR SIR  
system as use  
End Street B

obliged to run on the same tracks as, and between the horse cars, and subject to all the delays and stoppages unavoidable in the locality.

There are no electric railways of any kind in New York at present.

BOSTON.

The only electric railway in Boston is that of the West End Street Railway Co., who use the Thomson-Houston overhead system.

This company is gradually changing from horses to electricity, and has many points of interest as a typical street railway of the old style in process of being modernized; the wonderful exhibit which it makes of the increase in traffic resulting from the change to electricity, and of its ability to fully meet requirements of excessive traffic, and to continue running without interruption during unfavorable weather and heavy snow storms, are sufficient guarantees that both in economy and efficiency electricity is much superior to animal traction.

Reports had been circulated to the effect that the electric system was not approved by the citizens, and that several people had been killed by the electricity.

Upon enquiry from the superintendent of streets, and the officials of the Thomson-Houston Co. it was learned that no deaths had resulted from electrical accident; but that those referred to were caused by collisions, run overs and such like accidents which are liable to occur with any system of rapid transit.

The following letter from the Superintendent of Streets to Mr. Arthur W. Jones of the Thomson-Houston International Electric Co. is conclusive as to the opinion of the civic authorities:

BOSTON, NOVEMBER 24, 1890.

DEAR SIR,—I am pleased to state that the electric system as used in this city as motive power in the West End Street Railway service, has given satisfaction to the

public. Its advantages over the use of horses are, first, greater speed, possibly attended with a slight increase in the element of danger to pedestrians and vehicles; second, greater cleanliness, due to the entire absence of horses and their droppings.

From my observations of its working thus far, I think it has come to stay, and the travelling public would not consent to a return of the old system.

Very truly yours,

(Signed) J. EDWIN JONES,  
Superintendent of Streets.

The following table shows the number of cars and mileage of the West End railway for the dates given:

Date.	No. of Motor Cars.	Motor Cars including Towed Cars.	
			Mileage.
Feb., 1889.	9		15,186
March, "	9		36,088
April, "	8		36,829
May, "	9		39,331
June, "	9		38,338
July, "	10		69,238
August, "	13		74,550
Sept., "	31		123,040
Oct., "	31		104,328
Nov., "	38		139,314
Dec., "	68		199,551
Jany., 1890.	84		217,021
Feb., "	130		247,679
March, "	130		254,492
April, "	130		272,914
May, "	201		331,733
June, "	255		351,906
July, "	270		389,695
August, "	308		384,749
Sept., "	312		413,414
Oct., "	288		407,462
Nov., "	287		404,028

At the

In r  
tinue op

On t  
fall of a  
papers o  
in which

storm.

The p  
the Thom

"I th

St. Ry. C

on the spl

scrapers, c

"This

had since

I am told

system wa

itself.

"There

electric sy

through th

As show

Railway Co

March 3rd,

tired for el

day, only tw

at six o'clock

Dec., 1890.	282	402,204
Jan., 1891.	282	386,598
Feb., "	282	363,315
At the present time, over	300	

## Snow.

In reference to the ability of electric railways to continue operations during heavy snow storms :

On the 2nd March, last, a severe storm, with a snow fall of about 18 inches, occurred in Boston. The newspapers of that date bear testimony to the efficient manner in which the West End Street Railway worked during the storm.

The president of the company, Mr. Whitney, writes to the Thomson-Houston Co., as follows :

"I think the Thomson-Houston Co., and the West End St. Ry. Co., have good reasons to congratulate themselves on the splendid performance of the electric cars, plows and scrapers, during the snow storm of March 4th.

"This was by far the heaviest fall of snow we have had since we have used electricity as a motive power, and, I am told, the heaviest for several years. The whole system was operated without a hitch ; this fact speaks for itself.

"There is no doubt but that, with sufficient power, the electric system we are using would operate successfully through the worst snow storms of our climate."

As shown by the daily reports of the West End Street Railway Company, of cars in the house at six o'clock, on March 3rd, after 20 hours of storm, no cars had been retired for electrical troubles ; on March 4th, the severest day, only two cars were in the house for electric troubles at six o'clock ; and on March 5th, only one car.

VALUE OF STREET RAILWAY FRANCHISES.

The following is a synopsis of the conditions upon which the City of Toronto received tenders for the purchase and operation of their street railway system :

It will be remembered that the city took over the system from the company who had been operating it, paying the company an amount fixed by arbitration, viz. : \$1,453,788.

The party whose tender is accepted must take over all the property acquired by the city from the Toronto St. Ry. Co., at the amount of the award of the arbitrators.

The purchaser shall not charge the undertaking with bonds or debentures for a longer period than the term of the contract.

At the termination of the contract the city may take over the real and personal property necessary to be used in working the said railways, price to be fixed by arbitration.

The city will construct, reconstruct and maintain in repair, the street railway portion of the roadways, viz. : For double track, 16 ft. 6 in., and for single track, 8 ft. 3 in., on all streets traversed by the railway system, but not the tracks and substructure required for the said railway.

The purchaser shall pay the city the sum of \$800 per annum, per mile of single track (not including turnouts) and shall also pay the city per month, on the first Monday of each month, . . . per cent. of the gross receipts from passenger fares, freight, etc., and other sources of revenue obtained by operating the said railway.

The purchaser shall maintain all tracks to the satisfaction of the city engineer, and shall renew or replace the same as circumstances may require and as the city engineer may direct. In case of repavement of a street, tracks are to be removed and relaid in accordance with best modern practice.

When  
any exist  
electricit  
in conjun  
herein de  
Gener  
for repair  
The p  
down new  
service in  
mended b  
Provisi  
municipali  
In case  
the privile  
any other  
Provisi  
for city pur  
Privileg  
Provisi  
when it exc  
Electric  
system, app  
the council,  
Provisi  
Provisi  
engineer.  
No empl  
10 hours per  
no adult shal  
Rights re  
ways, and rail  
The follo  
have been rec

When the purchaser desires or is required to change any existing track, for the purpose of operating by electricity, the city will lay down a permanent pavement in conjunction therewith, upon the track allowance, as herein defined.

General conditions as to replacing roadbed taken up for repair of track.

The purchaser will be required to establish and lay down new lines, and to extend the track and street car service in such streets as may be from time to time recommended by the city engineer and approved by the council.

Provisions as to connecting with lines outside the municipality, in conformity with foregoing provisions.

In case purchaser fails to construct new lines as above, the privilege of laying down such lines may be granted to any other person or company.

Provisions enabling city to take up and replace track for city purposes.

Privilege hereby granted, subject to all existing rights.

Provisions as to removal of snow and ice from tracks, when it exceeds 6 inches in depth must be carted away.

Electric or other new system of motor, or combined system, approved by the city engineer and confirmed by the council, shall be introduced within one year.

Provisions as to sale of reduced fare tickets.

Provisions as to transfers to be satisfactory to city engineer.

No employee shall be compelled to work more than 10 hours per day, nor more than six days per week, and no adult shall be paid less than 15 cents per hour.

Rights reserved to build elevated or underground railways, and railways on certain streets.

The following table shows the several offers which have been received :

\* SCHEDULE 'A.' Synopsis of Results of Analytical Statements Showing Amounts to be Received by City Under Tenderers.

NAMES OF TENDERS.	Capital \$2,000,000	Capital, \$1,000,000	Capital, \$1,000,000	Capital, \$1,500,000
	Receipts \$750,000	Receipts \$1,000,000	Receipts \$1,000,000	Receipts \$1,500,000
	With 80 miles of Track	With 80 miles of Track	With 100 miles of Track	With 100 miles of Track
	City will Receive	City will Receive	City will Receive	City will Receive
Miller Bros. ....	\$110,725	\$142,850	\$278,500	\$387,850
Kiely, Everett, and Others. ....	117,250	135,000	175,500	237,000
“ if bonds guaranteed. ....	122,250	150,000	180,500	257,000
“ Alternative No. 2, if no cheap tickets	132,250	155,000	205,500	277,000
“ Alternative No. 2, if no cheap tickets and bonds guaranteed. ....				
Kiely, Everett, Alternative No. 3, in lieu of percentage and mileage. ....	137,250	170,000	220,500	297,000
Kiely, Everett, Alternative No. 3, in lieu of percentage and mileage, but bonds guaranteed. ....	136,000	136,000	136,000	136,000
Kiely, Everett, Alternative No. 3, in lieu of percentage and mileage, and without cheap tickets. ....	141,000	151,000	151,000	156,000
Kiely, Everett, Alternative No. 3, in lieu of percentage and without cheap tickets. ....	151,000	151,000	151,000	151,000
Kerr, Brock, and others. ....	156,000	166,000	166,000	171,000
“ Alternative No. 2, \$800 per mile and 60 per cent. of net profits. ....	100,300	130,050	257,550	368,050
Kerr, Brock, Alternative No. 3, \$800 per mile, 5 per cent. of gross receipts after deducting am'ts received from sale of tickets at reduced fares & 40 per cent net profits	96,400	117,400	207,400	291,800
* From report of City Engineer, City Solicitor and City Treasurer of Toronto, re tenders received for Street Railway property.	101,592	123,563	198,563	266,567

\* B

Synopsis of Analytical Statements, Provision having been made by City for Interest and Sinking Fund upon Permanent Pavements only.

\* From report of City Engineer, City Solicitor and City Treasurer of Toronto, re tenders received for Street Railway property. 266,567  
 198,563  
 123,563  
 101,592

\* B

Synopsis of Analytical Statements, Provision having been made by City for interest and Sinking Fund upon Permanent Pavements only.

— ASSUMING —

NAMES OF TENDERS.	Capital, \$2,000,000 Receipts 750,000 with 80 miles of track City to Provide		Capital, \$3,000,000 Receipts 1,000,000 with 80 miles of track City to Provide		Capital, \$5,000,000 Receipts 1,500,000 with 100 miles of track City to Provide		Capital, \$3,500,000 Receipts 1,000,000 with 100 miles of track City to Provide	
	Profit to City	City to Provide	Profit to City	City to Provide	Profit to City	City to Provide	Profit to City	City to Provide
Miller Bros.....	\$14,981	\$46,606	\$177,856	124,756	177,856	124,756	207,741	176,891
Kiely, Everett, and others.....	21,506	89,256	79,756	40,256	79,756	40,256	116,891	15,891
“ Alternative No. 2, if no cheap tickets and bonds guaranteed.....	26,506	54,256	94,756	40,256	94,756	40,256	136,891	15,891
“ Alternative No. 2, if no cheap tickets and mileage.....	36,506	29,256	109,756	40,256	109,756	40,256	136,891	15,891
Riely, Everett, Alternative No. 3, in lieu of percentage and mileage.....	41,506	74,256	124,756	40,256	124,756	40,256	176,891	15,891
Kiely, Everett, Alternative No. 3, in lieu of percentage and mileage, but bonds guaranteed.....	40,256	40,256	40,256	40,256	40,256	40,256	15,891	15,891
Kiely, Everett, Alternative No. 3, in lieu of percentage and mileage, and without cheap tickets, but with bonds guaranteed.....	45,256	55,256	55,256	55,256	55,256	55,256	35,891	35,891
Kerr, Brock, and others.....	60,256	70,256	70,256	70,256	70,256	70,256	50,891	50,891
“ Alternative No. 2, \$800 per mile, 60 per cent. of net profits.....	4,556	34,306	161,806	21,656	161,806	21,656	247,941	171,691
Kerr, Brock, Alternative No. 3, \$800 per mile, 5 per cent. of gross receipts after deducting amount received from sale of tickets at reduced fares, and 40 per cent. net profits.....	656	21,656	111,656	25,819	111,656	97,761	146,458	146,458

\* From report of City Engineer, City Solicitor and City Treasurer of Toronto, re tenders received for Street Railway property.

Schedule "A" gives the gross amounts which the city would receive under the several tenders.

Schedule "B" gives the net amount which the city would receive after providing for the maintenance of the pavement.

Though it is understood that there are some places in the United States where the street railways are required to pay to the city annually a small percentage of their gross earnings, this is not the case in any of the places visited by the undersigned, nor has he, at this date, been able to obtain any definite information in reference to such payments.

There can be no doubt that street railway systems in the large towns, when properly managed, are paying enterprises.

The opinion is now held very generally that enterprises such as street railways, water works, public lighting, etc., which, from their nature, are monopolies, and in which there cannot be general public competition, should be managed by the municipal authorities for the benefit of the general public. The public may receive the benefit either from reduced rates or by applying profits to the reduction of the general taxation.

When the public take the whole risk of such an enterprise and supply the capital to work it, it is right that they should receive the full benefit to be derived from it. On the other hand, if it is decided that it is not advisable to enter into such undertakings as public enterprises, but rather to allow them to be taken up by private companies, then, in dealing with such companies, the fact that they assume all risk and supply the necessary capital should secure for them liberal treatment at the hands of the municipal corporations.

The Toronto franchise is, no doubt, one of the most valuable in Canada, and the competition of companies who propose to take it over, on the terms fixed by the city, has been very keen; notwithstanding the great value of the

franchi  
the net  
several

In C  
overhea  
agrees t  
double  
consider  
the stree

The  
company  
portion o  
able for t

In Su  
pavement  
is used, in  
of the cos

COMPARIS

The f  
systems ha  
15 to 40 ce  
operating

(1) *Cost*—

By refe  
that the co  
same amou  
system is t  
several rea  
necessary fo

(2) *Mainten*

Mainten  
at 40 per ce  
will be gua

franchise, it appears from column I, schedule "B," that the net amount to be realized by the city, under the several tenders, is comparatively small.

In Ottawa, the new street railway company (electric overhead system) which has just gone into operation, agrees to pay to the city the sum of \$400 per annum for double track and \$300 per annum for single track, in consideration of which the corporation agrees to maintain the streets and bridges.

The arrangement in Winnipeg, under which the company pays the cost of paving and maintaining the portion of the street occupied by its tracks, is more favorable for the corporation.

In Superior, the street railway company pays for the pavement, except where power other than that of animals is used, in which case the company pays only such portion of the cost as is "made extra by reason of such track."

#### COMPARISON OF THE ELECTRIC OVERHEAD WIRE AND STORAGE BATTERY SYSTEMS.

The following remarks are intended to apply to systems having from 10 to 20 miles of track; using from 15 to 40 cars; having no grades exceeding 4 per 100, and operating in localities where snow fall is not excessive.

##### (1) *Cost*—

By referring to the estimates, page 21, it will be seen that the cost of the systems has been placed at about the same amount. The engine power provided for the storage system is the same as that for the overhead, though, for several reasons, it is probable that less power will be necessary for the storage system.

##### (2) *Maintenance*—

Maintenance of the storage batteries has been placed at 40 per cent. per annum, this being the amount which will be guaranteed by two companies, though two other

companies will guarantee the maintenance not to exceed 10 or 15 per cent.

The poles and wires occupy the same relative position in the overhead system as the batteries in the storage system. When an overhead system is once substantially erected, the cost of maintenance should not exceed 10 per cent. per annum, and for the first few years should be much less than that.

### (3) Operation—

Taking the average electrical horse power at 10 H. P. per car, and the maximum at 20 H. P. per car, on a 15 car road the total average is 150 H. P., and the total maximum 300 H. P.

By observations taken for the purpose, it has been found that the stopping, starting and changing speed of the cars makes the engine load vary rapidly between the minimum and maximum required.

Where the cars are connected directly with the central power, as in the overhead system, in the case stated above, the engine load may vary in a few moments time from 50 to 100 H. P., in addition to the strain upon the machinery and the consequent increased cost for maintenance, this condition requires that the engines be capable of taking up their maximum load at a moments notice, and this means that the steam pressure must be kept at or near the maximum, or in other words, the coal consumption must be always at its maximum.

On the other hand, the storage cars are independent units, each carrying its quantity of power for a fixed time and using it at the minimum or maximum rate as occasion requires.

The engines at the central station are, therefore, run at a constant rate, which rate is the average and not the maximum necessary to move the cars on the line. Placing the electrical efficiency of the storage battery at 80 per cent. and of the overhead wire at 90 per cent. the follow-

ing sta  
at the

Averag

car

Maximum

ove

Loss in

wh

ma

Total E.

The

posing th

to be the

In th

giving th

always d

not much

move the

Placin

H. P. per

to run 1

engine co

show a sa

per day.

In tak

overhead s

cars will n

for instanc

have any o

It has b

the cost of

the same, s

The cos

10 per cent

difference in

be \$20.54.

ing statement will show the difference in power required at the central station.

	Storage.	Overhead.
Average electrical H. P. required at car motors.....	150	150
Maximum in storage battery and overhead wire.....	150	300
Loss in batteries and overhead wires when engines are working at maximum .....	37.5	33
Total E. H. P. required.....	187.50	333

The above shows the difference in the systems, supposing the efficiency of the engines, generators and motors to be the same in each case.

In this statement all the cars on both systems are giving the same constant efficiency, in practice this is not always done, the E. H. P. for many overhead lines being not much, if any, above the average power required to move the cars.

Placing the maximum E. H. P. at 15 instead of 20 E. H. P. per car for the overhead system—supposing the cars to run 17 hours per day, with coal at \$8 per ton and engine consumption at 3lb per H. P. hour—this would show a saving in favor of the storage battery of \$12.75 per day.

In taking 15 H. P. per car as the maximum for the overhead system, it is evident that at times the individual cars will not be as efficient as those of the storage system, for instance when a number of the cars are started, or have any other heavy work to do at the same time.

It has been seen that for 15 cars and 10 miles of track the cost of storage batteries and overhead wires is about the same, say \$25,000 each.

The cost of maintenance of the overhead wires being 10 per cent., and of the storage batteries 40 per cent., the difference in favor of the overhead system per day would be \$20.54.

In the case of the storage battery, the extra weight carried by the cars, from  $1\frac{1}{2}$  to 2 tons each, should also be taken into consideration.

A road, not too long, with a very heavy traffic affords the best opportunity for economically working the overhead system; and a straggling road, with a comparatively light traffic, affords the most favorable conditions for the storage system.

Winnipeg, at present, more nearly approaches the latter condition.

From the point of view of the street railway companies there does not appear to be much to choose between the two systems, the difference at present being in favor of the overhead system.

From the standpoint of the public, the storage system is to be preferred on account of poles and wires not being required in the street.

While it is not expected that any great inconvenience would be experienced from properly erected poles and wires, their absence is undoubtedly sufficient to turn the scale in favor of the storage system.

It should be remembered that the overhead system has probably reached its maximum efficiency while the storage system, though so nearly approaching the overhead system, has not by any means done so.

H. N. RUTTAN,  
*City Engineer.*

Comparative Cost of Operating Various Street Railways.

	1	2	3	4	5	A	B	C	D	E
Average number of Motor Cars per day	15.18	7.2	6.1	1.1	3.26					
Average number of Trail Cars per day	10.67	2.2	1.1	.71						
Average number of Hours per car per day	14.21	7.4	1.8							
Electro-Motive Force								6	15	15



COMPARATIVE COST OF CONSTRUCTION, ELECTRIC OVERHEAD  
AND STORAGE SYSTEMS FOR TEN MILES TRACK AND  
FIFTEEN CARS.

	Overhead.	Storage
15 Cars complete with Motors and Batteries . . . . .	\$75,000	\$99,000
Power Plant . . . . .	10,000	10,000
Electric Plant . . . . .	8,000	8,000
Overhead System . . . . .	25,000	.....
Shifting Apparatus . . . . .	.....	2,000
Buildings, Land, etc . . . . .	12,000	12,000
10 miles Track . . . . .	70,000	70,000
	<hr/>	<hr/>
	\$200,000	\$201,000

WEIGHT PER HORSE-POWER-HOUR OF VARIOUS SECONDARY  
BATTERIES, BY MR. D. FITZ-GERALD.

Name of Battery.	lbs.	Authority.
Planté . . . . .	396	Reynier.
Faure { . . . . .	88	Faure.
{ . . . . .	165	Sir W. Thompson.
Faure, Old Model . . . . .	198	} Reynier.
“ New Model . . . . .	134	
	133	Prospectus.
E. P. S. L. Plates . . . . .	110	Reckengaun.
“ S. “ . . . . .	135	Fitz-Gerald.
Reynier { Zine Positive . . . . .	53.4	R. Taurine.
{ Planté Form.		
Lithanode Battery, Old Form . .	34.5	Fitz-Gerald.
“ “ ‘Union’ Cell	31.5	G. Forbes.

Boston  
Compa  
Constru  
Dubuq  
Franch  
“  
“  
Julian S  
Kind of  
New Yo  
Operatio  
Overhea  
“  
Snow on  
Storage S  
Track . .  
Toronto S  
Washingt  
West End  
“ “  
Weight S

## INDEX.

Boston .....	9
Comparison Overhead and Storage Systems .....	17
Construction, Comparative Cost of .....	22
Dubuque Street Railway—Storage ..	6
Franchises, Value of .....	12
"    Toronto .....	12
"    Ottawa .....	17
Julian System, New York .....	8
Kind of Tracks Recommended .....	5
New York Julian System Stopped, Reasons .....	8
Operation, Comparative Cost of, Various Railways ..	21
Overhead System and Tracks .....	4
"    "    Comparison with Storage .....	17
Snow on Electric Railways .....	11
Storage System, Comparison with Overhead .....	17
Track .....	4
Toronto Street Railway, Tenders for .....	14
Washington Street Railway—Storage .....	7
West End Street Railway, Boston .....	9
"    "    "    "    Cars and Mileage .....	10
Weight Storage Batteries .....	22



